

LED bulb 16891 230V 6W 600lm G9 330° IP20 840

Product code 16891

Supply voltage 230V
Output 6W
Luminous flux 600lumens
Luminaire's efficiency lm79 100W
Correlated colour temperature pure white 4000K
Lens angle 330
Socket G9
Cri 80
Protection class IP20
Lifespan 10000h
Length 72.0mm
Diameter 21.0mm
Weight 20g
In package 1pc
In box 200pcs
No. of switches 1000pcs
Work environment indoor use



LED bulb 16980 230V 6W 600lm G9 330° IP20 830

Product code 16980

Supply voltage 230V
Output 6W
Luminous flux 600lumens
Luminaire's efficiency lm79 100W
Correlated colour temperature warm white 3000K
Lens angle 330
Socket G9
Cri 80
Protection class IP20
Lifespan 10000h
Length 72.0mm
Diameter 21.0mm
Weight 20g
In package 1pc
In box 200pcs
No. of switches 1000pcs
Work environment indoor use



LED bulb 5050 24SMD 230V 4W 300lm G9 360° 3000K warm white

Product code 13162

Supply voltage 230V
Output 4W
Luminous flux 300lumens
Luminaire's efficiency lm79 75W
Correlated colour temperature warm white 3000K
Lens angle 360
Socket G9
Lifespan 50000h
Height 66.0mm
Diameter 32.0mm
Certificates CE, RoHS



LED bulb A5 G45B 230V 3W 225lm E27 280° IP20 830

Product code 14082

Equivalent 25W regular bulb
Supply voltage 230V
Output 3W
Electric current 30mA
Luminous flux 225lumens
Luminaire's efficiency lm79 75W
Correlated colour temperature warm white 3000K
Lens angle 280
Socket E27
Cri 80
Protection class IP20
Lifespan 25000h
Height 82.0mm
Diameter 45.0mm
In package 5pcs
In box 50pcs
Casing material aluminum + plastic
Polishing matt
No. of switches 12500pcs
Work environment indoor use
Operation temperature -10°C-40°C
Certificates CE,TUV-GS,RoHS



LED bulb A5S A60B with motion sensor 230V 6W 450lm E27 280° IP20 830

Product code 14064

Equivalent 45W regular bulb
Supply voltage 230V
Output 6W
Luminous flux 450lumens
Luminaire's efficiency lm79 75W
Correlated colour temperature warm white 3000K
Lens angle 280°
Socket E27
Cri 80
Protection class IP20
Lifespan 25000h
Height 113.0mm
Diameter 60.0mm
In package 5pcs
In box 50pcs
Casing material aluminum + plastic
Polishing matt
No. of switches 12500pcs
Work environment indoor use
Operation temperature -10°C-40°C
Certificates CE

Description: Installation height is 3-5 m; Light can be induced by under 10 lux; Human infrared induction in 6m; Induction angle of 120 degrees; Induction delays 60 seconds



LED bulb AR111 bulb + driver 230V 18W 1900lm 36° IP20 930

Product code 14901

Supply voltage 230V
Output 18W
Luminous flux 1900lumens
Luminaire's efficiency lm79 106W
Correlated colour temperature warm white 3000K
Lens angle 36°
Cri 90
Protection class IP20
Lifespan 50000h
Height 60.0mm
Diameter 111.0mm
Casing material aluminum
Power supply [PHILIPS](#)
Work environment indoor use
Certificates CE, RoHS



LED bulb G45 230V 1W 70lm E27 320° 827

Product code 15740

Supply voltage 230V
Output 1W
Luminous flux 70lumens
Luminaire's efficiency lm79 70W
Correlated colour temperature warm
white 2700K
Lens angle 320
Socket E27
Cri 80
Lifespan 25000h
Height 69.0mm
Diameter 45.0mm
No. of switches 12500pcs
Work environment indoor / outdoor
use
Certificates CE,RoHS



LED bulb G45 230V 1W CRI80 E27 320° blue

Product code 15738

Supply voltage 230V
Output 1W
Correlated colour temperature blue
blue
Lens angle 320
Socket E27
Cri 80
Lifespan 25000h
Height 69.0mm
Diameter 45.0mm
No. of switches 12500pcs
Work environment indoor / outdoor
use
Certificates CE,RoHS



LED bulb G45 230V 1W CRI80 E27 320° green

Product code 15737

Supply voltage 230V
Output 1W
Correlated colour temperature green
green
Lens angle 320
Socket E27
Cri 80
Lifespan 25000h
Height 69.0mm
Diameter 45.0mm
No. of switches 12500pcs
Work environment indoor / outdoor
use
Certificates CE,RoHS



LED bulb G45 230V 1W CRI80 E27 320° red

Product code 15736

Supply voltage 230V
Output 1W
Correlated colour temperature red red
Lens angle 320
Socket E27
Cri 80
Lifespan 25000h
Height 69.0mm
Diameter 45.0mm
No. of switches 12500pcs
Work environment indoor / outdoor
use
Certificates CE,RoHS



LED bulb G45 230V 1W CRI80 E27 320° yellow

Product code 15739

Supply voltage 230V
Output 1W
Correlated colour temperature yellow
yellow
Lens angle 320
Socket E27
Cri 80
Lifespan 25000h
Height 69.0mm
Diameter 45.0mm
No. of switches 12500pcs
Work environment indoor / outdoor
use
Certificates CE,RoHS



LED bulb G9 3528 12SMD 230V 2W 140lm 120° 3200K warm white

Product code 13261

Supply voltage 230V
Output 2W
Luminous flux 140lumens
Luminaire's efficiency lm79 70W
Correlated colour temperature warm
white 3200K
Lens angle 120
Height 51.0mm
Diameter 22.0mm



LED bulb LED INSERT white round 230V 6.5W 600lm 120° IP20 830

Product code 16930

Supply voltage 230V
Output 6.5W
Luminous flux 600lumens
Luminaire's efficiency lm79 92W
Correlated colour temperature warm white 3000K
Lens angle 120
Cri 80
Sdcm - macadam ellipses 6
Protection class IP20
Lifespan 10000h
Height 24.0mm
Diameter 50.0mm
Casing colour white
Casing material ceramic
Shape round
No. of switches 10000pcs
Work environment indoor use
Certificates CE



LED bulb LED PAR20 230V 8W 600lm E27 35° 830

Product code 14252

Equivalent 60W regular bulb
Supply voltage 230V
Output 8W
Electric current 80mA
Luminous flux 600lumens
Luminaire's efficiency lm79 75W
Correlated colour temperature warm white 3000K
Lens angle 35
Socket E27
Cri 80
Lifespan 15000h
Height 90.5mm
Width 63.0mm
In package 1pc
In box 50pcs
Casing material aluminum + plastic
No. of switches 12500pcs
Work environment indoor use
Operation temperature -10~+45°C
Certificates CE, RoHS



LED bulb MR16 A5 12V 3W 225lm GU5.3 120° 830

Product code 14022

Equivalent 25W regular bulb
Supply voltage 12V
Output 3W
Electric current 30mA
Luminous flux 225lumens
Luminaire's efficiency lm79 75W
Correlated colour temperature warm
white 3000K
Lens angle 120
Socket GU5.3
Cri 80
Lifespan 25000h
Height 52.5mm
Diameter 50.0mm
In package 5pcs
In box 50pcs
Casing material aluminum + plastic
No. of switches 12500pcs
Work environment indoor use
Operation temperature -10°C-40°C
Certificates CE,RoHS,TUV-GS



LED bulb MR16 A5 12V 6W 540lm GU5.3 120° 830

Product code 14313

Equivalent 40W regular bulb
Supply voltage 12V
Output 6W
Electric current 60mA
Luminous flux 540lumens
Luminaire's efficiency lm79 90W
Correlated colour temperature warm
white 3000K
Lens angle 120
Socket GU5.3
Cri 80
Lifespan 25000h
Height 52.0mm
Diameter 50.0mm
Casing material plastic
No. of switches 12500pcs
Work environment indoor use
Certificates CE,RoHS



LED bulb MR16 A5 230V 3W 240lm GU10 120° 830

Product code 14118

Equivalent 20W regular bulb
Supply voltage 230V
Output 3W
Electric current 30mA
Luminous flux 240lumens
Luminaire's efficiency lm79 80W
Correlated colour temperature warm white 3000K
Lens angle 120
Socket GU10
Cri 80
Lifespan 25000h
Height 51.0mm
Diameter 50.0mm
In package 5pcs
In box 50pcs
Casing material aluminum + plastic
No. of switches 12500pcs
Work environment indoor use
Operation temperature -10~+40°C
Certificates CE,RoHS,TUV-GS



LED bulb MR16 A5 230V 4W 260lm GU10 120° 865

Product code 14128

Equivalent 25W regular bulb
Supply voltage 230V
Output 4W
Electric current 50mA
Luminous flux 260lumens
Luminaire's efficiency lm79 65W
Correlated colour temperature cold white 6500K
Lens angle 120
Socket GU10
Cri 80
Lifespan 25000h
Height 51.0mm
Diameter 50.0mm
In package 5pcs
In box 50pcs
Casing material aluminum + plastic
Polishing matt
No. of switches 12500pcs
Work environment indoor use
Operation temperature -10~+40°C
Certificates CE,RoHS,TUV-GS



LED bulb MR16 A5 230V 8W 600lm GU10 120° 864

Product code 16504

Equivalent 20W regular bulb
Supply voltage 230V
Output 8W
Electric current 30mA
Luminous flux 600lumens
Luminaire's efficiency lm79 75W
Correlated colour temperature cold white 6400K
Lens angle 120
Socket GU10
Cri 80
Lifespan 25000h
Height 55.0mm
Diameter 50.0mm
In package 5pcs
In box 50pcs
Casing material aluminum + plastic
No. of switches 12500pcs
Work environment indoor use
Operation temperature -10~+40°C
Certificates CE,RoHS,TUV-GS



LED bulb MR16 A5 COB 12V 6W 300lm GU5.3 30° 830

Product code 14030

Equivalent 30W regular bulb
Supply voltage 12V
Output 6W
Luminous flux 300lumens
Luminaire's efficiency lm79 50W
Correlated colour temperature warm white 3000K
Lens angle 30
Socket GU5.3
Cri 80
Lifespan 25000h
Height 52.5mm
Diameter 50.0mm
In package 5pcs
In box 50pcs
Casing material aluminum + plastic
No. of switches 12500pcs
Work environment indoor use
Operation temperature -10°C-40°C
Certificates CE



LED bulb PREMIUM MB white 230V 7W 560lm E27 200° 830

Product code 16166

Brand PREMIUM
Supply voltage 230V
Output 7W
Luminous flux 560lumens
Luminaire's efficiency lm79 80W
Correlated colour temperature warm
white 3000K
Lens angle 200
Socket E27
Cri 80
Lifespan 30000h
Height 85.0mm
Diameter 45.0mm
Weight 20g
In package 1pc
In box 100pcs
Casing colour white
Casing material ceramic
No. of switches 20000pcs
Certificates CE, RohS



LED bulb PREMIUM MB white 230V 9W 900lm E14 200° 830

Product code 15433

Brand PREMIUM
Supply voltage 230V
Output 9W
Luminous flux 900lumens
Luminaire's efficiency lm79 100W
Correlated colour temperature warm
white 3000K
Lens angle 200
Socket E14
Cri 80
Lifespan 30000h
Height 90.0mm
Diameter 45.0mm
In package 1pc
In box 100pcs
Casing colour white
Casing material ceramic
No. of switches 20000pcs
Certificates CE, RohS



LED bulb PREMIUM MB white 230V 9W 900lm E14 200° 840

Product code 15434

Brand PREMIUM
Supply voltage 230V
Output 9W
Luminous flux 900lumens
Luminaire's efficiency lm79 100W
Correlated colour temperature pure
white 4000K
Lens angle 200
Socket E14
Cri 80
Lifespan 30000h
Height 90.0mm
Diameter 45.0mm
In package 1pc
In box 100pcs
Casing colour white
Casing material ceramic
No. of switches 20000pcs
Certificates CE, RohS



LED bulb PREMIUM MB white 230V 9W 900lm E27 200° 830

Product code 15430

Brand PREMIUM
Supply voltage 230V
Output 9W
Luminous flux 900lumens
Luminaire's efficiency lm79 100W
Correlated colour temperature warm
white 3000K
Lens angle 200
Socket E27
Cri 80
Lifespan 30000h
Height 85.0mm
Diameter 45.0mm
In package 1pc
In box 100pcs
Casing colour white
Casing material ceramic
No. of switches 20000pcs
Certificates CE, RohS



LED bulb PREMIUM MB white 230V 9W 900lm E27 200° 840

Product code 15431

Brand PREMIUM
Supply voltage 230V
Output 9W
Luminous flux 900lumens
Luminaire's efficiency lm79 100W
Correlated colour temperature pure white 4000K
Lens angle 200
Socket E27
Cri 80
Lifespan 30000h
Height 85.0mm
Diameter 45.0mm
In package 1pc
In box 100pcs
Casing colour white
Casing material ceramic
No. of switches 20000pcs
Certificates CE, RohS



LED bulb PREMIUM SW candle white 230V 9W 900lm E14 200° 830

Product code 15435

Brand PREMIUM
Supply voltage 230V
Output 9W
Luminous flux 900lumens
Luminaire's efficiency lm79 100W
Correlated colour temperature warm white 3000K
Lens angle 200
Socket E14
Cri 80
Lifespan 30000h
Height 90.0mm
Diameter 45.0mm
In package 1pc
In box 100pcs
Casing colour white
Casing material ceramic
No. of switches 20000pcs
Certificates CE, RohS



LED bulb PREMIUM SW candle white 230V 9W 900lm E14 200° 840

Product code 15436

Brand PREMIUM
Supply voltage 230V
Output 9W
Luminous flux 900lumens
Luminaire's efficiency lm79 100W
Correlated colour temperature pure
white 4000K
Lens angle 200
Socket E14
Cri 80
Lifespan 30000h
Height 90.0mm
Diameter 45.0mm
In package 1pc
In box 100pcs
Casing colour white
Casing material ceramic
No. of switches 20000pcs
Certificates CE, RohS



LED bulb PREMIUM SW candle white 230V 9W 900lm E27 200° 830

Product code 15437

Brand PREMIUM
Supply voltage 230V
Output 9W
Luminous flux 900lumens
Luminaire's efficiency lm79 100W
Correlated colour temperature warm
white 3000K
Lens angle 200
Socket E27
Cri 80
Lifespan 30000h
Height 37.0mm
Diameter 110.0mm
In package 1pc
In box 100pcs
Casing colour white
Casing material ceramic
No. of switches 20000pcs
Certificates CE, RohS



LED bulb PREMIUM SW candle white 230V 9W 900lm E27 200° 840

Product code 15438

Brand PREMIUM
Supply voltage 230V
Output 9W
Luminous flux 900lumens
Luminaire's efficiency lm79 100W
Correlated colour temperature pure
white 4000K
Lens angle 200
Socket E27
Cri 80
Lifespan 30000h
Height 37.0mm
Diameter 110.0mm
In package 1pc
In box 100pcs
Casing colour white
Casing material ceramic
No. of switches 20000pcs
Certificates CE, RohS



LED bulb R50 230V 5W 360lm E14 120° IP20 830

Product code 16330

Supply voltage 230V
Output 5W
Luminous flux 360lumens
Luminaire's efficiency lm79 72W
Correlated colour temperature warm
white 3000K
Lens angle 120
Socket E14
Cri 80
Protection class IP20
Lifespan 10000h
Height 85.0mm
Diameter 50.0mm
Weight 30g
In package 1pc
In box 100pcs
No. of switches 10000pcs
Work environment indoor use
Operation temperature -20°C~40°C
Certificates CE,RoHS



LED bulb REVAL BULB Summer Star 24V 8W 400lm CRI90 30° IP20 RGB + 2700K RGBW warm

Product code 16189

Brand [REVAL BULB](#)
Supply voltage 24V
Output 8W
Luminous flux 400lumens
Luminaire's efficiency lm79 50W
Correlated colour temperature RGBW
warm RGB + 2700K
Lens angle 30
Cri 90
Protection class IP20
Lifespan 35000h
Height 52.0mm
Diameter 49.0mm
Casing material aluminum
Work environment indoor use
Certificates CE



LED bulb Samsung 3W 210lm E14 170° IP20 3000K warm white

Product code 12194

Output 3W
Luminous flux 210lumens
Luminaire's efficiency lm79 70W
Correlated colour temperature warm
white 3000K
Lens angle 170
Socket E14
Protection class IP20



LED bulb Star Trading 344-04-1 230V 2.5W 290lm G9 IP20 827

Product code 16381

Brand [Star Trading](#)

Supply voltage 230V

Output 2.5W

Luminous flux 290lumens

Luminaire's efficiency lm79 116W

Correlated colour temperature warm
white 2700K

Socket G9

Cri 80

Sdcm - macadam ellipses 4

Protection class IP20

Lifespan 25000h

Length 42.0mm

Diameter 16.0mm

In package 10pcs

No. of switches 12500pcs

Work environment indoor use

Operation temperature -20 ~ 40°C



LED bulb Star Trading 344-09-3 230V 3.8W 410lm G9 IP20 840

Product code 17083 TRIAC dimmable

Brand [Star Trading](#)

Supply voltage 230V

Dimmable TRIAC

Output 3.8W

Luminous flux 410lumens

Luminaire's efficiency lm79 108W

Correlated colour temperature pure
white 4000K

Socket G9

Cri 80

Sdcm - macadam ellipses 6

Protection class IP20

Lifespan 25000h

Length 52.5mm

Diameter 17.4mm

In package 10pcs

No. of switches 12500pcs

Work environment indoor use

Operation temperature -20 ~ 40°C



LED bulb Star Trading 344-47 230V 5.6W 610lm G9 IP20 827

Product code 16758 TRIAC dimmable

Brand [Star Trading](#)
Supply voltage 230V
Power factor 0.91
Dimmable TRIAC
Output 5.6W
Luminous flux 610lumens
Luminaire's efficiency lm79 109W
Correlated colour temperature warm
white 2700K
Socket G9
Cri 80
Sdcm - macadam ellipses 6
Protection class IP20
Lifespan 25000h
Length 57.0mm
Diameter 18.2mm
In package 10pcs
No. of switches 12500pcs
Work environment indoor use
Operation temperature -20 ~ 40°C



LED bulb Star Trading G45 230V 1W 30lm E27 yellow

Product code 15316

Brand [Star Trading](#)
Supply voltage 230V
Output 1W
Luminous flux 30lumens
Luminaire's efficiency lm79 30W
Correlated colour temperature yellow
yellow
Socket E27
Lifespan 15000h
Height 68.0mm
Width 45.0mm
In package 1pc
In box 10pcs
No. of switches 12500pcs
Work environment indoor / outdoor
use
Operation temperature +5° - +35°C
Certificates CE,RoHS



Ideal LED lamp for lighting strips, as it consumes little power and provides cozy lighting.

LED bulb Star Trading Sauna A60 358-50 230V 4.5W 470lm E27 IP20 2700K warm white

Product code 16675

Equivalent 40W regular bulb

Brand [Star Trading](#)

Supply voltage 230V

Output 4.5W

Luminous flux 470lumens

Luminaire's efficiency lm79 104W

Correlated colour temperature warm white 2700K

Socket E27

Sdcm - macadam ellipses 6

Protection class IP20

Lifespan 15000h

Height 11.0mm

Diameter 6.0mm

In package 1pc

In box 10pcs

No. of switches 12500pcs

Work environment indoor / outdoor use

Operation temperature -30° - +60°C

Certificates CE,RoHS

