

Signal amplifier 4x6A 12-24V 576W IP20

Product code 15587

Supply voltage 12-24V
Output 576W
Electric current 24000mA
Protection class IP20
Height 24.0mm
Width 55.0mm
Length 65.0mm
Weight 100g
Casing material aluminum
Work environment indoor use
Certificates CE
Warranty 2 years



Signal amplifier LTECH LT-122 SPI 5-36V IP67

Product code 15908

Brand LTECH
Supply voltage 5-36V
Protection class IP67
Warranty 5 years



Signal amplifier LTECH LT-3060 24A 5-24V 576W

Product code 13790

Brand LTECH
Supply voltage 5-24V
Output 576W
Electric current 24000mA
Height 23.0mm
Width 87.0mm
Length 148.0mm
Weight 380g
Operation temperature -30°C~65°C
Certificates CE, RoHS
Warranty 3 years



Signal amplifier SKYDANCE EV3 3x6A 12-36V 648W IP20

Product code 16454

Brand [SKYDANCE](#)

Supply voltage 12-36V

Output 648W

Electric current 18000mA

Protection class IP20

Height 27.0mm

Width 45.0mm

Length 175.0mm

Weight 109g

Package weight 129g

Casing material plastic

Work environment indoor use

Operation temperature -30~55°C

Certificates CE, EMC, LVD

Warranty 5 years



Signal amplifier SKYDANCE EV4 4x5A 12-24V IP20

Product code 16968

Brand [SKYDANCE](#)

Supply voltage 12-24V

Maximum output 480W/1m

Electric current 20000mA

Protection class IP20

Height 27.0mm

Width 45.0mm

Length 175.0mm

Weight 120g

Package weight 140g

Casing material plastic

Work environment indoor use

Operation temperature -30~55°C

Certificates CE

Warranty 5 years



Signal amplifier SKYDANCE EV4-X 4x8A 12-24V IP20

Product code 16967

Brand [SKYDANCE](#)

Supply voltage 12-24V

Maximum output 768W/1m

Electric current 32000mA

Protection class IP20

Height 24.5mm

Width 76.0mm

Length 107.0mm

Weight 267g

Package weight 287g

Casing material aluminum

Work environment indoor use

Operation temperature -30~55°C

Certificates CE

Warranty 5 years



Signal amplifier SKYDANCE SPI SA 5-24V IP20

Product code 15831 RF dimmable

Brand [SKYDANCE](#)

Supply voltage 5-24V

Dimmable RF

Protection class IP20

Height 26.0mm

Width 52.0mm

Length 52.0mm

In package 1pc

Work environment indoor use

Operation temperature -30~55°C

Certificates CE

Warranty 5 years

