

LED driver 1750mA 20-34V LPF-60-1750 230V 60W IP67

Product code 13291

Supply voltage 230V
Output voltage 20-34V
Output 60W
Maximum output 60W/1m
Electric current 1750mA
Protection class IP67
Height 32.0mm
Width 42.0mm
Length 163.0mm
Weight 399g
Package weight 426g
Casing material plastic
Work environment indoor use
Certificates CE, RoHS



LED driver 3000mA 30-42V LW-FL100W silvery 230V 100W IP67

Product code 14107

Supply voltage 230V
Output voltage 30-42V
Output 100W
Electric current 3000mA
Protection class IP67
Height 45.0mm
Width 70.0mm
Length 164.0mm
Casing colour silvery
Casing material aluminum
Work environment outdoor use
Warranty 2 years



LED driver 300mA 40-50V ELF-15-50 230V 15W IP67

Product code 13293

Supply voltage 230V
Output voltage 40-50V
Output 15W
Electric current 300mA
Protection class IP67
Height 27.0mm
Width 37.0mm
Length 78.0mm
Casing material aluminum
Certificates CE
Warranty 2 years



LED driver 350mA 66-110V LPF-35-350 230V 35W IP67

Product code 12909

Supply voltage 230V
Output voltage 66-110V
Output 35W
Electric current 350mA
Protection class IP67
Height 28.0mm
Width 41.0mm
Length 147.0mm
Weight 227g
Package weight 250g
Casing material plastic
Work environment outdoor use
Certificates CE, RoHS



LED driver 950mA 25-40v PAN-TRAND 40W IP20

Product code 15167 TRIAC dimmable

Dimmable TRIAC
Output 40W
Protection class IP20



LED driver BOKE 1200mA 28-42V 230V 50W IP20

Product code 17161

Brand [BOKE](#)
Supply voltage 230V
Output voltage 28-42V
Output 50W
Maximum output 50W/1m
Electric current 1200mA
Protection class IP20
Lifespan 100000h
Height 29.0mm
Width 45.0mm
Length 135.0mm
Casing material plastic
Power supply [BOKE](#)
Work environment indoor use
Operation temperature -20 - 60°C
Warranty 5 years



LED driver BOKE 300-500mA 28-42V 230V 21W IP20

Product code 17159

Brand [BOKE](#)
Supply voltage 230V
Output voltage 28-42V
Output 21W
Maximum output 21W/1m
Electric current 500mA
Protection class IP20
Lifespan 100000h
Height 28.0mm
Width 45.0mm
Length 117.0mm
Casing material plastic
Power supply [BOKE](#)
Work environment indoor use
Operation temperature -20 - 60°C
Warranty 5 years



LED driver BOKE 500-1100mA 28-42V 230V 42W IP20

Product code 17160

Brand [BOKE](#)

Supply voltage 230V

Output voltage 28-42V

Output 42W

Maximum output 42W/1m

Electric current 1100mA

Protection class IP20

Lifespan 100000h

Height 28.0mm

Width 45.0mm

Length 117.0mm

Casing material plastic

Power supply [BOKE](#)

Work environment indoor use

Operation temperature -20 - 60°C

Warranty 5 years



LED driver BOKE 600-1100mA 3-42V DALI, PUSH 230V 42W IP20

**Product code 16015 DALI / PUSH
dimmable**

Brand [BOKE](#)

Supply voltage 230V

Dimmable DALI / PUSH

Output voltage 3-42V

Output 42W

Maximum output 42W/1m

Electric current 1100mA

Protection class IP20

Lifespan 50000h

Weight 170g

Casing material plastic

Power supply [BOKE](#)

Work environment indoor use

Operation temperature -20 - +45°C

Warranty 5 years



LED driver EMOS 200-350mA 25-40V, TRIAC 230V 14W IP20

Product code 16645 TRIAC dimmable

Brand [EMOS](#)

Supply voltage 230V

Dimmable TRIAC

Output voltage 25-40V

Output 14W

Maximum output 14W/1m

Electric current 350mA

Protection class IP20

Height 31.0mm

Width 46.0mm

Length 97.0mm

Weight 114g

Certificates CE

Warranty 5 years



LED driver KGP 300-1050mA 9-42V 230V 44.1W IP20

Product code 17575

Brand [KGP](#)

Supply voltage 230V

Power factor 0.95

Output voltage 9-42V

Output 44.1W

Maximum output 44.1W/1m

Electric current 1050mA

Protection class IP20

Lifespan 100000h

Height 23.0mm

Width 43.0mm

Length 131.2mm

In package 1pc

Casing material plastic

Work environment indoor use

Operation temperature -25 - +45°C

Certificates ENEC, UKCA, CE, EAC,

SAA, RoHS

Warranty 5 years



The power supply unit is designed for indoor use, and its IP20 protection class provides adequate protection against dust and small objects. It is an ideal choice for home and office spaces where a reliable and stable power source for various electronic devices is needed. By choosing a quality power supply unit from the LED house selection, you can be sure that your electronic devices are reliably and safely powered, ensuring their smooth operation and longer lifespan.

LED driver KGP LC75W 900-1800 NFC 230V 75W IP20

Product code 17556

Brand [KGP](#)

Supply voltage 230V

Power factor 0.95

Output voltage 50V

Output 75W

Electric current 1800mA

Protection class IP20

Lifespan 100000h

Height 21.0mm

Width 29.4mm

Length 280.0mm

In package 1pc

In box 20pcs

Casing material plastic

Work environment indoor use

Operation temperature -25 - +50°C

Certificates CE, RoHS, ENEC, SAA,
UKCA

Warranty 5 years



The power supply unit is designed for indoor use, and its IP20 protection class provides adequate protection against dust and small objects. It is an ideal choice for home and office spaces where a reliable and stable power source for various electronic devices is needed. By choosing a quality power supply unit from the LED house selection, you can be sure that your electronic devices are reliably and safely powered, ensuring their smooth operation and longer lifespan.

LED driver LIFUD 1000mA 27-42V LF-GDE042YF1000U DIM 0-10V 230V 42W IP20

Product code 13930 0-10V dimmable

Brand LIFUD
Supply voltage 230V
Dimmable 0-10V
Output voltage 27-42V
Output 42W
Electric current 1000mA
Protection class IP20
Height 30.0mm
Width 65.0mm
Length 140.0mm
Weight 200g
Casing material plastic
Work environment indoor use
Certificates CE, SELV, ENEC, F, M



LED driver LTECH DALI SE-12-100-400-W1DS 230V 12W IP20

Product code 16893 DALI dimmable

Brand LTECH
Supply voltage 230V
Power factor 0.85
Dimmable DALI
Output voltage 9-42V
Output 12W
Electric current 400mA
Protection class IP20
Height 20.0mm
Width 30.0mm
Length 135.0mm
Operation temperature -20 ~ 50°C
Warranty 5 years



DALI dimmable LED power supply that
can be easily reconfigured. 0.9-12W
100mA / 9-42V / 0.9-4.2W 150mA /
9-42V / 1.35-6.3W 200mA / 9-42V /
1.8-8.4W 250mA / 9-42V / 2.25-10.5W
300mA / 9-40V / 2.7-12W 350mA /
9-34V / 3.15-11.9W 400mA / 9-30V /
3.6-12W

LED driver MEAN WELL 1450mA HLG-60H-42A 230V 60W IP65

Product code 14541

Brand [MEAN WELL](#)
Supply voltage 230V
Output voltage 42V
Output 60W
Electric current 1450mA
Protection class IP65
Warranty 3 years



LED driver SKYDANCE TE-15A 230V 15W IP20

**Product code 16430 TRIAC / PUSH
dimmable**

Brand [SKYDANCE](#)
Supply voltage 230V
Dimmable TRIAC / PUSH
Output voltage 10-45V
Output 15W
Maximum output 15W/1m
Electric current 700mA
Protection class IP20
Height 30.0mm
Width 41.0mm
Length 151.0mm
Weight 106g
Package weight 123g
Work environment indoor use
Operation temperature -30~50°C
Certificates CE
Warranty 5 years



LED driver SKYDANCE TE-36A 230V 36W IP20

**Product code 16522 TRIAC / PUSH
dimmable**

Brand [SKYDANCE](#)

Supply voltage 230V

Dimmable TRIAC / PUSH

Output voltage 10-52V

Output 36W

Maximum output 36W/1m

Electric current 1200mA

Protection class IP20

Height 30.0mm

Width 44.0mm

Length 168.5mm

Work environment indoor use

Operation temperature -30~50°C

Certificates CE

Warranty 5 years

