

LED HOUSE

enlightening
spaces®



LED driver LIFUD 1500mA 27-42V LF-GDE060YF1500U DIM V white 230V 65W IP20 0-10V

Product code 14119

LF-GDE060YF 1500U

Product description Isolated LED driver designed for class II LED luminaires;
Input voltage AC100-277V for global market, max input voltage range AC90-305V;
Output power 30-65W, DC voltage range 27-42V;
Active PFC, high PF (PF>0.93@AC230V), high efficiency (up to 88%), low THD ($\leq 20\%$);
Meet the ERP and DLC standards after being installed inside finished LED lights;
Surge protection: 1KV;
0-10V, PWM and Rx dimmable version, dimming range 10%~100%;
Connecting with Lifud ZigBee convertor, it can realize ZigBee smart wireless control function;
Nominal lifetime above 50,000 hours, 5 years warranty;
Applied for panel lights, down lights, tube lights applications.
Housing properties Casing: polycarbonate, UL V-0 fireproof, white;

Warranty	5 years
Brand	LIFUD
Supply voltage	230V
Dimmable	0-10V
Output voltage	27-42V
Output	65W
Rated current	1500mA
Protection class	IP20
Lifespan	50000h
Length	193.0mm
Width	65.0mm
Height	31.0mm
Weight	280g
In package	30pcs
Casing colour	white
Casing material	plastic
Work environment	indoor use
Operation temperature	-30 °C - +50°C
Certificates	ENEC,CE,GS,CB,SAA,RCM