



**Recessed light Prolumen DL98A UGR19 white round 230V 18W 1530lm
90° IP54 930**

Product code 14493

Recessed LED luminaire for corridor lighting.

Protection class IP54 means that the luminaire is protected against normal dust and splashes from any direction - this feature makes DL98A ideal for illuminating bathrooms and other more humid spaces.

You can find this luminaire model in the LED House product range with both warm white (3000K) and daylight white (4000K) light.

High CRI level keeps the colours of illuminated areas and objects true and natural.

With proper use, the luminaire is energy-efficient, environmentally friendly, and has a very long lifespan (50,000h).

Illuminate your world with LED House professionals - [check out our project portfolio here!](#)

Correlated colour temperature	warm white 3000K
Luminous flux	1530lumens
Luminaire's efficiency lm79	85lm/W
Warranty	5 years
Brand	Prolumen
Supply voltage	230V
Power factor	0.90
Output	18W
Maximum output	18W
Lens angle	90°
Cri	90
Ugr	19
Sdcm - macadam ellipses	3
Protection class	IP54
Lifespan	50000h
Llmf tm21	L80B10 @25°C 50.000h
Height	95.0mm
Diameter	172.0mm
Installation opening diameter	146mm
Weight	351 g
Package weight	505 g
In package	1pc
In box	12pcs
Casing colour	white
Casing material	aluminium + plastic
Polishing	matt
Shape	round
Work environment	indoor use
Certificates	CE, RoHS
Eprel	2470363
Energy class	

