



## LED downlight PROLUMEN CL59-5-DALI white 230V 25W 1900lm 90° IP44 940

Product code 14927

Classic recessed LED luminaire with a round minimalist design.

From the LED House collection, you can find this luminaire model in two different light temperatures: 3000K warm white and 4000K daylight.

The IP44 protection class means that the luminaire is protected against >1.0mm dust particles and splashes from any direction. An ideal luminaire for corridors or dressing rooms.

Improve the quality of light in your evenday life and choose a ten notch lighting

Improve the quality of light in your everyday life and choose a top-notch lighting solution from <u>the LED</u> <u>house product range</u>!



| Correlated colour temperature | pure white 4000K |
|-------------------------------|------------------|
| Luminous flux                 | 1900lumens       |
| Luminaire's efficiency lm79   | 76lm/W           |
| Warranty                      | 5 years          |
| Brand                         | <b>PROLUMEN</b>  |
| Supply voltage                | 230V             |
| Power factor                  | 0.90             |
| Dimmable                      | DALI             |
| Output                        | 25W              |
| Lens angle                    | 90°              |
| Cri                           | 90               |
| Sdcm - macadam ellipses       | 6                |
| Protection class              | IP44             |
| Lifespan                      | 50000h           |
| Height                        | 45.0mm           |
| Diameter                      | 170.0mm          |
| Installation opening diameter | 140-150mm        |
| In package                    | 1pc              |
| In box                        | 12pcs            |
| Casing colour                 | white            |
| Casing material               | aluminum         |
| Work environment              | indoor use       |
| Certificates                  | CE, RoHS         |
| Eprel                         | <u>1952082</u>   |
| Energy class                  | F A<br>G         |





