



Recessed light Prolumen CL102B 2.5 white round 230V 10W 870lm 36° IP65 TRIAC 830

Product code 15080

Functional LED underlight, suitable for use in damp environments such as sauna anterooms or bathrooms.

The luminaire is recessed. It can be installed, for example, into the wall, ceiling, or countertop.

The luminaire is also available in LED House's selection with TRIAC dimming technology. The transmitted light temperature is 3000K (warm white).

With proper use, the luminaire is energy-efficient, environmentally friendly, and has a very long lifespan (50,000 hours).

Illuminate your world with LED House professionals - [check out our project portfolio here!](#)

| | |
|-------------------------------|---|
| Correlated colour temperature | warm white 3000K |
| Luminous flux | 870lumens |
| Luminaire's efficiency lm/W | 87lm/W |
| Warranty | 5 years |
| Source of light | CREE LED |
| Brand | Prolumen |
| Supply voltage | 230V |
| Power factor | 0.90 |
| Dimmable | TRIAC |
| Output | 10W |
| Maximum output | 10W |
| Lens angle | 36° |
| Cri | 80 |
| Sdcm - macadam ellipses | 6 |
| Protection class | IP65 |
| Lifespan | 50000h |
| Llmf tm21 | L80B10 @25°C 50.000h |
| Height | 40.0mm |
| Diameter | 90.0mm |
| Installation opening diameter | 74.5mm |
| In box | 50pcs |
| Casing colour | white |
| Casing material | aluminium |
| Polishing | matt |
| Shape | round |
| Work environment | indoor use |
| Certificates | CE, RoHS |
| Eprel | 1298465 |
| Energy class |  |

