



LED downlight PROLUMEN DL178-4 UGR19 white 230V 10W 1150lm 60° IP54 930

Product code 15548

Recessed LED ship light.

Recommended uses: corridors, public areas such as commercial spaces, schools, sports halls, and commercial premises.

The IP54 protection class means that the luminaire is protected against normal dust and splashes from any direction.

From the LED House range, you can find this luminaire model in two light temperatures: 3000K (warm white) and 4000K (daylight).

If you haven't found the perfect light fixture from our product range yet, then browse through the PROLUMEN catalogue as well!



Correlated colour temperature warm white 3000K

Luminous flux 1150lumens Luminaire's efficiency Im79 115lm/W Warranty 5 years **Brand PROLUMEN** Supply voltage 230V Power factor 0.90 Output 10W Lens angle 60° Cri 90 19 Ugr Sdcm - macadam ellipses 3

Protection class

Lifespan

Llmf tm21 L80B10 @25°C 50.000h

IP54

50000h

Height 78.0mm Diameter 145.0mm Installation opening diameter 120mm Weight 475g In box 18pcs Casing colour white Casing material aluminum IK06 Impact resistance Work environment indoor use

Work environment indoor use
Certificates CE, RoHS
Eprel 2024633

Energy class









