



**LED downlight PROLUMEN DL88 2,5 white round 230V 10W 780lm 24°  
IP20 TRIAC 930**


Product code 15929

LED ceiling light with deep recess and minimalist design for home or office.

You can find the DL88 model in the LED House selection with TRIAC and DALI technology, allowing users to dim and brighten the light according to their preferences. The selection includes downlights with warm white (2700K, 3000K) light.

IP20 protection class allows this light fixture to be used only in dry indoor spaces.

If you haven't found the perfect light fixture from our product range yet, then browse through the [PROLUMEN catalogue](#) as well!

|                               |                                                                                     |
|-------------------------------|-------------------------------------------------------------------------------------|
| Correlated colour temperature | warm white 3000K                                                                    |
| Luminous flux                 | 780lumens                                                                           |
| Luminaire's efficiency lm79   | 78lm/W                                                                              |
| Warranty                      | 5 years                                                                             |
| Brand                         | <a href="#">PROLUMEN</a>                                                            |
| Supply voltage                | 230V                                                                                |
| Power factor                  | 0.90                                                                                |
| Dimmable                      | TRIAC                                                                               |
| Output                        | 10W                                                                                 |
| Lens angle                    | 24°                                                                                 |
| Cri                           | 90                                                                                  |
| Sdcm - macadam ellipses       | 6                                                                                   |
| Protection class              | IP20                                                                                |
| Lifespan                      | 50000h                                                                              |
| Lmf tm21                      | L70B50 @25°C 50.000h                                                                |
| Height                        | 89.0mm                                                                              |
| Diameter                      | 85.0mm                                                                              |
| Installation opening diameter | 68mm                                                                                |
| In package                    | 1pc                                                                                 |
| In box                        | 24pcs                                                                               |
| Casing colour                 | white                                                                               |
| Casing material               | aluminum                                                                            |
| Polishing                     | matt                                                                                |
| Shape                         | round                                                                               |
| Work environment              | indoor use                                                                          |
| Eprel                         | <a href="#">1403539</a>                                                             |
| Energy class                  |  |

