



Recessed light Prolumen DL98A UGR19 black 230V 25W 2500lm 90° IP54 840

Product code 16097

Recessed LED luminaire. Ideal also for more humid spaces!


This luminaire is suitable for example in shopping centers, bedrooms, conference rooms, classrooms, living rooms, kitchens, bathrooms, and many other spaces.

Protection class IP54 means that the luminaire is protected against normal dust and splashes from any direction - this feature makes DL98 ideal for illuminating bathrooms and other more humid spaces.

You can find this luminaire model in the LED House product range with both warm white (3000K) and daylight white (4000K) light.

With proper use, the luminaire is energy-efficient, environmentally friendly, and has a very long lifespan (50,000h).

Illuminate your world with LED House professionals - [check out our project portfolio here!](#)

| | |
|-------------------------------|---|
| Correlated colour temperature | pure white 4000K |
| Luminous flux | 2500lumens |
| Luminaire's efficiency lm79 | 100lm/W |
| Warranty | 5 years |
| Brand | Prolumen |
| Supply voltage | 230V |
| Output | 25W |
| Maximum output | 25W |
| Lens angle | 90° |
| Cri | 80 |
| Ugr | 19 |
| Sdcm - macadam ellipses | 5 |
| Protection class | IP54 |
| Lifespan | 40000h |
| Lmf tm21 | L80B10 @25°C 50.000h |
| Height | 98.0mm |
| Diameter | 228.0mm |
| Installation opening diameter | 200mm |
| Weight | 351g |
| Package weight | 505g |
| In package | 12pcs |
| In box | 1pc |
| Casing colour | black |
| Casing material | aluminium + plastic |
| Work environment | indoor use |
| Certificates | CE,RoHS |
| Energy class |  |

