



Modular light Prolumen 600x600 Backlit UGR<19 h34 230V 36W 4320lm 90° IP20 840

Product code 16352

High quality modular luminaire, ideal for spaces such as offices and corridors.

The PROLUMEN ceiling panel luminaire stands out due to its low UGR value, long lifespan, and adaptable installation and maintenance methods.

The driver of this luminaire is external - this feature simplifies installation and maintenance by allowing easier access.

The luminaire is designed to be as eye-friendly as possible. In addition to a high UGR value, the Backlit panel is flicker-free. The high lumen output ensures that surfaces are covered with quality and sufficient light.

Improve the quality of light in your everyday life and choose a top-notch lighting solution from [the LED house product range!](#)

Correlated colour temperature	pure white 4000K
Luminous flux	4320lumens
Luminaire's efficiency lm79	120lm/W
Warranty	5 years
Power supply	BOKE
Brand	Prolumen
Supply voltage	230V
Power factor	0.90
Output	36W
Maximum output	36W
Lens angle	90°
Cri	80
Ugr	19
Sdcm - macadam ellipses	3
Protection class	IP20
Lifespan	50000h
Lmf tm21	L80B10 @25°C 50.000h
Length	595.0mm
Width	595.0mm
Height	34.0mm
Weight	1.6 kg
Package weight	2.15 kg
In package	1pc
In box	6pcs
Casing material	aluminium
Polishing	matt
No. of switches	25000times
Work environment	indoor use
Operation temperature	-10 ~ 40°C
Certificates	CE, RoHS
Eprel	1282703
Energy class	

