



Modular light PROLUMEN 600x600 Backlit UGR<19 h34 230V 36W 4320lm 120° IP20 840

Product code 16352

High quality modular luminaire, ideal for spaces such as offices and corridors.

The PROLUMEN ceiling panel luminaire stands out due to its low UGR value, long lifespan, and adaptable installation and maintenance methods.

The driver of this luminaire is external - this feature simplifies installation and maintenance by allowing easier access.

The luminaire is designed to be as eye-friendly as possible. In addition to a high UGR value, the Backlit panel is flicker-free. The high lumen output ensures that surfaces are covered with quality and sufficient light.

Improve the quality of light in your everyday life and choose a top-notch lighting solution from <u>the LED</u> house product range!



Correlated colour temperature pure white 4000K

Luminous flux 4320lumens Luminaire's efficiency Im79 120lm/W Warranty 5 years Power supply **BOKE** Brand **Prolumen** Supply voltage 230V Power factor 0.90 Output 36W Maximum output 36W Lens angle 120° Cri 80 Ugr 19 Sdcm - macadam ellipses 3

Llmf tm21 L80B10 @25°C 50.000h

IP20

50000h

Length 595.0mm Width 595.0mm Height 34.0mm Weight 1600g Package weight 2150g In package 1pc In box 6pcs Casing material aluminium Polishing matt

No. of switches 25000times Work environment indoor use Operation temperature $-10 \sim 40^{\circ}\text{C}$ Certificates CE, RoHS Eprel 1282703

Energy class

Protection class

Lifespan









