



LED downlight PROLUMEN DL98A UGR19 TRIAC white round 230V 18W 1530lm 90° IP54 930

Product code 16802

Recessed LED luminaire for corridor lighting.


Protection class IP54 means that the luminaire is protected against normal dust and splashes from any direction - this feature makes DL98A ideal for illuminating bathrooms and other more humid spaces.

You can find this luminaire model in the LED House product range with both warm white (3000K) and daylight white (4000K) light.

High CRI level keeps the colours of illuminated areas and objects true and natural.

With proper use, the luminaire is energy-efficient, environmentally friendly, and has a very long lifespan (50,000h).

Illuminate your world with LED House professionals - [check out our project portfolio here!](#)

| | |
|-------------------------------|-------------------------------------------------------------------------------------|
| Correlated colour temperature | warm white 3000K |
| Luminous flux | 1530lumens |
| Luminaire's efficiency lm79 | 85lm/W |
| Warranty | 5 years |
| Brand | PROLUMEN |
| Supply voltage | 230V |
| Dimmable | TRIAC |
| Output | 18W |
| Lens angle | 90° |
| Cri | 90 |
| Ugr | 19 |
| Protection class | IP54 |
| Lifespan | 50000h |
| Lmf tm21 | L80B10 @25°C 50.000h |
| Height | 95.0mm |
| Diameter | 172.0mm |
| Installation opening diameter | 146mm |
| Weight | 351g |
| Package weight | 505g |
| In package | 1pc |
| In box | 12pcs |
| Casing colour | white |
| Casing material | aluminum + plastic |
| Polishing | matt |
| Shape | round |
| Work environment | indoor use |
| Certificates | CE, RoHS |
| Energy class |  |