



## **LED luminaire Prolumen Barrett 1500 UP/DOWN black 230V 60W 5300lm 65° IP20 DALI 930**

Product code 17043

Linear workplace luminaire. High quality, easy to install, and long-lasting (50000h)!

This luminaire with IP20 protection class is an ideal choice for home or office environments.

There is also a model with DALI dimmer available. This technology allows adjusting the brightness of the luminaire according to needs.

This luminaire has an ideal color rendering index CRI90 for workspaces and offices. The model offers light temperatures ranging from warm white light (3000K) to cool white light (5700K).

Illuminate your world with LED House professionals - [check out our portfolio of projects here!!](#)

|                               |                          |
|-------------------------------|--------------------------|
| Correlated colour temperature | warm white 3000K         |
| Luminous flux                 | 5300lumens               |
| Luminaire's efficiency lm79   | 88lm/W                   |
| Warranty                      | 5 years                  |
| Power supply                  | <a href="#">BOKE</a>     |
| Brand                         | <a href="#">Prolumen</a> |
| Supply voltage                | 230V                     |
| Power factor                  | 0.90                     |
| Dimmable                      | DALI                     |
| Output                        | 60W                      |
| Maximum output                | 60W                      |
| Lens angle                    | 65°                      |
| Cri                           | 90                       |
| Ugr                           | 19                       |
| Sdcm - macadam ellipses       | 6                        |
| Protection class              | IP20                     |
| Lifespan                      | 50000h                   |
| Lmf tm21                      | L80B10 @25°C 50.000h     |
| Length                        | 1512.0mm                 |
| Width                         | 57.0mm                   |
| Height                        | 76.0mm                   |
| In box                        | 6pcs                     |
| Casing colour                 | black                    |
| Casing material               | aluminium                |
| Work environment              | indoor use               |
| Operation temperature         | -20 ~ 45°C               |
| Certificates                  | CE                       |
| Eprel                         | <a href="#">2663822</a>  |
| Energy class                  |                          |

