



LED luminaire PROLUMEN Delilah L-corner 150+150 white 230V 7.5W 650lm 110° IP20 940

Product code 17054

Extendable linear recessed luminaire that allows for creating light games according to preference.

Possible to install into walls and ceilings, creating a minimalist and striking appearance. This enables creating a modern look in spaces, perfect for both homes and commercial areas.

The luminaire is equipped with high-quality LED light sources, ensuring stable and uniform illumination. Recessed linear luminaires are energy-efficient and have a long lifespan.

Protection class IP20 means that the luminaires are suitable for indoor use only. The luminaire adds daylight (4000K) to the room and does not distort the true colors of objects under the light beam (CRI90).

Illuminate your world with LED House professionals - [check out our project portfolio here!](#) Extendable linear recessed luminaire that allows for creating light games according to preference.

Possible to install into walls and ceilings, creating a minimalist and striking appearance. This enables creating a modern look in spaces, perfect for both homes and commercial areas.

The luminaire is equipped with high-quality LED light sources, ensuring stable and uniform illumination. Recessed linear luminaires are energy-efficient and have a long lifespan.

Protection class IP20 means that the luminaires are suitable for indoor use only. The luminaire adds daylight (4000K) to the room and does not distort the true colors of objects under the light beam (CRI90).

Illuminate your world with LED House professionals - [check out our project portfolio here!](#)

Correlated colour temperature	pure white 4000K
Luminous flux	650lumens
Luminaire's efficiency lm79	87lm/W
Warranty	5 years
Brand	PROLUMEN
Supply voltage	230V
Power factor	0.90
Output	7.5W
Maximum output	7.5W
Lens angle	110°
Cri	90
Sdcm - macadam ellipses	6
Protection class	IP20
Lifespan	50000h
Length	150.0mm
Width	150.0mm
Height	29.0mm
In box	24pcs
Casing colour	white
Casing material	aluminum
Polishing	matt
Work environment	indoor use
Operation temperature	-20 ~ 45°C
Certificates	CE, RoHS
Energy class	

