



**LED downlight PROLUMEN DL178-4 UGR19 white 230V 25W 2500lm 36°
IP54 DALI 930**

Product code 17213


Recessed LED ship light.

Recommended uses: corridors, public areas such as commercial spaces, schools, sports halls, and commercial premises.

The IP54 protection class means that the luminaire is protected against normal dust and splashes from any direction.

From the LED House range, you can find this luminaire model in two light temperatures: 3000K (warm white) and 4000K (daylight).

If you haven't found the perfect light fixture from our product range yet, then browse through the [PROLUMEN catalogue](#) as well!

| | |
|-------------------------------|---|
| Correlated colour temperature | warm white 3000K |
| Luminous flux | 2500lumens |
| Luminaire's efficiency lm79 | 100lm/W |
| Warranty | 5 years |
| Brand | PROLUMEN |
| Supply voltage | 230V |
| Dimmable | DALI |
| Output | 25W |
| Maximum output | 25W |
| Lens angle | 36° |
| Cri | 90 |
| Ugr | 19 |
| Protection class | IP54 |
| Lifespan | 50000h |
| Lmf tm21 | L80B10 @25°C 50.000h |
| Height | 78.0mm |
| Diameter | 145.0mm |
| Installation opening diameter | 100mm |
| Weight | 475g |
| In box | 18pcs |
| Casing colour | white |
| Casing material | aluminum |
| Impact resistance | IK06 |
| Work environment | indoor use |
| Certificates | CE, RoHS |
| Energy class |  |

