

**Mirror light Prolumen ML27 600 black 230V 12W 1300lm CRI90 160X110°  
IP44 3000K, 4000K, 5700K 3CCT**

Product code 17241

LED lamp for the mirror.


The luminaire ensures true colors in three different directions - a very good option to use in the bathroom or near the mirror in the hallway. Minimalist design, without screws and additional details, the luminaire has an aluminum black matte body.

An ideal luminaire for the bathroom, hotel room, and above the makeup table.

We also recommend this LED luminaire above the dressing table. A light temperature of 5700K is ideal for beauty procedures and is also preferred by professional cosmetologists!

Can be mounted directly on the surface, but can also be suspended from the ceiling with additional accessories.

Improve the quality of light in your everyday life and choose a top-notch lighting solution from [the LED house product range](#)!

|                               |   |
|-------------------------------|---|
| Correlated colour temperature | 3CCT 3000K, 4000K, 5700K  |
| Luminous flux                 | 1300lumens  |
| Luminaire's efficiency lm79   | 108lm/W   |
| Warranty                      | 5 years   |
| Brand                         | <a href="#">Prolumen</a>  |
| Supply voltage                | 230V  |
| Power factor                  | 0.90  |
| Output                        | 12W   |
| Maximum output                | 12W   |
| Rated current                 | 300mA   |
| Lens angle                    | 160X110°  |
| Cri                           | 90  |
| Sdcm - macadam ellipses       | 6   |
| Protection class              | IP44  |
| Lifespan                      | 50000h  |
| Length                        | 600.0mm   |
| Width                         | 46.0mm  |
| Height                        | 72.0mm  |
| Weight                        | 1000g   |
| Package weight                | 1300g   |
| In package                    | 1pc   |
| In box                        | 6pcs  |
| Casing colour                 | black   |
| Polishing                     | matt  |
| Work environment              | indoor use  |
| Operation temperature         | -20 -45°C   |
| Certificates                  | CE  |
| Eprel                         | <a href="#">2174275</a>   |
| Energy class                  |  |

