



**LED industrial light PROLUMEN UFO Crossover V black 230V 100W  
14500lm 120° IP65 1-10V 830**

Product code 17345

LED industrial luminaire.

The luminaire's IP65 protection class means that the luminaire is protected against both fine dust and water jets.

The luminaire has a light temperature of 4000K, providing daylight-like illumination - the most suitable for work environments.

With proper use, the luminaire is energy-efficient, environmentally friendly, and has a very long lifespan (50,000 hours).

Delivery from EU warehouse in 7-14 days.

You can find the best assortment of industrial lighting in the [LED house product range!](#)

|                               |   |
|-------------------------------|---|
| Correlated colour temperature | warm white 3000K  |
| Luminous flux                 | 14500lumens   |
| Luminaire's efficiency lm79   | 145lm/W   |
| Warranty                      | 5 years   |
| Source of light               | <a href="#">PHILIPS LED</a>   |
| Power supply                  | <a href="#">SOSEN</a>   |
| Brand                         | <a href="#">PROLUMEN</a>  |
| Supply voltage                | 230V  |
| Power factor                  | 0.90  |
| Dimmable                      | 1-10V   |
| Output                        | 100W  |
| Lens angle                    | 120°  |
| Cri                           | 80  |
| Sdcm - macadam ellipses       | 6   |
| Protection class              | IP65  |
| Lifespan                      | 50000h  |
| Lmf tm21                      | L90B10 @25°C 50.000h  |
| Height                        | 174.0mm   |
| Diameter                      | 290.0mm   |
| Weight                        | 2700g   |
| Casing colour                 | black   |
| Casing material               | aluminum  |
| Polishing                     | matt  |
| No. of switches               | 100000times   |
| Impact resistance             | IK08  |
| Work environment              | indoor use  |
| Operation temperature         | -40 - +60°C   |
| Certificates                  | CE, RoHS  |
| Eprel                         | <a href="#">2247355</a>   |
| Energy class                  |  |

