



## **Facade luminaire Prolumen WL91 black 230V 8W 750lm 45° IP65 TRIAC 930**

Product code 17380

Modern wall light for indoor and outdoor use.


The IP65 protection class means that the luminaire is protected against fine dust and water splashes and can be used in outdoor conditions.

The light adds warm white illumination to the space, and thanks to the TRIAC technology, it is possible to adjust the brightness of the light beam.

The WL91 model's LED chips have high-quality color rendering (CRI90), ensuring that the light does not distort the true colors in the room

With proper use, the luminaire is energy-efficient, environmentally friendly, and has a very long lifespan (50,000 hours).

Illuminate your world with LED House professionals - [check out our project portfolio here!](#)

|                               |                                                                                     |
|-------------------------------|-------------------------------------------------------------------------------------|
| Correlated colour temperature | warm white 3000K                                                                    |
| Luminous flux                 | 750lumens                                                                           |
| Luminaire's efficiency lm79   | 94lm/W                                                                              |
| Warranty                      | 5 years                                                                             |
| Brand                         | <a href="#">Prolumen</a>                                                            |
| Supply voltage                | 230V                                                                                |
| Power factor                  | 0.90                                                                                |
| Dimmable                      | TRIAC                                                                               |
| Output                        | 8W                                                                                  |
| Maximum output                | 8W                                                                                  |
| Lens angle                    | 45°                                                                                 |
| Cri                           | 90                                                                                  |
| Sdcm - macadam ellipses       | 6                                                                                   |
| Protection class              | IP65                                                                                |
| Lifespan                      | 50000h                                                                              |
| Length                        | 121.0mm                                                                             |
| Width                         | 95.0mm                                                                              |
| Height                        | 202.0mm                                                                             |
| In package                    | 1pc                                                                                 |
| In box                        | 12pcs                                                                               |
| Casing colour                 | black                                                                               |
| Casing material               | aluminium                                                                           |
| Polishing                     | matt                                                                                |
| Impact resistance             | IK06                                                                                |
| Work environment              | indoor / outdoor use                                                                |
| Operation temperature         | -20 ~ 45°C                                                                          |
| Certificates                  | SAA, RoHS, CE                                                                       |
| Energy class                  |  |

