



## **LED warehouse light PROLUMEN Harrow 1500 DALI white 230V 75W 12000lm 90° IP65 840**

Product code 17554


Harrow - an innovative [industrial and warehouse luminaire](#) that meets a wide range of expectations, boasting an unusually long lifespan and high quality.

The Dreamboat luminaire meets various demands:

1. It can be installed either surface-mounted or suspended.
2. DALI dimming technology allows adjusting light intensity according to needs.
3. Power can be changed with a button press, making it possible to install the luminaire at different heights.

The luminaire has end caps at both ends, making wiring and maintenance exceptionally easy. Additionally, maintenance costs are lower than usual because individual components of the luminaire can be replaced separately, eliminating the need to replace the entire luminaire in case of a malfunction.

Illuminate your world with LED House professionals - [check out our project portfolio here!](#)

|                               |   |
|-------------------------------|---|
| Correlated colour temperature | pure white 4000K  |
| Luminous flux                 | 12000lumens   |
| Luminaire's efficiency lm79   | 160lm/W   |
| Warranty                      | 5 years   |
| Source of light               | <a href="#">PHILIPS LED</a>   |
| Led chip                      | SMD2835   |
| Power supply                  | ENEC certified  |
| Brand                         | <a href="#">PROLUMEN</a>  |
| Supply voltage                | 230V  |
| Power factor                  | 0.90  |
| Dimmable                      | DALI  |
| Output                        | 75W   |
| Lens angle                    | 90°   |
| Cri                           | 80  |
| Ugr                           | 25  |
| Sdcm - macadam ellipses       | 5   |
| En62471                       | RG0   |
| Protection class              | IP65  |
| Lifespan                      | 54000h  |
| Lmf tm21                      | L90B50 @25°C 50.000h  |
| Length                        | 1540.0mm  |
| Width                         | 76.0mm  |
| Height                        | 80.0mm  |
| In package                    | 1pc   |
| In box                        | 9pcs  |
| Casing colour                 | white   |
| Casing material               | aluminum  |
| Impact resistance             | IK10  |
| Work environment              | indoor / outdoor use  |
| Operation temperature         | -20° - +45°C  |
| Certificates                  | TUV CE, CB, RoHS  |
| Energy class                  |  |

