

# Track light Prolumen Arles black 48V 6W 450lm 36° IP20 DALI 927

Product code 17573

LED track light with an elegant matte black design!

This IP20-rated light is an ideal choice for home or office environments. Thanks to its CRI90, the LED light can display colors naturally, contributing to the overall atmosphere and feel of the room.

The 48V Arles model is available with the following options: Dimming: DALI, RF Beam angle: 15°/24°/36°/50° Color temperature: 2700/3000/3500/4000K or adjustable 2700-6500K.

Pairing the RF Remote:
Switch off the power, then switch on the power again, repeat this process. Then, immediately press the zone button on the remote control three times briefly. If the light blinks, it means the pairing was successful.

Deleting the RF Remote:
Switch off the power, then switch on the power again, repeat this process. Then, immediately press the zone button on the remote control five times briefly. If the light blinks, it means all pairings with the remote controls have been deleted.


Proper use makes this luminaire energy-efficient, environmentally friendly, and with a very long lifespan (50,000 hours).

Illuminate your world with LED House professionals - check out our project portfolio here!

© LED House OÜ, tel: (+372) 56 202 303
Kadaka street 3/3, Tallinn 10621, Estonia, info@ledhouse.ee

| | |
|---|---|
| Correlated colour temperature | warm white 2700K |
| Luminous flux | 450lumens |
| Luminaire’s efficiency | 75lm/W |
| Warranty | 5 years |
| Source of light | CITIZEN LED |
| LED chip | COB |
| Brand | Prolumen |
| Supply voltage | 48V |
| Power factor | 0.90 |
| Dimmable | DALI |
| Output | 6W |
| Maximum output | 6W |
| Lens angle | 36° |
| CRI | 90 |
| SDCM - MacAdam Ellipses | 3 |
| EN62471 | RG0 |
| Protection class | IP20 |
| Lifespan | 50000h |
| LLMF TM21 | L80B10 @25°C 50.000h |
| Height | 70.0mm |
| Diameter | 40.0mm |
| In package | 1pc |
| In box | 30pcs |
| Casing colour | black |
| Casing material | aluminium |
| Work environment | indoor use |
| Operation temperature | -20 +40°C |
| Certificates | CE |
| EPREL | 2002103 |
| Energy class |  |






© LED House OÜ, tel: (+372) 56 202 303
Kadaka street 3/3, Tallinn 10621, Estonia, info@ledhouse.ee