



**Recessed light Prolumen DL178-4 UGR19 white 230V 10W 1100lm 60°
IP54 TRIAC 930**

Product code 17609


Recessed LED ship light.

Recommended uses: corridors, public areas such as commercial spaces, schools, sports halls, and commercial premises.

The IP54 protection class means that the luminaire is protected against normal dust and splashes from any direction.

From the LED House range, you can find this luminaire model in two light temperatures: 3000K (warm white) and 4000K (daylight).

If you haven't found the perfect light fixture from our product range yet, then browse through the [PROLUMEN catalogue](#) as well!

| | |
|-------------------------------|---|
| Correlated colour temperature | warm white 3000K |
| Luminous flux | 1100lumens |
| Luminaire's efficiency lm79 | 110lm/W |
| Warranty | 5 years |
| Source of light | CITIZEN LED |
| Led chip | COB |
| Brand | Prolumen |
| Supply voltage | 230V |
| Power factor | 0.90 |
| Dimmable | TRIAC |
| Output | 10W |
| Maximum output | 10W |
| Lens angle | 60° |
| Cri | 90 |
| Ugr | 19 |
| Sdcm - macadam ellipses | 3 |
| Protection class | IP54 |
| Lifespan | 50000h |
| Llmf tm21 | L80B10 @25°C 50.000h |
| Height | 78.0mm |
| Diameter | 145.0mm |
| Installation opening diameter | 120mm |
| Weight | 475 g |
| In package | 1pc |
| In box | 18pcs |
| Casing colour | white |
| Casing material | aluminium |
| Impact resistance | IK06 |
| Work environment | indoor use |
| Operation temperature | -20 - +45°C |
| Certificates | CE, RoHS |
| Eprel | 2024634 |
| Energy class |  |

