



## **LED module luminaire PROLUMEN 600x600 Backlit UGR<19 h34 230V 36W 4220lm 120° IP20 830**

Product code 17708


High quality modular luminaire, ideal for spaces such as offices and corridors.

The PROLUMEN ceiling panel luminaire stands out due to its low UGR value, long lifespan, and adaptable installation and maintenance methods.

The driver of this luminaire is external - this feature simplifies installation and maintenance by allowing easier access.

The luminaire is designed to be as eye-friendly as possible. In addition to a high UGR value, the Backlit panel is flicker-free. The high lumen output ensures that surfaces are covered with quality and sufficient light.

Improve the quality of light in your everyday life and choose a top-notch lighting solution from [the LED house product range](#)!

|                               |   |
|-------------------------------|---|
| Correlated colour temperature | warm white 3000K  |
| Luminous flux                 | 4220lumens  |
| Luminaire's efficiency lm79   | 117lm/W   |
| Warranty                      | 5 years   |
| Power supply                  | <a href="#">BOKE</a>  |
| Brand                         | <a href="#">PROLUMEN</a>  |
| Supply voltage                | 230V  |
| Power factor                  | 0.90  |
| Output                        | 36W   |
| Maximum output                | 36W   |
| Lens angle                    | 120°  |
| Cri                           | 80  |
| Ugr                           | 19  |
| Sdcm - macadam ellipses       | 3   |
| Protection class              | IP20  |
| Lifespan                      | 50000h  |
| Llmf tm21                     | L80B10 @25°C 50.000h  |
| Length                        | 595.0mm   |
| Width                         | 595.0mm   |
| Height                        | 34.0mm  |
| Weight                        | 1600g   |
| Package weight                | 2150g   |
| In package                    | 1pc   |
| Casing material               | aluminum  |
| Polishing                     | matt  |
| No. of switches               | 25000times  |
| Work environment              | indoor use  |
| Operation temperature         | -10 ~ 40°C  |
| Certificates                  | CE, RoHS  |
| Energy class                  |  |

