



Modular light PROLUMEN 600x600 Backlit UGR<19 h34 230V 36W 4220lm 120° IP20 830

Product code 17708

High quality modular luminaire, ideal for spaces such as offices and corridors.

The PROLUMEN ceiling panel luminaire stands out due to its low UGR value, long lifespan, and adaptable installation and maintenance methods.

The driver of this luminaire is external - this feature simplifies installation and maintenance by allowing easier access.

The luminaire is designed to be as eye-friendly as possible. In addition to a high UGR value, the Backlit panel is flicker-free. The high lumen output ensures that surfaces are covered with quality and sufficient light.

Improve the quality of light in your everyday life and choose a top-notch lighting solution from <u>the LED</u> <u>house product range!</u>



Correlated colour temperature warm white 3000K

Luminous flux 4220lumens Luminaire's efficiency Im79 117lm/W Warranty 5 years Power supply **BOKE Brand Prolumen** Supply voltage 230V Power factor 0.90 Output 36W Maximum output 36W Lens angle 120° Cri 80 Ugr 19 Sdcm - macadam ellipses 3 Protection class IP20

Llmf tm21 L80B10 @25°C 50.000h

50000h

Length595.0mmWidth595.0mmHeight34.0mmWeight1600gPackage weight2150gIn package1pc

Casing material aluminium Polishing matt

 $\begin{array}{lll} \text{No. of switches} & 25000 \text{times} \\ \text{Work environment} & \text{indoor use} \\ \text{Operation temperature} & -10 \sim 40 ^{\circ} \text{C} \\ \text{Certificates} & \text{CE, RoHS} \\ \end{array}$

Energy class

Lifespan







