



Linear light Prolumen Linda 66D 1200 with downward light distribution black 230V 28W 3600lm 75° IP20 DALI 830


Product code 17751

Prolumen Linda is a compact linear luminaire with excellent light distribution, featuring a high-quality microprismatic PMMA plastic diffuser. This luminaire is designed to provide superior lighting in any environment, perfectly fitting into both modern and classic interiors.

Light tone options: 3000K - warm and cozy light 4000K - neutral and clear light 3000-6500K - adjustable light that allows you to choose the right tone according to your mood and needs

Prolumen Linda luminaires are designed to be interconnected, creating a seamless and long lighting line that highlights the best features of your space.

Thanks to its excellent efficiency, Prolumen Linda is an energy-efficient and environmentally friendly choice, while still delivering powerful and uniform light output.

| | |
|-------------------------------|---|
| Correlated colour temperature | warm white 3000K |
| Luminous flux | 3600lumens |
| Luminaire's efficiency lm79 | 129lm/W |
| Warranty | 5 years |
| Led chip | 2835SMD |
| Power supply | BOKE |
| Brand | Prolumen |
| Supply voltage | 230V |
| Power factor | 0.90 |
| Dimmable | DALI |
| Output | 28W |
| Maximum output | 28W |
| Lens angle | 75° |
| Cri | 80 |
| Ugr | 19 |
| Sdcm - macadam ellipses | 6 |
| En62471 | RG0 |
| Protection class | IP20 |
| Lifespan | 50000h |
| Llmf tm21 | L70B50 @25°C 50.000h |
| Length | 1204.0mm |
| Width | 56.0mm |
| Height | 75.0mm |
| Weight | 2750g |
| In box | 6pcs |
| Casing colour | black |
| Casing material | aluminium |
| Polishing | matt |
| Impact resistance | IK06 |
| Work environment | indoor use |
| Operation temperature | -20° - +45°C |
| Certificates | CE |
| Eprel | 2091158 |
| Energy class |  |

