



**LED street light PROLUMEN BEAST TR bracket black 230V 100W 16500lm  
130x60° IP66 1-10V 740**

Product code 17862

A street light that makes moving in urban spaces safe even in the dark of night!

It is perfect for driveways, streets, parking lots, and all other outdoor areas that need safe, affordable, and efficient lighting.

Protection classes IP66 and IK08 ensure the fixture's durability and long life in outdoor conditions. Additionally, the light is ideal for collaboration with security cameras - see the product specifications for more details.

Furthermore, the maintenance process of the light has been made exceptionally easy - allowing you to save on labor and time! This feature is ensured by the removable electric plate, which makes connecting wires during installation particularly convenient.

|                               |   |
|-------------------------------|---|
| Correlated colour temperature | pure white 4000K  |
| Luminous flux                 | 16500lumens   |
| Luminaire's efficiency lm79   | 165lm/W   |
| Warranty                      | 5 years   |
| Source of light               | <a href="#">LUMILEDS</a>  |
| Led chip                      | SMD5050   |
| Power supply                  | <a href="#">INVENTRONICS</a>  |
| Flickering ieee 1789          | 1%  |
| Brand                         | <a href="#">PROLUMEN</a>  |
| Supply voltage                | 230V  |
| Power factor                  | 0.95  |
| Dimmable                      | 1-10V   |
| Output                        | 100W  |
| Lens angle                    | 130x60°   |
| Cri                           | 70  |
| Sdcm - macadam ellipses       | 6   |
| Protection class              | IP66  |
| Lifespan                      | 100000h   |
| Llmf tm21                     | L70 @25°C 100.000h  |
| Length                        | 428.0mm   |
| Width                         | 304.0mm   |
| Height                        | 88.0mm  |
| Casing colour                 | black   |
| Casing material               | aluminum + plastic  |
| Polishing                     | matt  |
| Impact resistance             | IK08  |
| Work environment              | outdoor use   |
| Operation temperature         | -40° - +50°C  |
| Certificates                  | CE, ENEC, CB  |
| Eprel                         | <a href="#">2187245</a>   |
| Energy class                  |  |

