



**Linear light PROLUMEN Linda 66D 1500 with light distribution upwards and downwards, UGR<19 + suspension wires. black 230V 49W 6500lm 75° IP2**

Product code 18163

Prolumen Linda is a compact linear luminaire with excellent light distribution, featuring a high-quality microprismatic PMMA plastic diffuser. This luminaire is designed to provide superior lighting in any environment, perfectly fitting into both modern and classic interiors.

Light tone options: 3000K - warm and cozy light 4000K - neutral and clear light 3000-6500K - adjustable light that allows you to choose the right tone according to your mood and needs

Prolumen Linda luminaires are designed to be interconnected, creating a seamless and long lighting line that highlights the best features of your space.

Thanks to its excellent efficiency, Prolumen Linda is an energy-efficient and environmentally friendly choice, while still delivering powerful and uniform light output.

Correlated colour temperature	pure white 4000K
Luminous flux	6500lumens
Luminaire's efficiency lm79	133lm/W
Warranty	5 years
Led chip	2835SMD
Power supply	<a href="#">BOKE</a>
Brand	<a href="#">Prolumen</a>
Supply voltage	230V
Power factor	0.90
Dimmable	DALI
Output	49W
Maximum output	49W
Lens angle	75°
Cri	80
Ugr	19
Sdcm - macadam ellipses	3
Protection class	IP20
Lifespan	50000h
Length	1504.0mm
Width	56.0mm
Height	75.0mm
Weight	1700g
Package weight	2133g
In box	6pcs
Casing colour	black
Casing material	aluminium
Impact resistance	IK06
Work environment	indoor use
Operation temperature	-20° - +45°C
Certificates	CE
Energy class	

