



LED module luminaire ECO 600x600 Backlit UGR<22 white 230V 36W 4320lm 120° IP40 840

Product code 18238

Budget friendly modular luminaire, ideal for spaces such as offices and corridors.

The ceiling panel luminaire stands out due to its low UGR value, long lifespan, and adaptable installation and maintenance methods.

The driver of this luminaire is external - this feature simplifies installation and maintenance by allowing easier access.

The luminaire is designed to be as eye-friendly as possible. In addition to a high UGR value, the Backlit panel is flicker-free. The high lumen output ensures that surfaces are covered with quality and sufficient light.

Improve the quality of light in your everyday life and choose a top-notch lighting solution from the LED house product range!



Correlated colour temperature pure white 4000K

Luminous flux 4320lumens
Luminaire's efficiency lm79 120lm/W
Warranty 3 years

Source of light SAMSUNG LED

Power supply **LIFUD Brand** ECO Supply voltage 230V Power factor 0.90 Output 36W Lens angle 120° Cri 80 Ugr 22 Sdcm - macadam ellipses 6 Protection class IP40 Lifespan 50000h Length 595.0mm Width 595.0mm Height 25.0mm In package 1pc In box 6pcs Casing colour white Casing material aluminum Polishing matt Work environment indoor use

Certificates CE, RoHS, ENEC, CB, New ERP

Energy class

Operation temperature



-20 - +40°C





