



**LED luminaire PROLUMEN RALTEX 600 white 230V 30W 4800lm CRI80
120° IP66 DALI 3000K, 4000K, 5000K 3CCT**

Product code 18262

This durable industrial luminaire is designed for demanding environments where reliability and precise lighting control are essential. Equipped with DALI control, it integrates perfectly into smart lighting systems, allowing brightness adjustment, energy savings, and improved working conditions.

With a sealed and rugged housing, the luminaire withstands dust, moisture, and heavy-duty use. It is ideal for production facilities, logistics centers, warehouses, and other industrial spaces where consistent and reliable illumination is required.

Ceiling-mounted and suitable for continuous installation, it provides an efficient lighting solution with low maintenance and long service life — an excellent choice for professional applications.

Correlated colour temperature	3CCT 3000K, 4000K, 5000K
Luminous flux	4800lumens
Luminaire's efficiency lm79	160lm/W
Warranty	5 years
Power supply	BOKE
Brand	PROLUMEN
Supply voltage	230V
Power factor	0.90
Dimmable	DALI
Output	30W
Maximum output	30W
Lens angle	120°
Cri	80
Sdcm - macadam ellipses	3
Protection class	IP66
Lifespan	100000h
Llmf tm21	L80B10 @25°C 100.000h
Length	600.0mm
Width	74.0mm
Height	69.0mm
Weight	1130g
In package	1pc
In box	6pcs
Casing colour	white
Casing material	aluminum + plastic
Operation temperature	-20° - +45°C
Certificates	CE, RoHS
Eprel	2409688
Energy class	

