



LED luminaire PROLUMEN RALTEX 1200 white 230V 50W 8000lm CRI80 120° IP66 DALI 3000K, 4000K, 5000K 3CCT

Product code 18263

This durable industrial luminaire is designed for demanding environments where reliability and precise lighting control are essential. Equipped with DALI control, it integrates perfectly into smart lighting systems, allowing brightness adjustment, energy savings, and improved working conditions.

With a sealed and rugged housing, the luminaire withstands dust, moisture, and heavy-duty use. It is ideal for production facilities, logistics centers, warehouses, and other industrial spaces where consistent and reliable illumination is required.

Ceiling-mounted and suitable for continuous installation, it provides an efficient lighting solution with low maintenance and long service life — an excellent choice for professional applications.



Correlated colour temperature 3CCT 3000K, 4000K, 5000K

8000lumens Luminous flux Luminaire's efficiency Im79 160lm/W Warranty 5 years Power supply **BOKE** Brand **Prolumen** Supply voltage 230V Power factor 0.90 Dimmable DALI 50W Output Maximum output 50W Lens angle 120° Cri 80 Sdcm - macadam ellipses 3 Protection class IP66

Llmf tm21 L80B10 @25°C 100.000h

100000h

Length 1200.0mm
Width 74.0mm
Height 69.0mm
Weight 1500g
In package 1pc
In box 6pcs
Casing colour white

Lifespan

Casing material aluminium + plastic

Operation temperature -20° - +45°C
Certificates CE, RoHS
Eprel 2409689

Energy class





