



Modular light Prolumen 600x600 UGR<19 + frame 230V 25W 3500lm 120° IP20 830

Product code 18298

High quality modular luminaire, ideal for spaces such as offices and corridors.

The PROLUMEN ceiling panel luminaire stands out due to its low UGR value, long lifespan, and adaptable installation and maintenance methods.

The driver of this luminaire is external - this feature simplifies installation and maintenance by allowing easier access.

The luminaire is designed to be as eye-friendly as possible. In addition to a high UGR value, the Backlit panel is flicker-free. The high lumen output ensures that surfaces are covered with quality and sufficient light.

Improve the quality of light in your everyday life and choose a top-notch lighting solution from [the LED house product range!](#)

Correlated colour temperature	warm white 3000K
Luminous flux	3500lumens
Luminaire's efficiency lm79	140lm/W
Warranty	5 years
Power supply	LIFUD
Brand	Prolumen
Supply voltage	230V
Power factor	0.90
Output	25W
Maximum output	25W
Lens angle	120°
Cri	80
Ugr	19
Sdcm - macadam ellipses	3
Protection class	IP20
Lifespan	50000h
Llmf tm21	L80B10 @25°C 50.000h
Length	595.0mm
Width	595.0mm
Height	34.0mm
In package	1pc
Casing material	aluminium
Polishing	matt
Work environment	indoor use
Operation temperature	-10 ~ 40°C
Certificates	CE, RoHS
Eprel	2372200
Energy class	

