



LED industrial light PROLUMEN TP LINK 1500 +MW white 230V 60W 8400lm 120° IP65 840

Product code 18348

LED industrial luminaire, suitable for use in workshops, warehouses, corridors, under roofs, garages, etc.

In workspaces, LED lighting is an excellent choice: it provides bright and ergonomic lighting, which helps maintain employees' focus and productivity.


Reliability is ensured by the OSRAM power supply unit and a 5-year warranty. If the luminaire fails within 5 years, we will replace it with a new one!

Very easy and quick installation:

The luminaire fits between two clips, which are fastened with two screws. On average, installation takes less than 3 minutes!

IP65 protection class ensures strong waterproofness of the luminaire and allows it to be used in outdoor conditions, where it may even be under direct water pressure.

Illuminate your world with the help of LED House professionals - check out our portfolio of projects [here!](#)

| | |
|-------------------------------|---|
| Correlated colour temperature | pure white 4000K |
| Luminous flux | 8400lumens |
| Luminaire's efficiency lm79 | 140lm/W |
| Warranty | 5 years |
| Source of light | BRIDGELUX LED |
| Power supply | LIFUD |
| Brand | PROLUMEN |
| Supply voltage | 230V |
| Power factor | 0.90 |
| Output | 60W |
| Lens angle | 120° |
| Cri | 80 |
| Lor | 80 |
| Sdcm - macadam ellipses | 6 |
| Protection class | IP65 |
| Lifespan | 50000h |
| Llmf tm21 | L80B10 @25°C 50.000h |
| Length | 1502.0mm |
| Width | 74.0mm |
| Height | 65.0mm |
| In package | 1pc |
| In box | 6pcs |
| Casing colour | white |
| Casing material | aluminum + plastic |
| Polishing | matt |
| Impact resistance | IK08 |
| Work environment | indoor / outdoor use |
| Operation temperature | -20° +40°C |
| Certificates | CE, D, F |
| Energy class |  |

