



Modular light Prolumen 600x600 Backlit UGR<19 h26 230V 18-40W 6400lm 90° IP20 Dip Switch 840

Product code 19060

High quality modular luminaire, ideal for spaces such as offices and corridors.

The PROLUMEN ceiling panel luminaire stands out due to its low UGR value, long lifespan, and adaptable installation and maintenance methods.

The driver of this luminaire is external - this feature simplifies installation and maintenance by allowing easier access.

The luminaire is designed to be as eye-friendly as possible. In addition to a high UGR value, the Backlit panel is flicker-free. The high lumen output ensures that surfaces are covered with quality and sufficient light.

Improve the quality of light in your everyday life and choose a top-notch lighting solution from [the LED house product range!](#)

Correlated colour temperature	pure white 4000K
Luminous flux	6400lumens
Luminaire's efficiency lm79	160lm/W
Warranty	5 years
Source of light	SANAN LED
Power supply	BOKE
Brand	Prolumen
Supply voltage	230V
Power factor	0.95
Dimmable	Dip Switch
Output	18-40W
Maximum output	40W
Lens angle	90°
Cri	80
Sdcm - macadam ellipses	5
Protection class	IP20
Lifespan	102000h
Lmf tm21	L70B10 @25°C 100.000h
Length	595.0mm
Width	595.0mm
Height	26.0mm
Weight	1.8 kg
In box	10pcs
Impact resistance	IK08
Operation temperature	-20° - +45°C
Eprel	2386007
Energy class	

