



**LED luminaire Prolumen Bianca white 230V 17W 2349lm CRI80 120° IP44  
DALI 3000K, 4000K, 5000K 3CCT**

Product code 19066


High-quality, dimmable ceiling light.

DALI Dim technology allows adjusting the light according to preference.

4000K LED lights provide clear and sharp illumination, perfect for lighting stores and other commercial spaces.

The high color rendering index CRI90 ensures the accuracy of colors under the light beam. IP44 protection class means the luminaire can be used even in damp conditions.

Illuminate your world with the help of LED House professionals - [check out our portfolio of projects here!!](#)

|                               |   |
|-------------------------------|---|
| Correlated colour temperature | 3CCT 3000K, 4000K, 5000K  |
| Luminous flux                 | 2349lumens  |
| Luminaire's efficiency lm79   | 138lm/W   |
| Warranty                      | 5 years   |
| Power supply                  | <a href="#">BOKE</a>  |
| Brand                         | <a href="#">Prolumen</a>  |
| Supply voltage                | 230V  |
| Power factor                  | 0.90  |
| Dimmable                      | DALI  |
| Output                        | 17W   |
| Maximum output                | 17W   |
| Lens angle                    | 120°  |
| Cri                           | 80  |
| Sdcm - macadam ellipses       | 6   |
| Protection class              | IP44  |
| Lifespan                      | 50000h  |
| Lmf tm21                      | L80B10 @25°C 50.000h  |
| Length                        | 660.0mm   |
| Width                         | 152.0mm   |
| Height                        | 52.2mm  |
| Weight                        | 1.55 kg   |
| Package weight                | 1.8 kg  |
| In package                    | 1pc   |
| In box                        | 4pcs  |
| Casing colour                 | white   |
| Casing material               | polycarbonate   |
| Polishing                     | matt  |
| Work environment              | indoor use  |
| Operation temperature         | -20° +40°C  |
| Certificates                  | CE, D, F  |
| Eprel                         | <a href="#">2386015</a>   |
| Energy class                  |  |

