



## LED module luminaire 120x300 Backlit + frame white 230V 36W 4320lm 120° IP20 840

Product code 19161

Budget friendly modular luminaire, ideal for spaces such as offices and corridors.

The ceiling panel luminaire stands out due to its low UGR value, long lifespan, and adaptable installation and maintenance methods.

The driver of this luminaire is external - this feature simplifies installation and maintenance by allowing easier access.

The luminaire is designed to be as eye-friendly as possible. In addition to a high UGR value, the Backlit panel is flicker-free. The high lumen output ensures that surfaces are covered with quality and sufficient light.

Improve the quality of light in your everyday life and choose a top-notch lighting solution from <u>the LED</u> <u>house product range</u>!



| Correlated colour temperature | pure white 4000K     |
|-------------------------------|----------------------|
| Luminous flux                 | 4320lumens           |
| Luminaire's efficiency lm79   | 120lm/W              |
| Warranty                      | 3 years              |
| Power supply                  | <u>LIFUD</u>         |
| Supply voltage                | 230V                 |
| Power factor                  | 0.90                 |
| Output                        | 36W                  |
| Maximum output                | 36W                  |
| Lens angle                    | 120°                 |
| Cri                           | 80                   |
| Protection class              | IP20                 |
| Lifespan                      | 30000h               |
| Llmf tm21                     | L90B50 @25°C 50.000h |
| Length                        | 1195.0mm             |
| Width                         | 295.0mm              |
| Height                        | 39.0mm               |
| In package                    | 1pc                  |
| In box                        | 6pcs                 |
| Casing colour                 | white                |
| Casing material               | aluminum + plastic   |
| Impact resistance             | IK03                 |
| Work environment              | indoor use           |
| Operation temperature         | -20° - +45°°C        |
| Certificates                  | CE, SAA, RoHS,       |
| Energy class                  |                      |



