



Linear light Prolumen Linda 5076 1200 UGR≤20 with downward light distribution black 230V 34W 4100lm 90° IP20 DALI 830

Product code 19390

Prolumen Linda is a compact linear luminaire with excellent light distribution, featuring a high-quality microprismatic PMMA plastic diffuser. This luminaire is designed to provide superior lighting in any environment, perfectly fitting into both modern and classic interiors.

Light tone options: 3000K - warm and cozy light 4000K - neutral and clear light 3000-6500K - adjustable light that allows you to choose the right tone according to your mood and needs

Prolumen Linda luminaires are designed to be interconnected, creating a seamless and long lighting line that highlights the best features of your space.

Thanks to its excellent efficiency, Prolumen Linda is an energy-efficient and environmentally friendly choice, while still delivering powerful and uniform light output.

Correlated colour temperature warm white 3000K

Luminous flux 4100lumens

Luminaire's efficiency lm79 121lm/W

Warranty 5 years

Led chip 2835SMD

Power supply [BOKE](#)

Brand [Prolumen](#)

Supply voltage 230V

Power factor 0.90

Dimmable DALI

Output 34W

Maximum output 34W

Lens angle 90°

Cri 80

Ugr 20

Sdcm - macadam ellipses 3

En62471 RG0

Protection class IP20

Lifespan 50000h

Llmf tm21 L80B50 @25°C 75.000h

Length 1160.0mm

Width 50.0mm

Height 76.0mm

In box 6pcs

Casing colour black

Casing material aluminium

Polishing matt

Impact resistance IK06

Work environment indoor use

Operation temperature -20° - +45°C

Certificates CE

Energy class

