

MAYTONI



Track light Maytoni Flarity brass 24V 3W 60lm 120° IP20 927

Product code 20544

1. DESCRIPTION AND INTENDED USE OF THE DEVICE

The Flarity Magnetic Modular Track System serves as the foundation for constructing track lighting systems. It is designed to mount and supply power to Flarity track luminaires in a DC network with a nominal voltage of 24V. The system supports both wall and ceiling mounting options and is compatible with materials that are normally flammable.

Mounting can be achieved using either rigid fixtures or cable hanger.

Track is available in the following color:

Brass with electroplated finish.

Comes in three configurations:

Straight segments: 1 meter and 2 meters in length.

Circular tracks: 650 mm and 800 mm in diameter. Semi-circular cross-section tracks: 650 mm and 800 mm in diameter. The segments can be cut at any point using specialized equipment, allowing for the creation of various configurations, ranging from simple to multi-level light installations. The Flarity system supports group dimming functions when used with appropriate power supplies that operate on the DALI protocol. Additionally, it supports dimming methods such as 0/1-10V, Triac, and PWM (using dimmers, controllers, and remotes

Correlated colour temperature	warm white 2700K
Luminous flux	60lumens
Warranty	3 years
Brand	Maytoni
Supply voltage	24V
Output	3W
Lens angle	120°
Cri	90
Protection class	IP20
Height	112.0mm
Diameter	90.0mm
Weight	150 g
Package weight	320 g
In package	1pc
Casing colour	brass
Casing material	aluminium
Work environment	indoor use
Manufacturer's homepage	maytoni.de/en/catalog/functional/track-systems/flarity-system-luminaire-series/luminaires-flarity/tr147-1-3w2-7k-bs-de/

