MAYTONI



Track light Maytoni Flarity Keila brass 24V 5W 250lm 120° IP20 927


Product code 20549

1. DESCRIPTION AND INTENDED USE OF THE DEVICE
The Flarity Magnetic Modular Track System serves as the foundation for constructing track lighting systems. It is designed to mount and supply power to Flarity track luminaires in a DC network with a nominal voltage of 24V. The system supports both wall and ceiling mounting options and is compatible with materials that are normally flammable.
Mounting can be achieved using either rigid fixtures or cable hanger.
Track is available in the following color:
Brass with electroplated finish.
Comes in three configurations:
Straight segments: 1 meter and 2 meters in length.
Circular tracks: 650 mm and 800 mm in diameter. Semi-circular cross-section tracks: 650 mm and 800 mm in diameter. The segments can be cut at any point using specialized equipment, allowing for the creation of various configurations, ranging from simple to multi-level light installations. The Flarity system supports group dimming functions when used with appropriate power supplies that operate on the DALI protocol. Additionally, it supports dimming methods such as 0/1-10V, Triac, and PWM (using dimmers, controllers, and remotes for LED strips)

Correlated colour temperature	warm white 2700K
Luminous flux	250lumens
Warranty	3 years
Brand	Maytoni
Supply voltage	24V
Output	5W
Lens angle	120°
Cri	90
Protection class	IP20
Height	115.0mm
Diameter	70.0mm
Weight	200 g
Package weight	280 g
In package	1pc
Casing colour	brass
Casing material	aluminium
Work environment	indoor use
Manufacturer's homepage	maytoni.de/en/catalog/functional/track-systems/flarity-system-luminaire-series/luminaires-flarity/tr146-1-5w2-7k-bs-de/

© LED House OÜ, tel: (+372) 56 202 303
Kadaka street 3/3, Tallinn 10621, Estonia, info@ledhouse.ee







© LED House OÜ, tel: (+372) 56 202 303
Kadaka street 3/3, Tallinn 10621, Estonia, info@ledhouse.ee