

# Recessed light Prolumen Gimbal COB D114 white 230V 12W 1100lm 60° IP20 DALI 930

Product code 20701

Directional recessed LED luminaire suitable for use in commercial and warehouse spaces.

This recessed luminaire model features dimming capability, allowing users to adjust the brightness of the light according to their preferences.

A high color rendering index (CRI90) keeps the colors of the areas and objects beneath the lighting true and natural.

Gimbal models are available in the LED House product range with both warm white (3000K) and daylight white (4000K) light.

With proper use, the luminaire is energy-efficient, environmentally friendly, and has a very long lifespan (50,000h).

Illuminate your world with LED House professionals - check out our project portfolio here!

© LED House OÜ, tel: (+372) 56 202 303
Kadaka street 3/3, Tallinn 10621, Estonia, info@ledhouse.ee

| | |
|---|---|
| Correlated colour temperature | warm white 3000K |
| Luminous flux | 1100lumens |
| Luminaire’s efficiency | 92lm/W |
| Warranty | 5 years |
| Source of light | CITIZEN LED |
| Brand | Prolumen |
| Supply voltage | 230V |
| Power factor | 0.90 |
| Dimmable | DALI |
| Output | 12W |
| Maximum output | 12W |
| Lens angle | 60° |
| Cri | 90 |
| Sdcm - macadam ellipses | 3 |
| Protection class | IP20 |
| Lifespan | 50000h |
| Llmf tm21 | L80B50 @25°C 50.000h |
| Height | 90.0mm |
| Diameter | 114.0mm |
| Installation opening diameter | 100mm |
| In box | 18pcs |
| Casing colour | white |
| Casing material | aluminium |
| Polishing | matt |
| Impact resistance | IK05 |
| Work environment | indoor use |
| Certificates | CE |
| Energy class | F (A↑G) |





© LED House OÜ, tel: (+372) 56 202 303
Kadaka street 3/3, Tallinn 10621, Estonia, info@ledhouse.ee