



## **Spotlight Prolumen DL340B black 230V 15W 1469lm 36° IP40 930**

Product code 20703

Modern matte white surface-mounted light.

The aluminum matte white body allows for easy adjustment of the light direction. The light fixture rotates within a 360-degree radius, and horizontally, the direction can be adjusted up to 90 degrees.

Its minimalist design blends perfectly with various interiors, whether at home, in the office, or in a business environment.

With an IP40 protection rating, this surface-mounted light is an ideal choice for home or office environments, providing warm white light at a temperature of 3000K.

Thanks to CRI90, the LED light fixture is capable of presenting colors in a natural way, contributing to the overall atmosphere and feeling of the room.

Upgrade the quality of light in your everyday life and choose a top-notch lighting solution from the LED house product range!

|                               |   |
|-------------------------------|---|
| Correlated colour temperature | warm white 3000K  |
| Luminous flux                 | 1469lumens  |
| Luminaire's efficiency lm79   | 98lm/W  |
| Warranty                      | 5 years   |
| Brand                         | <a href="#">Prolumen</a>  |
| Supply voltage                | 230V  |
| Power factor                  | 0.90  |
| Output voltage                | 40V   |
| Output                        | 15W   |
| Maximum output                | 15W   |
| Rated current                 | 250mA   |
| Lens angle                    | 36°   |
| Cri                           | 90  |
| Ugr                           | 19  |
| Sdcm - macadam ellipses       | 3   |
| Protection class              | IP40  |
| Lifespan                      | 50000h  |
| Lmf tm21                      | L80B10 @25°C 50.000h  |
| Height                        | 100.0mm   |
| Diameter                      | 100.0mm   |
| Installation opening diameter | 95mm  |
| Weight                        | 540 g   |
| Package weight                | 600 g   |
| In package                    | 1pc   |
| In box                        | 24pcs   |
| Casing colour                 | black   |
| Casing material               | aluminium   |
| Work environment              | indoor use  |
| Operation temperature         | -20 ~ 45°C  |
| Certificates                  | CE  |
| Eprel                         | <a href="#">2729158</a>   |
| Energy class                  |  |

