



Recessed light Prolumen DL103 G2 white round 230V 13W 1150lm 36° IP65 DALI 930


Product code 22318


Recessed LED luminaire.

The IP65 protection class means that the luminaire is protected against fine dust and low-pressure jets. Thanks to this feature, this luminaire is suitable for outdoor use and in moister environments.

From the LED House product range, you can also find this model with TRIAC technology, which allows dimming functionality. In addition, you can choose between two light temperatures: 3000K (warm white) and 4000K (daylight).

If you haven't found the perfect light fixture from our product range yet, then browse through the [PROLUMEN catalogue](#) as well!

| | |
|-------------------------------|---|
| Correlated colour temperature | warm white 3000K |
| Luminous flux | 1150lumens |
| Luminaire's efficiency lm79 | 88lm/W |
| Warranty | 5 years |
| Brand | Prolumen |
| Supply voltage | 230V |
| Power factor | 0.90 |
| Dimmable | DALI |
| Output | 13W |
| Maximum output | 13W |
| Lens angle | 36° |
| Cri | 90 |
| Sdcm - macadam ellipses | 5 |
| Protection class | IP65 |
| Lifespan | 50000h |
| Llmf tm21 | L80B10 @25°C 50.000h |
| Height | 65.0mm |
| Diameter | 110.0mm |
| Installation opening diameter | 90mm |
| In box | 30pcs |
| Casing colour | white |
| Casing material | aluminium |
| Polishing | matt |
| Shape | round |
| Work environment | indoor use |
| Operation temperature | -20 - +45°C |
| Certificates | CE, RoHS |
| Eprel | 2679754 |
| Energy class |  |



ENERGY

Prolumen
22318

A
B
C
D
E
F
G

13
kWh/1000h

2019/2015

