

Linear light Prolumen Linda 6060 1200 UGR□20 with downward light distribution black 230V 34W 4100lm 90° IP20 DALI 930

Product code 23249

Prolumen Linda is a compact linear luminaire with excellent light distribution, featuring a high-quality microprismatic PMMA plastic diffuser. This luminaire is designed to provide superior lighting in any environment, perfectly fitting into both modern and classic interiors.

Light tone options: 3000K - warm and cozy light 4000K - neutral and clear light 3000-6500K - adjustable light that allows you to choose the right tone according to your mood and needs

Prolumen Linda luminaires are designed to be interconnected, creating a seamless and long lighting line that highlights the best features of your space.

Thanks to its excellent efficiency, Prolumen Linda is an energy-efficient and environmentally friendly choice, while still delivering powerful and uniform light output.

Correlated colour temperature	warm white 3000K
Luminous flux	4100lumens
Luminaire’s efficiency	121lm/W
Warranty	5 years
LED chip	2835SMD
Power supply	BOKE
Brand	Prolumen
Supply voltage	230V
Power factor	0.90
Dimmable	DALI
Output	34W
Maximum output	34W
Lens angle	90°
CRI	90
UGR	20
SDCM - MacAdam Ellipses	3
EN62471	RG0
Protection class	IP20
Lifespan	50000h
LLMF TM21	L80B50 @25°C 75.000h
Length	1160.0mm
Width	60.0mm
Height	60.0mm
In box	6pcs
Casing colour	black
Casing material	aluminium
Polishing	matt
Impact resistance	IK06
Work environment	indoor use
Operation temperature	-20° - +45°C
Certificates	CE
EPREL	2792746
Energy class	D (A↑G)







© LED House OÜ, tel: (+372) 56 202 303
Kadaka street 3/3, Tallinn 10621, Estonia, info@ledhouse.ee