

LED driver LIFUD 1500mA 27-42V LF-GDE060YF1500U DIM 0-10V white 65W IP20 (14119)

Product code: 14119
brand: [LIFUD](#)
input voltage: 230V
dimmable: 0-10V
output voltage: 27-42V
power: 65W
current: 1500mA
IP rating: IP20
service life of LED: 50000h
height: 31mm
width: 65mm
length: 193mm
weight: 280g
in pack: 30pcs
casing colour: white
casing material: plastic
working environment: indoor use
working temperature: -30 °C - +50°C
certifications: ENEC,CE,GS,CB,SAA,RCM
warranty: 5 years



price: €27,00+VAT
price: €32,40 including VAT
LF-GDE060YF 1500U Product description
Isolated LED driver designed for class II LED luminaires; Input voltage AC100-277V for global market, max input voltage range AC90-305V; Output power 30-65W, DC voltage range 27-42V; Active PFC, high PF (PF>0.93@AC230V), high efficiency (up to 88%), low THD ($\leq 20\%$); Meet the ERP and DLC standards after being installed inside finished LED lights; Surge protection: 1KV; 0-10V, PWM and Rx dimmable version, dimming range 10%~100%; Connecting with Lifud ZigBee convertor, it can realize ZigBee smart wireless control function; Nominal lifetime above 50,000 hours, 5 years warranty; Applied for panel lights, down lights, tube lights applications. Housing properties Casing: polycarbonate, UL V-0 fireproof, white;