

## LED driver LIFUD 1500mA 27-42V LF-GDE060YF1500U DIM 0-10V white 65W IP20 (LH4119)

Product code: LH4119

brand: [LIFUD](#)

input voltage: 230V

dimnable: 0-10V

output voltage: 27-42V

power: 65W

current: 1500mA

IP rating: IP20

service life of LED: 50000h

height: 31mm

width: 65mm

length: 193mm

weight: 280g

in pack: 30pcs

casing colour: white

casing material: plastic

working environment: indoor use

working temperature: -30 °C - +50°C

certifications: ENEC,CE,GS,CB,SAA,RCM

warranty: 5 years



price: €27,00+VAT

price: €32,40 including VAT

LF-GDE060YF 1500U Product description

Isolated LED driver designed for class II

LED luminaires; Input voltage

AC100-277V for global market, max input

voltage range AC90-305V; Output power

30-65W, DC voltage range 27-42V; Active

PFC, high PF (PF>0.93@AC230V), high

efficiency (up to 88%), low THD (≤20%);

Meet the ERP and DLC standards after

being installed inside finished LED lights;

Surge protection: 1KV; 0-10V, PWM and

Rx dimmable version, dimming range

10%~100%; Connecting with Lifud

ZigBee convertor, it can realize ZigBee

smart wireless control function; Nominal

lifetime above 50,000 hours, 5 years

warranty; Applied for panel lights, down

lights, tube lights applications. Housing

properties Casing: polycarbonate, UL V-0

fireproof, white;