

Battery Deye GB-L 12,27kWh HV set (3x4,09kWh LiFePO4) + Battery controller IP65

Product code 17069


Brand [Deye](#)

Output voltage 307,2V

Protection class IP65

Warranty 5 years

Safe - Built-in device that eliminates fire hazards with a special substance within 3 seconds. Stacking tower - Modules are connected in series without cable connection, enhancing system efficiency. Heat management - Detecting the temperature of main parts, elements, power plugs, etc. Suitable for everywhere - IP protection grade 65, corrosion resistance class $\geq C2$, environmentally friendly battery. Sleek and concealed - The tower features minimalist design to remain relatively invisible. Maximum utilization scope (DOD) 90%. [Read more about the Deye inverter here.](#)



Battery Deye GB-L 16,36kWh HV set (4x4,09kWh LiFePO4) + Battery controller IP65

Product code 17070


Brand [Deye](#)

Output voltage 409,6V

Protection class IP65

Warranty 5 years

Safe - Built-in device that eliminates fire hazards with a special substance within 3 seconds. Stacking tower - Modules are connected in series without cable connection, enhancing system efficiency. Heat management - Detecting the temperature of main parts, elements, power plugs, etc. Suitable for everywhere - IP protection grade 65, corrosion resistance class $\geq C2$, environmentally friendly battery. Sleek and concealed - The tower features minimalist design to remain relatively invisible. Maximum utilization scope (DOD) 90%. [Read more about the Deye inverter here.](#)



Battery Deye GB-L 20,45kWh HV set (5x4,09kWh LiFePO4) + Battery controller IP65

Product code 17071


Brand [Deye](#)

Output voltage 512V

Protection class IP65

Warranty 5 years

Safe - Built-in device that eliminates fire hazards with a special substance within 3 seconds. Stacking tower - Modules are connected in series without cable connection, enhancing system efficiency. Heat management - Detecting the temperature of main parts, elements, power plugs, etc. Suitable for everywhere - IP protection grade 65, corrosion resistance class $\geq C2$, environmentally friendly battery. Sleek and concealed - The tower features minimalist design to remain relatively invisible. Maximum utilization scope (DOD) 90%. [Read more about the Deye inverter here.](#)



Battery Deye GB-L 24,56kWh HV set (6x4,09kWh LiFePO4) + Battery controller IP65

Product code 17058


Brand [Deye](#)

Output voltage 614,4V

Protection class IP65

Warranty 5 years

Safe - Built-in device that eliminates fire hazards with a special substance within 3 seconds. Stacking tower - Modules are connected in series without cable connection, enhancing system efficiency. Heat management - Detecting the temperature of main parts, elements, power plugs, etc. Suitable for everywhere - IP protection grade 65, corrosion resistance class $\geq C2$, environmentally friendly battery. Sleek and concealed - The tower features minimalist design to remain relatively invisible. Maximum utilization scope (DOD) 90%. [Read more about the Deye inverter here.](#)



Battery Deye GB-L 4,09kWh HV LiFePO4 IP65

Product code 17067

Brand [Deye](#)

Protection class IP65

Warranty 5 years

Safe - Built-in device that eliminates fire hazards with a special substance within 3 seconds. Stacking tower - Modules are connected in series without cable connection, enhancing system efficiency. Heat management - Detecting the temperature of main parts, elements, power plugs, etc. Suitable for everywhere - IP protection grade 65, corrosion resistance class $\geq C2$, environmentally friendly battery. Sleek and concealed - The tower features minimalist design to remain relatively invisible. Maximum utilization scope (DOD) 90%.



Battery Deye GB-L 8,18kWh HV set (2x4,09kWh LiFePO4) + Battery controller IP65

Product code 17068

Brand [Deye](#)


Output voltage 204,8V

Protection class IP65

Warranty 5 years

Safe - Built-in device that eliminates fire hazards with a special substance within 3 seconds. Stacking tower - Modules are connected in series without cable connection, enhancing system efficiency. Heat management - Detecting the temperature of main parts, elements, power plugs, etc. Suitable for everywhere - IP protection grade 65, corrosion resistance class $\geq C2$, environmentally friendly battery. Sleek and concealed - The tower features minimalist design to remain relatively invisible. Maximum utilization scope (DOD) 90%.

[Read more about the Deye inverter here.](#)



Controller Deye GB-L BMS+BASE IP65

Product code 17163

Brand [Deye](#)

Protection class IP65

Warranty 5 years

Safe - Built-in device that eliminates fire hazard with special substance within 3 seconds. Stacking tower - Modules are connected in series without cable connection, improving system efficiency. Heat management - Detecting the temperature of main parts, elements, power sockets, etc. Suitable everywhere - IP protection grade 65, corrosion resistance class $\geq C2$, environmentally friendly battery. Sleek and concealed - The tower features minimalist design to remain relatively invisible. Maximum utilization scope (DOD) 90%.



Battery GROWATT ARK 12.8H-A1 HV set (5x2,56kWh LiFePO4) + controller IP65

Product code 16491

Brand [GROWATT](#)

Protection class IP65

Height 1170.0mm

Width 250.0mm

Length 610.0mm


Weight 160000g

Work environment indoor / outdoor use

Operation temperature -10 °C ... +50°C

Certificates CE

Warranty 10 years



Cables GROWATT ARK 2.5H-A1 Cable Pack

Product code 16698

Brand [GROWATT](#)
Certificates CE

The ARK 2.5H-A1 Cable Pack is for connecting batteries, designed for Growatt batteries to connect them to each other. The product is part of a set and can only be ordered as part of the set. When ordered individually, there will be an additional €50+VAT shipping fee from the EU warehouse.



Battery GROWATT ARK 2.5H-A1 High Voltage 2.5kWh LiFePO4 Battery (XH, SPH, SPA) IP65

Product code 16696

Brand [GROWATT](#)
Protection class IP65
Height 265.0mm
Width 650.0mm
Length 260.0mm
Weight 165000g
Work environment indoor / outdoor use
Operation temperature -10 °C ... +50°C
Certificates CE
Warranty 5 years



GROWATT ARK Battery Base

Product code 16699

Brand [GROWATT](#)
Certificates CE

Growatt ARK 2.5-A1 Battery Base is a battery base designed for Growatt batteries for ground installation. The product is part of a set and can only be ordered as part of the set. When ordering individually, a 50EUR shipping fee from the EU warehouse will be added



Electrical switchboard GROWATT ATS-T

Product code 16566

Brand [GROWATT](#)

Certificates CE

Warranty 2 years



Controller GROWATT BMS BDC 95045-A1 (XH) IP65

Product code 16697

Brand [GROWATT](#)

Protection class IP65

Height 170.0mm

Width 610.0mm

Length 250.0mm

Weight 10000g

Work environment indoor / outdoor
use

Operation temperature -10 °C ...
+50°C

Certificates CE

Warranty 5 years



Controller GROWATT BMS HVC 60050-A1 (SPH, SPA) IP65

Product code 16700

Brand [GROWATT](#)

Protection class IP65

Height 170.0mm

Width 610.0mm

Length 250.0mm

Weight 10000g

Work environment indoor / outdoor
use

Operation temperature -10 °C ...
+50°C

Certificates CE

Warranty 10 years



Battery Shoto HP10- Box5 Pro 20,48kWh LV set (4x5,12kWh LiFePO4) IP20

Product code 17250

Brand Shoto
Output voltage 51.2V
Protection class IP20
Height 250.0mm
Width 440.0mm
Length 580.0mm
Weight 200000g
Operation temperature -5°C~+50°C
Warranty 5 years



Battery Sigenergy SigenStor BAT 5.0 (5.38kWh)

Product code 17177

Brand [Sigenergy](#)
Height 270.0mm
Width 767.0mm
Length 260.0mm
Weight 55000g
Warranty 10 years

5-8 kWh LiFePO4 battery module. 9 battery cells in one 8 kWh pack. 1 to 6 batteries per stack (max 48 kWh). Max 10 stacks in parallel. DOD (Depth of Discharge) 100%. Charging power 6000W. 280 Ah high-capacity battery cells, low voltage, and durable. Multilayer complete battery safety protection. Visible battery status in the mySigen APP application. Fast and easy installation. Smooth backup switch in 0ms. IP66 protection class. Product warranty: 10 years. Any combination of BAT5 and BAT8 models is possible. Only Sigenergy's own batteries can be used in the Sigenergy system



Battery Sigenergy SigenStor BAT 8.0 (8.06kWh)

Product code 17037

Brand [Sigenergy](#)

Warranty 10 years

5-8 kWh LiFePO4 battery module. 9 battery cells in one 8 kWh pack. 1 to 6 batteries per stack (max 48 kWh). Max 10 stacks in parallel. DOD (Depth of Discharge) 100%. Charging power 6000W. 280 Ah high-capacity battery cells, low voltage, and durable. Multilayer complete battery safety protection. Visible battery status in the mySigen APP application. Fast and easy installation. Smooth backup switch in 0ms. IP66 protection class. Product warranty: 10 years. Any combination of BAT5 and BAT8 models is possible. Only Sigenergy's own batteries can be used in the Sigenergy system



Battery STELTEC 10,24kWh HV set (4x2,56kWh LiFePO4) + Battery controller IP65

Product code 16919

Brand STELTEC

Protection class IP65

Height 1030.0mm

Width 600.0mm

Length 210.0mm

Weight 130000g

Work environment indoor use

Operation temperature 10 °C ...

+50°C

Certificates CE

Warranty 5 years

HV Battery System for Growatt SPH TL3 Inverter. Cobalt Free Lithium Iron Phosphate (LFP). Depth of Discharge DOD 90%. Voltage of a single battery module is 48V. Charging and discharging current is 35A. Number of charges 6000 times.



Battery STELTEC 12,8kWh HV set (5x2,56kWh LiFePO4) + Battery controller IP65

Product code 16938

Brand STELTEC
Protection class IP65
Height 1030.0mm
Width 600.0mm
Length 210.0mm
Weight 130000g
Work environment indoor use
Operation temperature 10 °C ...
+50°C
Certificates CE
Warranty 5 years

HV Battery System for Growatt SPH TL3 Inverter. Cobalt Free Lithium Iron Phosphate (LFP). Depth of Discharge DOD 90%. Voltage of a single battery module is 48V. Charging and discharging current is 35A. Number of charges 6000 times.



Battery STELTEC 2,56kWh STE-BSH-2560 LiFePO4 HV modul IP65

Product code 17211

Brand STELTEC
Protection class IP65
Height 1030.0mm
Width 600.0mm
Length 210.0mm
Weight 130000g
Work environment indoor use
Operation temperature 10 °C ...
+50°C
Certificates CE
Warranty 5 years

HV Battery System for Growatt SPH TL3 Inverter. Cobalt Free Lithium Iron Phosphate (LFP). Depth of Discharge DOD 90%. Voltage of a single battery module is 48V. Charging and discharging current is 35A. Number of charges 6000 times.



Battery STELTEC 20,48kWh HV set (5x2,56kWh LiFePO4) + Battery controller IP65

Product code 16854

Brand STELTEC
Protection class IP65
Height 1580.0mm
Width 606.0mm
Length 220.0mm
Weight 200000g
Work environment indoor use
Operation temperature 15 °C ...
+35°C
Certificates CE
Warranty 5 years

HV Battery System for Growatt SPH TL3 Inverter. Cobalt Free Lithium Iron Phosphate (LFP). Depth of Discharge DOD 90%. Voltage of a single battery module is 48V. Charging and discharging current is 35A. Number of charges 6000 times.



Battery STELTEC 25,6kWh HV set (10x2,56kWh LiFePO4) + Battery controller IP65

Product code 16937

Brand STELTEC
Protection class IP65
Height 1030.0mm
Width 600.0mm
Length 210.0mm
Weight 130000g
Work environment indoor use
Operation temperature 10 °C ...
+50°C
Certificates CE
Warranty 5 years

HV Battery System for Growatt SPH TL3 Inverter. Cobalt Free Lithium Iron Phosphate (LFP). Depth of Discharge DOD 90%. Voltage of a single battery module is 48V. Charging and discharging current is 35A. Number of charges 6000 times.



Battery STELTEC 51.2V 102AH 5.22kWh LV module (LiFePO4) white IP54

Product code 16918

Brand STELTEC
Output voltage 48V
Protection class IP54
Height 350.0mm
Width 515.0mm
Length 200.0mm
Weight 46000g
Casing colour white
Warranty 10 years



Battery STELTEC BU5220 51.2V 102AH 5.22kWh rack 3U (LiFePO4) IP20

Product code 16917

Brand STELTEC
Output voltage 48V
Protection class IP20
Height 130.0mm
Width 440.0mm
Length 550.0mm
Weight 46000g
Warranty 10 years



Battery STELTEC E-home 5kW inverter (1 phase) + 10.44kWh batteries 5000W IP54

Product code 16927

Brand STELTEC
Output voltage 230V
Output 5000W
Maximum output 5000W/1m
Protection class IP54
Work environment indoor / outdoor
use
Operation temperature -10 °C ...
+40°C
Certificates CE
Warranty 5 years



Controller STELTEC STE-BC50 BMS+BASE IP65

Product code 17212

Brand STELTEC
Protection class IP65
Height 1030.0mm
Width 600.0mm
Length 210.0mm
Weight 130000g
Work environment indoor use
Operation temperature 10 °C ...
+50°C
Certificates CE
Warranty 5 years



Battery STELTEC STE-BSW-5220 51.2V 102AH 5.22kWh (LiFePO4) white IP54

Product code 15845

Brand STELTEC
Output voltage 48V
Protection class IP54
Height 470.0mm
Width 520.0mm
Length 142.0mm
Weight 48000g
Casing colour white
Warranty 10 years

