



Controller GNE TEK Beebox-H PLC IP65


Product code 16484

Brand GNE TEK
Protection class IP65
Height 65.0mm
Width 210.0mm
Length 220.0mm
Weight 880g
Operation temperature -20...60°C
Certificates CE, LVD, EMC
Warranty 10 years

Beebox-H has an emergency shutdown function, which can be activated either over the internet network or directly from the device. The GNE rapid shutdown system consists of modules behind the solar panels (optimizers) and the control device Beetrans. The modules behind the panels communicate with the control device Beetrans PLC (Power Line Communications). By default, the optimizers are turned off. When the sun shines on the panel, Beetrans sends a signal to the modules (optimizers), and the system opens the circuit of those modules that are producing electricity. If there are malfunctions in the solar panel system, the Beetrans control device disconnects the panels from the circuit. The same happens when pressing the emergency button on the controller - the Beetrans shutdown signal is sent to the modules (optimizers), and each solar panel in the system is disconnected from the circuit. Only individual panel voltages below 60V remain in the system. Up to 60 optimizers can be connected in two strings behind one controller. Works with Honeybee optimizers.











Optimizer GNE TEK Honeybee 650-PLC 1500V 12-75V 650W IP68

Product code 16483

Brand GNE TEK
Supply voltage 12-75V
Output 650W
Maximum output 650W/1m
Rated current 15000mA
Protection class IP68
Height 25.0mm
Width 110.0mm
Length 130.0mm
Weight 588g
In package 1pc
Work environment outdoor use
Operation temperature -40...85°C
Certificates CE, LVD, EMC
Warranty 10 years

