5.08.2025

Power track Corner T white 230V IP20

Product code 13661


Supply voltage 230V Protection class IP20 Casing colour white Warranty 5 years



Controller Linear Rail 30X 3F

Product code 13657

Height 40.0mm Width 68.0mm Length 2832.0mm





Cover Linear Rail S 1200 white

Product code 13659

Length 1500.0mm Casing colour white

Cover plate for empty module of linear light.





Cover Linear Rail S 1500 white

Product code 16037

Length 1500.0mm Casing colour white Warranty 5 years

Cover plate for empty module of linear light.



End cup Linear Rail S white

Product code 13658

Casing colour white



Trunking rail Linear S 1500 white

Product code 13860

Length 1500.0mm Casing colour white Warranty 5 years

Light rail module for attaching LED lights. Multi-channel wiring allows for simple and efficient wiring. Illuminate your world with LED House professionals - check out our project portfolio here!







Power track PROLUMEN Corner L white 230V IP20



Brand PROLUMEN
Supply voltage 230V
Protection class IP20
Casing colour white
Warranty 5 years



Power track PROLUMEN Corner L white 230V IP20

Product code 13663

Brand PROLUMEN
Supply voltage 230V
Protection class IP20
Casing colour white
Warranty 5 years



Power cable PROLUMEN Feed-in connector 5 wires

Product code 16105

Brand **PROLUMEN**







Power cable PROLUMEN Feed-in connector 8 wires



LED luminaire PROLUMEN Linear C 1500 + Emergency white 230V 50W 7400lm 90° IP20 DALI 840



Product code 17666 DALI dimmable

Brand PROLUMEN Supply voltage 230V Dimmable DALI Output 50W Maximum output 50W/1m Luminous flux 7400lumens Luminaire's efficiency Im79 148W Correlated colour temperature pure white 4000K Lens angle 90 Cri 80 Ugr 19 Sdcm - macadam ellipses 3 Protection class IP20 Lifespan 50000h Width 60.0mm Length 1500.0mm Casing colour white Casing material metal Polishing matt Impact resistance IK05 Work environment indoor use Certificates CE, RoHS Warranty 5 years







Suspension cord PROLUMEN Linear Rail S 1,5m

Product code 13660

Brand PROLUMEN





Power track PROLUMEN Linear Rail S 1500 white

Product code 16911

Brand PROLUMEN Length 1500.0mm Casing colour white Warranty 5 years

Light rail module for attaching LED lights. Multi-channel wiring allows for simple and efficient wiring. Illuminate your world with LED House professionals - check out our project portfolio here!



Power track PROLUMEN Linear Rail S 1500 white

Product code 16912

Brand PROLUMEN Length 1500.0mm Casing colour white Warranty 5 years

Light rail module for attaching LED lights. Multi-channel wiring allows for simple and efficient wiring. Illuminate your world with LED House professionals - check out our project portfolio here!



Suspension cord PROLUMEN Linear Rail S 5m

Product code 16914

Brand PROLUMEN





Power track PROLUMEN Linear Rail S 600 white

Product code 17668

Brand PROLUMEN
Length 600.0mm
Casing colour white
Warranty 5 years

Light rail module for attaching LED lights. Multi-channel wiring allows for simple and efficient wiring. Illuminate your world with LED House professionals - check out our project portfolio here!



PROLUMEN Linear Rail S cable gland

Product code 17669

Brand <u>PROLUMEN</u> Warranty 5 years

Illuminate your world with LED House professionals - <u>check out our project</u> <u>portfolio here!</u>





LED luminaire PROLUMEN Linear S 1500 35/40/45/50W 180lm/W white 230V 120° IP20 840

Product code 16227

Brand PROLUMEN Supply voltage 230V Correlated colour temperature pure white 4000K Lens angle 120 Cri 80 Uar 19 Protection class IP20 Lifespan 50000h Length 1500.0mm Casing colour white Casing material metal Polishing matt Impact resistance IK05 Work environment indoor use Certificates CE, RoHS Warranty 5 years

PROLUMEN Linear S 1500 is a linear luminaire that is installed onto the power track. This luminaire series offers various power options and configurations, allowing for lighting customization based on specific requirements and room characteristics. The IP20 protection class ensures durability against dust and minor liquid ingress, making them suitable for various indoor environments such as offices, shopping centers, or homes. Additionally, there is also the PROLUMEN Linear S 1500 model available, which supports the DALI system, enabling advanced management and control of the lighting according to the needs Illuminate your world with LED House professionals - check out our project portfolio here!



LED luminaire PROLUMEN Linear S 1500 35/40/45/50W 180lm/W






white 230V 9000lm 90° IP20 DALI 840

Product code 17649 DALI dimmable

Brand PROLUMEN Supply voltage 230V Dimmable DALI Luminous flux 9000lumens Correlated colour temperature pure white 4000K Lens angle 90 Cri 80 Uar 19 Sdcm - macadam ellipses 3 Protection class IP20 Lifespan 50000h Width 60.0mm Length 1500.0mm Casing colour white Casing material metal Polishing matt Impact resistance IK05 Work environment indoor use Certificates CE. RoHS Warranty 5 years









LED luminaire PROLUMEN Linear S 1500 35/40/45/50W 180lm/W white 230V 90° IP20 830

Product code 16004

Brand PROLUMEN Supply voltage 230V Correlated colour temperature warm white 3000K Lens angle 90 Cri 80 Uar 19 Protection class IP20 Lifespan 50000h Length 1500.0mm Casing colour white Casing material metal Polishing matt Impact resistance IK05 Work environment indoor use Certificates CE, RoHS Warranty 5 years









LED luminaire PROLUMEN Linear S 1500 35/40/45/50W 180lm/W white 230V 90° IP20 840

Product code 16012

Brand PROLUMEN Supply voltage 230V Correlated colour temperature pure white 4000K Lens angle 90 Cri 80 Uar 19 Protection class IP20 Lifespan 50000h Width 60.0mm Length 1500.0mm Casing colour white Casing material metal Polishing matt Impact resistance IK05 Work environment indoor use Certificates CE, RoHS Warranty 5 years









LED luminaire PROLUMEN Linear S 1500 55/60/65/70W 180lm/W white 230V 70W 12600lm 120° IP20 830

Product code 17620

Brand PROLUMEN Supply voltage 230V Output 70W Maximum output 70W/1m Luminous flux 12600lumens Luminaire's efficiency Im79 180W Correlated colour temperature warm white 3000K Lens angle 120 Cri 80 Ugr 19 Sdcm - macadam ellipses 3 Protection class IP20 Lifespan 50000h Length 1500.0mm In package 1pc In box 10pcs Casing colour white Casing material metal Polishing matt Impact resistance IK05 Work environment indoor use Certificates CE, RoHS Warranty 5 years









LED luminaire PROLUMEN Linear S 1500 55/60/65/70W 180lm/W white 230V 70W 12600lm 90° IP20 840

Product code 18110

Brand PROLUMEN Supply voltage 230V Output 70W Maximum output 70W/1m Luminous flux 12600lumens Luminaire's efficiency Im79 180W Correlated colour temperature pure white 4000K Lens angle 90 Cri 80 Ugr 19 Sdcm - macadam ellipses 3 Protection class IP20 Lifespan 50000h Length 1500.0mm In package 1pc In box 10pcs Casing colour white Casing material metal Polishing matt Impact resistance IK05 Work environment indoor use Certificates CE, RoHS Warranty 5 years









LED luminaire PROLUMEN Linear S 1500 70W 180lm/W white 230V 12600lm CRI80 120° IP20 DALI 3000K, 4000K, 6000K 3CCT

Product code 16908 DALI dimmable

Brand PROLUMEN Supply voltage 230V Dimmable DALI Luminous flux 12600lumens Correlated colour temperature 3CCT 3000K, 4000K, 6000K Lens angle 120 Cri 80 Ugr 19 Protection class IP20 Lifespan 50000h Length 1500.0mm Casing colour white Casing material metal Polishing matt Power supply TRIDONIC Impact resistance IK05 Work environment indoor use Certificates CE, RoHS Warranty 5 years









LED luminaire PROLUMEN Linear S 1500 Emergency white 230V 50W 9250lm 90° IP20 840

Product code 17664

Brand PROLUMEN Supply voltage 230V Output 50W Maximum output 50W/1m Luminous flux 9250lumens Luminaire's efficiency Im79 185W Correlated colour temperature pure white 4000K Lens angle 90 Cri 80 Ugr 19 Sdcm - macadam ellipses 3 Protection class IP20 Lifespan 50000h Width 60.0mm Length 1500.0mm Casing colour white Casing material metal Polishing matt Impact resistance IK05 Work environment indoor use Certificates CE, RoHS Warranty 5 years









LED luminaire PROLUMEN Linear S 1500 white 230V 50W 9250lm 90° IP20 DALI 840

Product code 17665 DALI dimmable

Brand PROLUMEN Supply voltage 230V Dimmable DALI Output 50W Maximum output 50W/1m Luminous flux 9250lumens Luminaire's efficiency Im79 185W Correlated colour temperature pure white 4000K Lens angle 90 Cri 80 Ugr 19 Sdcm - macadam ellipses 3 Protection class IP20 Lifespan 50000h Width 60.0mm Length 1500.0mm Casing colour white Casing material metal Polishing matt Impact resistance IK05 Work environment indoor use Certificates CE, RoHS Warranty 5 years



Power track PROLUMEN Linear S end cap white

Product code 17667

Brand <u>PROLUMEN</u>
Casing colour white
Warranty 5 years

Illuminate your world with LED House professionals - <u>check out our project</u> <u>portfolio here!</u>





Power track PROLUMEN Linear S module 1500 white

Product code 17671

Brand PROLUMEN Length 1500.0mm Casing colour white Warranty 5 years

Illuminate your world with LED House professionals - check out our project portfolio here!



Power track PROLUMEN Linear S module 600 white

Product code 17670

Brand PROLUMEN Length 600.0mm Casing colour white Warranty 5 years


Illuminate your world with LED House professionals - <u>check out our project</u> <u>portfolio here!</u>







Power track PROLUMEN Linear S module for EXIT 600 white DALI



LED luminaire PROLUMEN Linear S-line 1500 35/40/45/50W 180lm/W white 230V 50W 9000lm 120° IP20 830



Product code 16104

Brand PROLUMEN Supply voltage 230V Output 50W Maximum output 50W/1m Luminous flux 9000lumens Luminaire's efficiency Im79 180W Correlated colour temperature warm white 3000K Lens angle 120 Cri 80 Ugr 19 Protection class IP20 Lifespan 50000h Length 1500.0mm In box 10pcs Casing colour white Casing material metal Polishing matt Impact resistance IK05 Work environment indoor use Certificates CE, RoHS Warranty 5 years



