



Carrier for street light ø60mm tube

Product code 14456

Installation opening diameter 60mm





LED street light LT H gray 230V 33W 3898Im IP65 DALI 830

Product code 19111 DALI dimmable

Supply voltage 230V Power factor 0.90 Dimmable DALI Output 33W Maximum output 33W/1m Luminous flux 3898lumens Luminaire's efficiency Im79 118W Correlated colour temperature warm white 3000K Cri 80 Sdcm - macadam ellipses 3 Protection class IP65 Lifespan 100000h Llmf tm21 L80B10 @25°C 100.000h Height 195.0mm Width 150.0mm Length 550.0mm In package 1pc Casing colour gray Casing material aluminum + plastic Polishing matt Impact resistance IK08 Work environment outdoor use Operation temperature -40 ~ 45°C Certificates CE Warranty 5 years







LED street light PROLUMEN ADELA black 230V 70W 9100lm 60x140° IP66 DALI 830

Product code 18152 DALI dimmable

Brand PROLUMEN Supply voltage 230V Power factor 0.95 Dimmable DALI Output 70W Maximum output 70W/1m Luminous flux 9100lumens Luminaire's efficiency Im79 130W Correlated colour temperature warm white 3000K Lens angle 60x140 Source of light **LUMILEDS** Cri 80 Sdcm - macadam ellipses 6 Protection class IP66 Lifespan 100000h Llmf tm21 L80B10 @25°C 100.000h Height 205.0mm Width 272.0mm Length 508.0mm Casing colour black Casing material aluminum Polishing matt Power supply **SOSEN** Impact resistance IK08 Work environment outdoor use Operation temperature -40 °C ... +50°C

A street light that makes moving in urban spaces safe even in the dark of night! It is perfect for driveways, streets, parking lots, and all other outdoor areas that need safe, affordable, and efficient lighting. Protection classes IP66 and IK08 ensure the fixture's durability and long life in outdoor conditions. Additionally, the light is ideal for collaboration with security cameras see the product specifications for more details. Furthermore, the maintenance process of the light has been made exceptionally easy allowing you to save on labor and time! This feature is ensured by the removable electric plate, which makes connecting wires during installation particularly convenient.

Certificates CE Warranty 5 years







LED street light PROLUMEN ADELA MW + Lux black 230V 100W 13400lm 60x140° IP66 1-10V 830

Product code 17094 1-10V dimmable

Brand PROLUMEN Supply voltage 230V Power factor 0.95 Dimmable 1-10V Output 100W Maximum output 100W/1m Luminous flux 13400lumens Luminaire's efficiency Im79 134W Correlated colour temperature warm white 3000K Lens angle 60x140 Source of light **LUMILEDS** Cri 80 Sdcm - macadam ellipses 6 Protection class IP66 Lifespan 100000h Llmf tm21 L80B10 @25°C 100.000h Height 205.0mm Width 272.0mm Length 508.0mm Casing colour black Casing material aluminum Polishing matt Power supply **INVENTRONICS** Impact resistance IK08 Work environment outdoor use Operation temperature -40 °C ... +50°C

A street light that makes moving in urban spaces safe even in the dark of night! It is perfect for driveways, streets, parking lots, and all other outdoor areas that need safe, affordable, and efficient lighting. Protection classes IP66 and IK08 ensure the fixture's durability and long life in outdoor conditions. Additionally, the light is ideal for collaboration with security cameras see the product specifications for more details. Furthermore, the maintenance process of the light has been made exceptionally easy allowing you to save on labor and time! This feature is ensured by the removable electric plate, which makes connecting wires during installation particularly convenient.

Certificates CE Warranty 5 years








LED street light PROLUMEN ADELA MW + Lux black 230V 30W 4100lm 60x140° IP66 1-10V 830

Product code 17045 1-10V dimmable

Brand PROLUMEN Supply voltage 230V Power factor 0.95 Dimmable 1-10V Output 30W Maximum output 30W/1m Luminous flux 4100lumens Luminaire's efficiency Im79 137W Correlated colour temperature warm white 3000K Lens angle 60x140 Source of light **LUMILEDS** Cri 80 Sdcm - macadam ellipses 2 Protection class IP66 Lifespan 100000h Llmf tm21 L80B10 @25°C 100.000h Height 201.2mm Width 269.8mm Length 479.7mm Casing colour black Casing material aluminum Polishing matt Power supply **INVENTRONICS** Impact resistance IK08 Work environment outdoor use Operation temperature -40 °C ... +50°C Certificates CE Warranty 5 years

Smart streetlight that makes moving in urban spaces safe even in the darkness of the night! Ideal for driveways, streets, parking lots, and all other outdoor areas requiring safe and efficient lighting. The luminaire is perfectly suited for integration with security cameras (see additional details in the product specifications). Additionally, the luminaire's maintenance process has been made particularly easy - saving on labor and time! This feature is provided by a removable electrical board, making wiring connections exceptionally convenient during installation.







LED street light PROLUMEN ADELA MW + Lux black 230V 50W 6500lm 60x140° IP66 0-10V 830

Product code 17049 0-10V dimmable

Brand PROLUMEN Supply voltage 230V Power factor 0.95 Dimmable 0-10V Output 50W Maximum output 50W/1m Luminous flux 6500lumens Luminaire's efficiency Im79 130W Correlated colour temperature warm white 3000K Lens angle 60x140 Source of light **LUMILEDS** Cri 80 Sdcm - macadam ellipses 6 Protection class IP66 Lifespan 100000h Llmf tm21 L80B10 @25°C 100.000h Height 201.2mm Width 269.8mm Length 479.7mm Casing colour black Casing material aluminum Polishing matt Power supply **INVENTRONICS** Impact resistance IK08 Work environment outdoor use Operation temperature -40 °C ... +50°C Certificates CE

Smart streetlight that makes moving in urban spaces safe even in the darkness of the night! Ideal for driveways, streets, parking lots, and all other outdoor areas requiring safe and efficient lighting. The luminaire is perfectly suited for integration with security cameras (see additional details in the product specifications). Additionally, the luminaire's maintenance process has been made particularly easy - saving on labor and time! This feature is provided by a removable electrical board, making wiring connections exceptionally convenient during installation.







LED street light PROLUMEN Avarta 40W 5600lm 120° No dim 740

Product code 19056 No dim dimmable

Brand PROLUMEN
Dimmable No dim
Output 40W
Maximum output 40W/1m
Luminous flux 5600lumens
Luminaire's efficiency Im79 140W
Correlated colour temperature pure
white 4000K
Lens angle 120
Cri 70
Power supply SOSEN
Warranty 5 years



LED street light PROLUMEN BEAST SF bracket black 230V 100W 16500lm 130x60° IP66 1-10V 740





Product code 18226 1-10V dimmable

Brand PROLUMEN Supply voltage 230V Power factor 0.95 Dimmable 1-10V Output 100W Maximum output 100W/1m Luminous flux 16500lumens Luminaire's efficiency Im79 165W Correlated colour temperature pure white 4000K Lens angle 130x60 Source of light **LUMILEDS** Cri 70 Sdcm - macadam ellipses 6 Protection class IP66 Lifespan 100000h Llmf tm21 L80B10 @25°C 100.000h Height 105.0mm Width 304.0mm Length 428.0mm Weight 3820g Casing colour black Casing material aluminum + plastic Polishing matt Power supply **INVENTRONICS** Impact resistance IK08 Work environment outdoor use Operation temperature -40° - +50°C Certificates CE, ENEC, CB Warranty 5 years







LED street light PROLUMEN BEAST SF bracket black 230V 200W 30000lm 130x60° IP66 1-10V 740

Product code 17903 1-10V dimmable

Brand PROLUMEN Supply voltage 230V Power factor 0.95 Dimmable 1-10V Output 200W Maximum output 200W/1m Luminous flux 30000lumens Luminaire's efficiency Im79 150W Correlated colour temperature pure white 4000K Lens angle 130x60 Source of light **LUMILEDS** Cri 70 Sdcm - macadam ellipses 6 Protection class IP66 Lifespan 100000h Llmf tm21 L80B10 @25°C 100.000h Height 105.0mm Width 304.0mm Length 428.0mm Weight 3820g Casing colour black Casing material aluminum + plastic Polishing matt Power supply **INVENTRONICS** Impact resistance IK08 Work environment outdoor use Operation temperature -40° - +50°C Certificates CE, ENEC, CB Warranty 5 years








LED street light PROLUMEN BEAST TR bracket black 230V 100W 16500lm 130x60° IP66 1-10V 740

Product code 17862 1-10V dimmable

Brand PROLUMEN Supply voltage 230V Power factor 0.95 Dimmable 1-10V Output 100W Maximum output 100W/1m Luminous flux 16500lumens Luminaire's efficiency Im79 165W Correlated colour temperature pure white 4000K Lens angle 130x60 Source of light LUMILEDS Cri 70 Sdcm - macadam ellipses 6 Protection class IP66 Lifespan 100000h Llmf tm21 L80B10 @25°C 100.000h Height 88.0mm Width 304.0mm Length 428.0mm Casing colour black Casing material aluminum + plastic Polishing matt Power supply **INVENTRONICS** Impact resistance IK08 Work environment outdoor use Operation temperature -40° - +50°C Certificates CE, ENEC, CB Warranty 5 years







LED street light PROLUMEN BEAST TR bracket black 230V 240W 40947lm 100x140° IP66 0-10V 740

Product code 17802 0-10V dimmable

Brand PROLUMEN Supply voltage 230V Power factor 0.95 Dimmable 0-10V Output 240W Maximum output 240W/1m Luminous flux 40947lumens Luminaire's efficiency Im79 171W Correlated colour temperature pure white 4000K Lens angle 100x140 Source of light LUMILEDS Cri 70 Sdcm - macadam ellipses 6 Protection class IP66 Lifespan 100000h Height 184.2mm Width 304.0mm Length 595.4mm Weight 7030g Casing colour black Casing material aluminum Polishing matt Power supply **INVENTRONICS** Impact resistance IK08 Work environment outdoor use Operation temperature -40° - +50°C Certificates CE, ENEC, CB Warranty 5 years







LED street light PROLUMEN BEAST TR bracket black 230V 400W 66419lm 100x140° IP66 1-10V 750

Product code 17803 1-10V dimmable

Brand PROLUMEN Supply voltage 230V Power factor 0.95 Dimmable 1-10V Output 400W Maximum output 400W/1m Luminous flux 66419lumens Luminaire's efficiency Im79 166W Correlated colour temperature pure white 5000K Lens angle 100x140 Source of light LUMILEDS Cri 70 Sdcm - macadam ellipses 6 Protection class IP66 Lifespan 100000h Height 199.6mm Width 339.6mm Length 767.5mm Weight 1099g Casing colour black Casing material aluminum Polishing matt Power supply **INVENTRONICS** Impact resistance IK08 Work environment outdoor use Operation temperature -40° - +50°C Certificates CE, ENEC, CB Warranty 5 years







LED street light PROLUMEN BEAST U bracket black 230V 400W 66419lm 100x140° IP66 1-10V 750

Product code 17804 1-10V dimmable

Brand PROLUMEN Supply voltage 230V Power factor 0.95 Dimmable 1-10V Output 400W Maximum output 400W/1m Luminous flux 66419lumens Luminaire's efficiency Im79 166W Correlated colour temperature pure white 5000K Lens angle 100x140 Source of light LUMILEDS Cri 70 Sdcm - macadam ellipses 6 Protection class IP66 Lifespan 100000h Height 199.6mm Width 339.6mm Length 767.5mm Weight 1099g Casing colour black Casing material aluminum Polishing matt Power supply **INVENTRONICS** Impact resistance IK08 Work environment outdoor use Operation temperature -40° - +50°C Certificates CE, ENEC, CB Warranty 5 years







LED street light PROLUMEN BEAST YK bracket black 230V 200W 30000lm 130x60° IP66 1-10V 740

Product code 17861 1-10V dimmable

Brand PROLUMEN Supply voltage 230V Power factor 0.95 Dimmable 1-10V Output 200W Maximum output 200W/1m Luminous flux 30000lumens Luminaire's efficiency Im79 150W Correlated colour temperature pure white 4000K Lens angle 130x60 Source of light **LUMILEDS** Cri 70 Sdcm - macadam ellipses 6 Protection class IP66 Lifespan 100000h Llmf tm21 L80B10 @25°C 100.000h Height 105.0mm Width 304.0mm Length 428.0mm Weight 3820g Casing colour black Casing material aluminum + plastic Polishing matt Power supply **INVENTRONICS** Impact resistance IK08 Work environment outdoor use Operation temperature -40° - +50°C Certificates CE, ENEC, CB Warranty 5 years







LED street light PROLUMEN BEAST YK bracket black 230V 300W 48900lm 130x60° IP66 1-10V 740

Product code 17863 1-10V dimmable

Brand PROLUMEN Supply voltage 230V Power factor 0.95 Dimmable 1-10V Output 300W Maximum output 300W/1m Luminous flux 48900lumens Luminaire's efficiency Im79 163W Correlated colour temperature pure white 4000K Lens angle 130x60 Source of light LUMILEDS Cri 70 Sdcm - macadam ellipses 6 Protection class IP66 Lifespan 100000h Llmf tm21 L70 @25°C 100.000h Height 88.0mm Width 304.0mm Length 428.0mm Casing colour black Casing material aluminum + plastic Polishing matt Power supply **INVENTRONICS** Impact resistance IK08 Work environment outdoor use Operation temperature -40° - +50°C Certificates CE, ENEC, CB Warranty 5 years







LED street light PROLUMEN Hermoso 30/ 40/ 60W 9600lm CRI70 TP III° No dim 2200K, 3000K, 4000K 3CCT

Product code 19054 No dim dimmable

Brand PROLUMEN
Dimmable No dim
Output 30/ 40/ 60W
Maximum output 30/ 40W/1m
Luminous flux 9600lumens
Correlated colour temperature 3CCT
2200K, 3000K, 4000K
Lens angle TP III
Cri 70
Power supply SOSEN
Warranty 5 years

Outdoor light with an elegant style. Available options: 30W, 40W, 60W, 90W. This light is suitable for poles with a diameter of 60-80mm. It is perfect for driveways, streets, parking lots, and all other outdoor areas that need safe, affordable, and efficient lighting.



LED street light PROLUMEN Hermoso black 230V 30W 4000lm 90° IP66 730



16/33 26.08.2025

Product code 17590

Brand **PROLUMEN** Supply voltage 230V Power factor 0.95 Output 30W Maximum output 30W/1m Luminous flux 4000lumens Luminaire's efficiency Im79 133W Correlated colour temperature warm white 3000K Lens angle 90 Source of light PHILIPS LED Cri 70 Sdcm - macadam ellipses 6 Protection class IP66 Lifespan 50000h Llmf tm21 L90B10 @25°C 50.000h Height 539.0mm Diameter 422.0mm Weight 27500g In package 1pc Casing colour black Casing material aluminum Polishing matt Power supply **SOSEN** Impact resistance IK08 Work environment outdoor use Operation temperature -40 °C ... +50°C Certificates CE Warranty 5 years

Outdoor light with an elegant style. Available options: 30W, 40W, 60W, 90W. This light is suitable for poles with a diameter of 60-80mm. It is perfect for driveways, streets, parking lots, and all other outdoor areas that need safe, affordable, and efficient lighting.







LED street light PROLUMEN Hermoso black 230V 40W 6000lm 90° IP66 830

Product code 17044

Brand PROLUMEN Supply voltage 230V Power factor 0.95 Output 40W Maximum output 40W/1m Luminous flux 6000lumens Luminaire's efficiency Im79 150W Correlated colour temperature warm white 3000K Lens angle 90 Source of light **LUMILEDS** Cri 80 Sdcm - macadam ellipses 6 Protection class IP66 Lifespan 50000h Llmf tm21 L90B10 @25°C 50.000h Height 539.0mm Diameter 422.0mm Weight 5700g In package 1pc Casing colour black Casing material aluminum Polishing matt Power supply MEAN WELL Impact resistance IK08 Work environment outdoor use Operation temperature -40 °C ... +50°C Certificates CE

Outdoor light with an elegant style. Available options: 30W, 40W, 60W, 90W. This light is suitable for poles with a diameter of 60-80mm. It is perfect for driveways, streets, parking lots, and all other outdoor areas that need safe, affordable, and efficient lighting.







LED street light PROLUMEN Hermoso black 230V 60W 8400lm 90° IP66 730

Product code 19419

Brand PROLUMEN Supply voltage 230V Power factor 0.95 Output 60W Maximum output 60W/1m Luminous flux 8400lumens Luminaire's efficiency Im79 140W Correlated colour temperature warm white 3000K Lens angle 90 Source of light PHILIPS LED Cri 70 Sdcm - macadam ellipses 6 Protection class IP66 Lifespan 50000h Llmf tm21 L90B10 @25°C 50.000h Height 539.0mm Diameter 422.0mm In package 1pc In box 2pcs Casing colour black Casing material aluminum Polishing matt Power supply **SOSEN** Impact resistance IK08 Work environment outdoor use Operation temperature -40 °C ... +50°C Certificates CE

Outdoor light with an elegant style. Available options: 30W, 40W, 60W, 90W. This light is suitable for poles with a diameter of 60-80mm. It is perfect for driveways, streets, parking lots, and all other outdoor areas that need safe, affordable, and efficient lighting.







LED street light PROLUMEN Hermoso black 230V 60W 8400lm 90° IP66 830

Product code 17844

Brand PROLUMEN Supply voltage 230V Power factor 0.95 Output 60W Maximum output 60W/1m Luminous flux 8400lumens Luminaire's efficiency Im79 140W Correlated colour temperature warm white 3000K Lens angle 90 Source of light PHILIPS LED Cri 80 Sdcm - macadam ellipses 6 Protection class IP66 Lifespan 50000h Llmf tm21 L90B10 @25°C 50.000h Height 539.0mm Diameter 422.0mm Weight 5700g In package 1pc Casing colour black Casing material aluminum Polishing matt Power supply MEAN WELL Impact resistance IK08 Work environment outdoor use Operation temperature -40 °C ... +50°C Certificates CE

Outdoor light with an elegant style. Available options: 30W, 40W, 60W, 90W. This light is suitable for poles with a diameter of 60-80mm. It is perfect for driveways, streets, parking lots, and all other outdoor areas that need safe, affordable, and efficient lighting.







LED street light PROLUMEN Hermoso black 230V 90W 13500lm 90° IP66 830

Product code 17845

Brand PROLUMEN Supply voltage 230V Power factor 0.95 Output 90W Maximum output 90W/1m Luminous flux 13500lumens Luminaire's efficiency Im79 150W Correlated colour temperature warm white 3000K Lens angle 90 Source of light **LUMILEDS** Cri 80 Sdcm - macadam ellipses 6 Protection class IP66 Lifespan 50000h Llmf tm21 L90B10 @25°C 50.000h Height 539.0mm Diameter 422.0mm Weight 5700g In package 1pc Casing colour black Casing material aluminum Polishing matt Power supply MEAN WELL Impact resistance IK08 Work environment outdoor use Operation temperature -40 °C ... +50°C Certificates CE Warranty 5 years

Outdoor light with an elegant style. Available options: 30W, 40W, 60W, 90W. This light is suitable for poles with a diameter of 60-80mm. It is perfect for driveways, streets, parking lots, and all other outdoor areas that need safe, affordable, and efficient lighting.








LED street light PROLUMEN Meta 100W 13500lm TP II° No dim 727

Product code 19038 No dim dimmable

Brand PROLUMEN
Dimmable No dim
Output 100W
Maximum output 100W/1m
Luminous flux 13500lumens
Luminaire's efficiency Im79 135W
Correlated colour temperature warm
white 2700K
Lens angle TP II
Cri 70
Power supply MEAN WELL
Warranty 5 years





LED street light PROLUMEN Meta 20-50W 6750lm TP II° No dim 727

Product code 19039 No dim dimmable

Brand PROLUMEN
Dimmable No dim
Output 20-50W
Maximum output 20-50W/1m
Luminous flux 6750lumens
Correlated colour temperature warm
white 2700K
Lens angle TP II
Cri 70
Power supply SOSEN
Warranty 5 years








LED street light PROLUMEN Meta 20-50W 7500lm TP II° No dim 740

Product code 19041 No dim dimmable

Brand PROLUMEN
Dimmable No dim
Output 20-50W
Maximum output 20-50W/1m
Luminous flux 7500lumens
Correlated colour temperature pure
white 4000K
Lens angle TP II
Cri 70
Power supply SOSEN
Warranty 5 years





LED street light PROLUMEN Meta 40-100W 13500lm TP II° No dim 727

Product code 19040 No dim dimmable

Brand PROLUMEN
Dimmable No dim
Output 40-100W
Maximum output 40-100W/1m
Luminous flux 13500lumens
Correlated colour temperature warm
white 2700K
Lens angle TP II
Cri 70
Power supply SOSEN
Warranty 5 years







LED street light PROLUMEN Poseidon 40W 6400lm TP III° 727

Product code 19042

Brand PROLUMEN
Output 40W
Maximum output 40W/1m
Luminous flux 6400lumens
Luminaire's efficiency Im79 160W
Correlated colour temperature warm
white 2700K
Lens angle TP III
Cri 70
Power supply Without driver
Warranty 5 years

LED Street Light for illuminating streets and parking lots. Tube mounting for 60mm tube. This is a project sales product, please inquire about the delivery time and availability from our customer service.



LED street light PROLUMEN Poseidon 40W 7200lm TP III° 740

Product code 19044

Brand PROLUMEN
Output 40W
Maximum output 40W/1m
Luminous flux 7200lumens
Luminaire's efficiency Im79 180W
Correlated colour temperature pure
white 4000K
Lens angle TP III
Cri 70
Power supply Without driver
Warranty 5 years







LED street light PROLUMEN Poseidon 75W 13500lm TP III° 740

Product code 19377

Brand PROLUMEN
Output 75W
Maximum output 75W/1m
Luminous flux 13500lumens
Luminaire's efficiency Im79 180W
Correlated colour temperature pure
white 4000K
Lens angle TP III
Cri 70
Power supply Without driver
Warranty 5 years

LED Street Light for illuminating streets and parking lots. Tube mounting for 60mm tube. This is a project sales product, please inquire about the delivery time and availability from our customer service.



LED street light PROLUMEN Poseidon 80W 12800lm TP III° 727

Product code 19043

Brand PROLUMEN
Output 80W
Maximum output 80W/1m
Luminous flux 12800lumens
Luminaire's efficiency Im79 160W
Correlated colour temperature warm
white 2700K
Lens angle TP III
Cri 70
Power supply Without driver
Warranty 5 years





25/33 26.08.2025

LED street light PROLUMEN Poseidon 80W 14400lm TP III° 740

Product code 19045

Brand <u>PROLUMEN</u>

Warranty 5 years

Output 80W
Maximum output 80W/1m
Luminous flux 14400lumens
Luminaire's efficiency Im79 180W
Correlated colour temperature pure
white 4000K
Lens angle TP III
Cri 70
Power supply Without driver

LED Street Light for illuminating streets and parking lots. Tube mounting for 60mm tube. This is a project sales product, please inquire about the delivery time and availability from our customer service.



LED street light PROLUMEN Poseidon gray 230V 100W 13000lm $60x140^{\circ}$ IP66 740

Product code 14977

Brand PROLUMEN Supply voltage 230V Output 100W Maximum output 100W/1m Luminous flux 13000lumens Luminaire's efficiency Im79 130W Correlated colour temperature pure white 4000K Lens angle 60x140 Source of light CREE LED Cri 70 Sdcm - macadam ellipses 6 Protection class IP66 Lifespan 50000h Llmf tm21 L90B10 @25°C 50.000h Height 100.0mm Width 235.0mm Length 610.0mm Installation opening diameter 60mm Casing colour gray Casing material aluminum Polishing matt Power supply MEAN WELL Impact resistance IK08 Work environment outdoor use Operation temperature -40°C - +70°C

Certificates CE, ENEC







LED street light PROLUMEN Poseidon gray 230V 100W 15000lm IP66 DALI 840

Product code 16972 DALI dimmable

Brand PROLUMEN Supply voltage 230V Dimmable DALI Output 100W Maximum output 100W/1m Luminous flux 15000lumens Luminaire's efficiency Im79 150W Correlated colour temperature pure white 4000K Source of light **CREE LED** Cri 80 Sdcm - macadam ellipses 6 Protection class IP66 Lifespan 50000h Llmf tm21 L90B10 @25°C 50.000h Height 109.0mm Width 240.0mm Length 613.0mm Installation opening diameter 60mm Weight 4572g Package weight 5270g In package 1pc Casing colour gray Casing material aluminum Polishing matt Impact resistance IK08 Work environment outdoor use

LED Street Light for illuminating streets and parking lots. Tube mounting for 60mm tube. This is a project sales product, please inquire about the delivery time and availability from our customer service.

Operation temperature -40°C - +70°C

Certificates CE, ENEC







LED street light PROLUMEN Poseidon gray 230V 24W 3600lm 150x150° IP66 830

Product code 16250

Brand PROLUMEN Supply voltage 230V Output 24W Maximum output 24W/1m Luminous flux 3600lumens Luminaire's efficiency Im79 150W Correlated colour temperature warm white 3000K Lens angle 150x150 Source of light **CREE LED** Cri 80 Sdcm - macadam ellipses 6 Protection class IP66 Lifespan 50000h Llmf tm21 L90B10 @25°C 50.000h Height 100.0mm Width 200.0mm Length 570.0mm Installation opening diameter 60mm Casing colour gray Casing material aluminum Polishing matt Power supply MEAN WELL Impact resistance IK08 Work environment outdoor use Operation temperature -40°C - +70°C Certificates CE. ENEC







LED street light PROLUMEN Poseidon gray 230V 40W 6400lm 150x150° IP66 830

Product code 16249

Brand PROLUMEN Supply voltage 230V Output 40W Maximum output 40W/1m Luminous flux 6400lumens Luminaire's efficiency Im79 160W Correlated colour temperature warm white 3000K Lens angle 150x150 Source of light **CREE LED** Cri 80 Sdcm - macadam ellipses 6 Protection class IP66 Lifespan 50000h Llmf tm21 L90B10 @25°C 50.000h Height 100.0mm Width 235.0mm Length 610.0mm Installation opening diameter 60mm Casing colour gray Casing material aluminum Polishing matt Power supply MEAN WELL Impact resistance IK08 Work environment outdoor use Operation temperature -40°C - +70°C Certificates CE. ENEC

LED Street Light for illuminating streets and parking lots. Tube mounting for 60mm tube. This is a project sales product, please inquire about the delivery time and availability from our customer service.



LED street light PROLUMEN Ryder black 230V 70W 7700lm IP66 DALI 830



29/33 26.08.2025

Product code 18154 DALI dimmable

Brand PROLUMEN Supply voltage 230V Power factor 0.95 Dimmable DALI Output 70W Maximum output 70W/1m Luminous flux 7700lumens Luminaire's efficiency Im79 110W Correlated colour temperature warm white 3000K Source of light **LUMILEDS** Cri 80 Sdcm - macadam ellipses 6 Protection class IP66 Lifespan 100000h Llmf tm21 L80B10 @25°C 100.000h Height 282.0mm Diameter 610.0mm Casing colour black Casing material aluminum Polishing matt Power supply **SOSEN** Impact resistance IK08 Work environment outdoor use Operation temperature -40 °C ... +50°C Certificates CE Warranty 5 years







30/33 26.08.2025

LED street light PROLUMEN Slim silvery 230V 150W 18000lm 70x140° IP66 840


Product code 14326

Brand PROLUMEN Supply voltage 230V Output 150W Maximum output 150W/1m Luminous flux 18000lumens Luminaire's efficiency Im79 120W Correlated colour temperature pure white 4000K Lens angle 70x140 Source of light LUMILEDS Cri 80 Protection class IP66 Lifespan 50000h Installation opening diameter 60mm Weight 2100g In package 1pc Casing colour silvery Casing material aluminum Polishing matt Power supply MEAN WELL Work environment outdoor use Operation temperature -40° -+50°C Certificates CE, RoHS, ENEC

The LED street light Slim is a product of the PROLUMEN brand by the Estonian company LED House OÜ. The product uses LUMILEDS LUXEON 3030 2D LEDs and a Mean Well ELG series power supply. The housing is made of aluminum, powder-coated, and corrosion-resistant. The light is directed by a high-quality lens made of PMMA material. The recommended installation height for a 60W light is 4-6 meters. The light is powered by a Mean Well power supply, which is one of the most sold and widely used power supply manufacturers in the world. The input voltage of the power supplies ranges from 180 to 295V. A PFC function (power factor correction) is built-in. The working efficiency is up to 91.5%. Protection elements are built-in to safeguard against overheating, overvoltage, and overload. The power supplies have an IP67 protection class and are suitable for both indoor and outdoor use. Mean Well offers a 5-year manufacturer's warranty on the power supplies. More information about Mean Well power supplies can be found at www.meanwell.com













LED street light PROLUMEN Slim silvery 230V 40W 4800lm 70x140° IP66 840


Product code 15837

Brand PROLUMEN Supply voltage 230V Output 40W Maximum output 40W/1m Luminous flux 4800lumens Luminaire's efficiency Im79 120W Correlated colour temperature pure white 4000K Lens angle 70x140 Source of light LUMILEDS Cri 80 Protection class IP66 Lifespan 50000h Installation opening diameter 60mm Weight 2100g In package 1pc Casing colour silvery Casing material aluminum Polishing matt Power supply MEAN WELL Work environment outdoor use Operation temperature -40° -+50°C Certificates CE, RoHS, ENEC

The LED street light Slim is a product of the PROLUMEN brand by the Estonian company LED House OÜ. The product uses LUMILEDS LUXEON 3030 2D LEDs and a Mean Well ELG series power supply. The housing is made of aluminum, powder-coated, and corrosion-resistant. The light is directed by a high-quality lens made of PMMA material. The recommended installation height for a 60W light is 4-6 meters. The light is powered by a Mean Well power supply, which is one of the most sold and widely used power supply manufacturers in the world. The input voltage of the power supplies ranges from 180 to 295V. A PFC function (power factor correction) is built-in. The working efficiency is up to 91.5%. Protection elements are built-in to safeguard against overheating, overvoltage, and overload. The power supplies have an IP67 protection class and are suitable for both indoor and outdoor use. Mean Well offers a 5-year manufacturer's warranty on the power supplies. More information about Mean Well power supplies can be found at www.meanwell.com













LED street light PROLUMEN ST57+30W Monocrystalline Solar Panel 20W 4000lm 120x50° IP66 740

Product code 17957

Brand PROLUMEN Output 20W Maximum output 20W/1m Luminous flux 4000lumens Luminaire's efficiency Im79 200W Correlated colour temperature pure white 4000K Lens angle 120x50 Cri 70 Protection class IP66 Lifespan 80000h Llmf tm21 L80B10 @25°C 80.000h Height 140.0mm Width 345.0mm Length 570.0mm Weight 3900g Casing material aluminum Work environment outdoor use Certificates CE, RoHS Warranty 5 years

ST57 Solar-Powered Streetlight - And no cables are needed! ST57 is a fullrange solar streetlight offering six different sizes: 10W, 20W, 30W, 40W, 50W, and 60W, making it ideal for various applications. Smart control features, such as a built-in microwave sensor and timer dimming, ensure longer discharge times. The adjustable mounting angle improves charging efficiency, and the removable battery makes maintenance simple. Key Features: MPPT controller and mono-crystalline solar panels: Maximum charging capability. LiFePO4 battery: Reliable and long-lasting energy storage. Aluminum alloy casing and polycarbonate optical lens: Durable and weather-resistant design. Easy to clean and maintain with a shell design allowing for quick battery replacement. Efficient heat dissipation. Smart control options, including a built-in microwave sensor and timer dimming, ensure energy efficiency. 360° adjustable connection and ±40° tilt angle adjustment. Quick and easy installation with a plug-andplay system. Applications: Rural roads, urban roads, walkways, parking lots, courtyards, plazas, and parks. NB! The product is available for preorder, with a minimum order quantity of 10 units. Battery warranty 3 years, other parts of the light 5 years.







LED street light Street Master gray 230V 35W 5950lm 155x80° IP66 DALI 740

Product code 17782 DALI dimmable

Supply voltage 230V Power factor 0.98 Dimmable DALI Output 35W Maximum output 35W/1m Luminous flux 5950lumens Luminaire's efficiency Im79 170W Correlated colour temperature pure white 4000K Lens angle 155x80 Cri 70 Protection class IP66 Lifespan 80000h Height 102.0mm Width 209.0mm Length 507.0mm Weight 3300g In package 1pc Casing colour gray Casing material aluminum Polishing matt No. of switches 30000pcs Impact resistance IK09 Work environment outdoor use Operation temperature -30° - +45°C Certificates CE, ENEC Warranty 5 years

