



Carrier for street light ø60mm tube

Product code 14456

Installation opening diameter 60mm





LED street light PROLUMEN ADELA (MW + Lux) black 230V 100W 13400lm 60x140° IP66 830





Product code 17094

Brand PROLUMEN Supply voltage 230V Power factor 0.95 Output 100W Luminous flux 13400lumens Luminaire's efficiency Im79 134W Correlated colour temperature warm white 3000K Lens angle 60x140 Source of light **LUMILEDS** Sdcm - macadam ellipses 6 Protection class IP66 Lifespan 100000h Llmf tm21 L80B10 @25°C 100.000h Height 205.0mm Width 272.0mm Length 508.0mm Casing colour black Casing material aluminum Polishing matt Power supply **INVENTRONICS** Impact resistance IK08 Work environment outdoor use Operation temperature -40 °C ... +50°C Certificates CE Warranty 5 years

A street light that makes moving in urban spaces safe even in the dark of night! It is perfect for driveways, streets, parking lots, and all other outdoor areas that need safe, affordable, and efficient lighting. Protection classes IP66 and IK08 ensure the fixture's durability and long life in outdoor conditions. Additionally, the light is ideal for collaboration with security cameras see the product specifications for more details. Furthermore, the maintenance process of the light has been made exceptionally easy allowing you to save on labor and time! This feature is ensured by the removable electric plate, which makes connecting wires during installation particularly convenient.







LED street light PROLUMEN ADELA (MW + Lux) black 230V 30W 4100lm 60x140° IP66 830

Product code 17045

Brand PROLUMEN Supply voltage 230V Power factor 0.95 Output 30W Luminous flux 4100lumens Luminaire's efficiency Im79 137W Correlated colour temperature warm white 3000K Lens angle 60x140 Source of light **LUMILEDS** Cri 80 Sdcm - macadam ellipses 2 Protection class IP66 Lifespan 100000h Llmf tm21 L80B10 @25°C 100.000h Height 201.2mm Width 269.8mm Length 479.7mm Casing colour black Casing material aluminum Polishing matt Power supply **INVENTRONICS** Impact resistance IK08 Work environment outdoor use Operation temperature -40 °C ... +50°C Certificates CE Warranty 5 years

Smart streetlight that makes moving in urban spaces safe even in the darkness of the night! Ideal for driveways, streets, parking lots, and all other outdoor areas requiring safe and efficient lighting. The luminaire is perfectly suited for integration with security cameras (see additional details in the product specifications). Additionally, the luminaire's maintenance process has been made particularly easy - saving on labor and time! This feature is provided by a removable electrical board, making wiring connections exceptionally convenient during installation.







LED street light PROLUMEN ADELA (MW + Lux) black 230V 50W 6500lm 60x140° IP66 830

Product code 17049

Brand PROLUMEN Supply voltage 230V Power factor 0.95 Output 50W Luminous flux 6500lumens Luminaire's efficiency Im79 130W Correlated colour temperature warm white 3000K Lens angle 60x140 Source of light **LUMILEDS** Cri 80 Sdcm - macadam ellipses 6 Protection class IP66 Lifespan 100000h Llmf tm21 L80B10 @25°C 100.000h Height 201.2mm Width 269.8mm Length 479.7mm Casing colour black Casing material aluminum Polishing matt Power supply **INVENTRONICS** Impact resistance IK08 Work environment outdoor use Operation temperature -40 °C ... +50°C Certificates CE Warranty 5 years

Smart streetlight that makes moving in urban spaces safe even in the darkness of the night! Ideal for driveways, streets, parking lots, and all other outdoor areas requiring safe and efficient lighting. The luminaire is perfectly suited for integration with security cameras (see additional details in the product specifications). Additionally, the luminaire's maintenance process has been made particularly easy - saving on labor and time! This feature is provided by a removable electrical board, making wiring connections exceptionally convenient during installation.







LED street light PROLUMEN Hermoso black 230V 30W 4000lm 90° IP66 730

Product code 17590

Brand PROLUMEN Supply voltage 230V Power factor 0.95 Output 30W Luminous flux 4000lumens Luminaire's efficiency Im79 133W Correlated colour temperature warm white 3000K Lens angle 90 Source of light PHILIPS LED Cri 70 Sdcm - macadam ellipses 6 Protection class IP66 Lifespan 50000h Llmf tm21 L90B10 @25°C 50.000h Height 539.0mm Diameter 422.0mm Weight 27500g In package 1pc Casing colour black Casing material aluminum Polishing matt Power supply **SOSEN** Impact resistance IK08 Work environment outdoor use Operation temperature -40 °C ... +50°C Certificates CE Warranty 5 years

Outdoor light with an elegant style. Available options: 30W, 40W, 60W, 90W. This light is suitable for poles with a diameter of 60-80mm. It is perfect for driveways, streets, parking lots, and all other outdoor areas that need safe, affordable, and efficient lighting.







LED street light PROLUMEN Hermoso black 230V 40W 6000lm 90° IP66 830

Product code 17044

Brand PROLUMEN Supply voltage 230V Power factor 0.95 Output 40W Luminous flux 6000lumens Luminaire's efficiency Im79 150W Correlated colour temperature warm white 3000K Lens angle 90 Source of light **LUMILEDS** Cri 80 Sdcm - macadam ellipses 6 Protection class IP66 Lifespan 50000h Llmf tm21 L90B10 @25°C 50.000h Height 539.0mm Diameter 422.0mm Weight 5700g In package 1pc Casing colour black Casing material aluminum Polishing matt Power supply MEAN WELL Impact resistance IK08 Work environment outdoor use Operation temperature -40 °C ... +50°C Certificates CE Warranty 5 years

Outdoor light with an elegant style. Available options: 30W, 40W, 60W, 90W. This light is suitable for poles with a diameter of 60-80mm. It is perfect for driveways, streets, parking lots, and all other outdoor areas that need safe, affordable, and efficient lighting.







LED street light PROLUMEN Slim silvery 230V 40W 4800lm 70x140° IP66 840


Product code 15837

Brand **PROLUMEN** Supply voltage 230V Output 40W Luminous flux 4800lumens Luminaire's efficiency lm79 120W Correlated colour temperature pure white 4000K Lens angle 70x140 Source of light **LUMILEDS** Cri 80 Protection class IP66 Lifespan 50000h Installation opening diameter 60mm Weight 2100g In package 1pc Casing colour silvery Casing material aluminum Polishing matt Power supply MEAN WELL Work environment outdoor use Operation temperature -40° -+50°C Certificates CE, RoHS, ENEC

The LED street light Slim is a product of the PROLUMEN brand by the Estonian company LED House OÜ. The product uses LUMILEDS LUXEON 3030 2D LEDs and a Mean Well ELG series power supply. The housing is made of aluminum, powder-coated, and corrosion-resistant. The light is directed by a high-quality lens made of PMMA material. The recommended installation height for a 60W light is 4-6 meters. The light is powered by a Mean Well power supply, which is one of the most sold and widely used power supply manufacturers in the world. The input voltage of the power supplies ranges from 180 to 295V. A PFC function (power factor correction) is built-in. The working efficiency is up to 91.5%. Protection elements are built-in to safeguard against overheating, overvoltage, and overload. The power supplies have an IP67 protection class and are suitable for both indoor and outdoor use. Mean Well offers a 5-year manufacturer's warranty on the power supplies. More information about Mean Well power supplies can be found at www.meanwell.com













LED street light PROLUMEN Slim silvery 230V 60W 7200lm 70x140° IP66 840


Product code 13957

Brand PROLUMEN Supply voltage 230V Output 60W Luminous flux 7200lumens Luminaire's efficiency lm79 120W Correlated colour temperature pure white 4000K Lens angle 70x140 Source of light LUMILEDS Cri 80 Protection class IP66 Lifespan 50000h Installation opening diameter 60mm Weight 2100g In package 1pc Casing colour silvery Casing material aluminum Polishing matt Power supply MEAN WELL Work environment outdoor use Operation temperature -40° -+50°C Certificates CE, RoHS, ENEC Warranty 5 years

The LED street light Slim is a product of the PROLUMEN brand by the Estonian company LED House OÜ. The product uses LUMILEDS LUXEON 3030 2D LEDs and a Mean Well ELG series power supply. The housing is made of aluminum, powder-coated, and corrosion-resistant. The light is directed by a high-quality lens made of PMMA material. The recommended installation height for a 60W light is 4-6 meters. The light is powered by a Mean Well power supply, which is one of the most sold and widely used power supply manufacturers in the world. The input voltage of the power supplies ranges from 180 to 295V. A PFC function (power factor correction) is built-in. The working efficiency is up to 91.5%. Protection elements are built-in to safeguard against overheating, overvoltage, and overload. The power supplies have an IP67 protection class and are suitable for both indoor and outdoor use. Mean Well offers a 5-year manufacturer's warranty on the power supplies. More information about Mean Well power supplies can be found at www.meanwell.com













LED street light Slim Adaptor 60

Product code 14528

Installation opening diameter 60mm



