Street light Auva gray 230V 51W 7716lm IP66 DALI 730

Product code 20679 **DALI dimmable**

Supply voltage 230V
Dimmable DALI
Output 51W
Maximum output 51W/1m
Luminous flux 7716lumens
Luminaire’s efficiency 151W
Correlated colour temperature warm white 3000K
Cri 70
Protection class IP66
Lifespan 100000h
Llmf tm21 L90B10 @25°C 100.000h
Height 102.0mm
Width 250.0mm
Length 525.0mm
Weight 49 g
Casing colour gray
Casing material aluminium
Polishing matt
Impact resistance IK09
Work environment outdoor use
Operation temperature -40°C - +70°C
Certificates CE, ENEC



Street light DKS850 14700LM 105W B 740 NB3 40-60 IC0

Product code 23962

Carrier for street light ø60mm tube

Product code 14456

Installation opening diameter 60mm





Street light Liralighting FAT 4000 black 230V 17W 2008lm IP65 DALI 830

Product code 19696 DALI dimmable

Brand Liralighting
Supply voltage 230V
Power factor 0.90
Dimmable DALI
Output 17W
Maximum output 17W/1m
Luminous flux 2008lumens
Luminaire’s efficiency 118W
Correlated colour temperature warm white 3000K
Cri 80
Sdcm - macadam ellipses 3
Protection class IP65
Lifespan 100000h
Llmf tm21 L80B10 @25°C 100.000h
Height 4000.0mm
Width 150.0mm
Length 800.0mm
Package weight 3.5 kg
In package 1pc
Casing colour black
Casing material aluminium + plastic
Polishing matt
Impact resistance IK06
Work environment outdoor use
Operation temperature -40 ~ 45°C
Certificates CE
Warranty 5 years



Street light Liralighting FAT DOUBLE 4000 black 230V 34W 4016lm IP65 DALI 830

Product code 19698 DALI dimmable

Brand Liralighting
Supply voltage 230V
Power factor 0.90
Dimmable DALI
Output 34W
Maximum output 17W/1m
Luminous flux 4016lumens
Luminaire’s efficiency 118W
Correlated colour temperature warm white 3000K
Cri 80
Sdcm - macadam ellipses 3
Protection class IP65
Lifespan 100000h
Llmf tm21 L80B10 @25°C 100.000h
Height 4000.0mm
Width 150.0mm
Length 1450.0mm
Package weight 40 g
In package 1pc
Casing colour black
Casing material aluminium + plastic
Polishing matt
Impact resistance IK06
Work environment outdoor use
Operation temperature -40 ~ 45°C
Certificates CE
Warranty 5 years



Street light Liralighting LT H gray 230V 33W 3898lm IP65 DALI 830

Product code 19111 DALI dimmable

Brand Liralighting
Supply voltage 230V
Power factor 0.90
Dimmable DALI
Output 33W
Maximum output 33W/1m
Luminous flux 3898lumens
Luminaire’s efficiency 118W
Correlated colour temperature warm white 3000K
Cri 80
Sdcm - macadam ellipses 3
Protection class IP65
Lifespan 100000h
Llmf tm21 L80B10 @25°C 100.000h
Height 195.0mm
Width 150.0mm
Length 550.0mm
In package 1pc
Casing colour gray
Casing material aluminium + plastic
Polishing matt
Impact resistance IK08
Work environment outdoor use
Operation temperature -40 ~ 45°C
Certificates CE
Warranty 5 years



Street light Liralighting REET AR 400 black 230V 20W 2171lm IP65 DALI 830

Product code 19701 DALI dimmable

Brand Liralighting
Supply voltage 230V
Power factor 0.90
Dimmable DALI
Output 20W
Maximum output 20W/1m
Luminous flux 2171lumens
Luminaire’s efficiency 109W
Correlated colour temperature warm white 3000K
Cri 80
Sdcm - macadam ellipses 3
Protection class IP65
Lifespan 100000h
Llmf tm21 L80B10 @25°C 100.000h
Height 491.0mm
Diameter 400.0mm
Package weight 9 kg
In package 1pc
Casing colour black
Casing material aluminium + plastic
Polishing matt
Impact resistance IK06
Work environment outdoor use
Operation temperature -40 ~ 45°C
Certificates CE
Warranty 5 years



Street light Liralighting REET AR 400 black 230V 26W 2919lm IP65 830

Product code 22312

Brand Liralighting
Supply voltage 230V
Power factor 0.90
Output 26W
Maximum output 26W/1m
Luminous flux 2919lumens
Luminaire’s efficiency 112W
Correlated colour temperature warm white 3000K
Cri 80
Sdcm - macadam ellipses 3
Protection class IP65
Lifespan 100000h
Llmf tm21 L80B10 @25°C 100.000h
Height 491.0mm
Diameter 400.0mm
Package weight 9 kg
In package 1pc
Casing colour black
Casing material aluminium + plastic
Polishing matt
Impact resistance IK06
Work environment outdoor use
Operation temperature -40 ~ 45°C
Certificates CE
Warranty 5 years



Remote Power/CCT remote

Product code 22949



Street light Prolumen ADELA black 230V 120W 19200lm 60x140° IP66 740

Product code 22738

Brand Prolumen
Supply voltage 230V
Power factor 0.95
Output 120W
Maximum output 120W/1m
Luminous flux 19200lumens
Luminaire’s efficiency 160W
Correlated colour temperature pure white 4000K
Lens angle 60x140
Source of light LUMILEDS
Cri 70
Sdcm - macadam ellipses 6
Protection class IP66
Lifespan 100000h
Llmf tm21 L80B10 @25°C 100.000h
Height 201.2mm
Width 269.8mm
Length 479.7mm
Casing colour black
Casing material aluminium
Polishing matt
Power supply INVENTRONICS
Impact resistance IK08
Work environment outdoor use
Operation temperature -40 °C ... +50°C
Certificates CE
Warranty 5 years



A street light that makes moving in urban spaces safe even in the dark of night! It is perfect for driveways, streets, parking lots, and all other outdoor areas that need safe, affordable, and efficient lighting. Protection classes IP66 and IK08 ensure the fixture's durability and long life in outdoor conditions. Additionally, the light is ideal for collaboration with security cameras - see the product specifications for more details. Furthermore, the maintenance process of the light has been made exceptionally easy - allowing you to save on labor and time! This feature is ensured by the removable electric plate, which makes connecting wires during installation particularly convenient.

Street light Prolumen ADELA black 230V 30W 4500lm 60x140° IP66 730

Product code 22733

Brand Prolumen
Supply voltage 230V
Power factor 0.95
Output 30W
Maximum output 30W/1m
Luminous flux 4500lumens
Luminaire’s efficiency 150W
Correlated colour temperature warm white 3000K
Lens angle 60x140
Source of light LUMILEDS
Cri 70
Sdcm - macadam ellipses 2
Protection class IP66
Lifespan 100000h
Llmf tm21 L80B10 @25°C 100.000h
Height 120.0mm
Width 270.0mm
Length 474.0mm
Weight 3.8 kg
Casing colour black
Casing material aluminium
Polishing matt
Power supply OSRAM
Impact resistance IK08
Work environment outdoor use
Operation temperature -40 °C ... +50°C
Certificates CE
Warranty 5 years



Smart streetlight that makes moving in urban spaces safe even in the darkness of the night! Ideal for driveways, streets, parking lots, and all other outdoor areas requiring safe and efficient lighting. The luminaire is perfectly suited for integration with security cameras (see additional details in the product specifications). Additionally, the luminaire's maintenance process has been made particularly easy - saving on labor and time! This feature is provided by a removable electrical board, making wiring connections exceptionally convenient during installation.

Street light Prolumen ADELA black 230V 30W 4500lm 60° IP66 DALI 730

Product code 19705 DALI dimmable

Brand Prolumen
Supply voltage 230V
Power factor 0.95
Dimmable DALI
Output 30W
Maximum output 30W/1m
Luminous flux 4500lumens
Luminaire’s efficiency 150W
Correlated colour temperature warm white 3000K
Lens angle 60
Source of light LUMILEDS
Cri 70
Sdcm - macadam ellipses 2
Protection class IP66
Lifespan 100000h
Llmf tm21 L80B10 @25°C 100.000h
Height 120.0mm
Width 270.0mm
Length 474.0mm
Weight 3.8 kg
Casing colour black
Casing material aluminium
Polishing matt
Power supply OSRAM
Impact resistance IK08
Work environment outdoor use
Operation temperature -40 °C ... +50°C
Certificates CE
Warranty 5 years



Smart streetlight that makes moving in urban spaces safe even in the darkness of the night! Ideal for driveways, streets, parking lots, and all other outdoor areas requiring safe and efficient lighting. The luminaire is perfectly suited for integration with security cameras (see additional details in the product specifications). Additionally, the luminaire's maintenance process has been made particularly easy - saving on labor and time! This feature is provided by a removable electrical board, making wiring connections exceptionally convenient during installation.

Street light Prolumen ADELA black 230V 50W 6500lm 60x140° IP66 730

Product code 22734

Brand Prolumen
Supply voltage 230V
Power factor 0.95
Output 50W
Maximum output 50W/1m
Luminous flux 6500lumens
Luminaire’s efficiency 130W
Correlated colour temperature warm white 3000K
Lens angle 60x140
Source of light LUMILEDS
Cri 70
Sdcm - macadam ellipses 6
Protection class IP66
Lifespan 100000h
Llmf tm21 L80B10 @25°C 100.000h
Height 201.2mm
Width 269.8mm
Length 479.7mm
Casing colour black
Casing material aluminium
Polishing matt
Power supply INVENTRONICS
Impact resistance IK08
Work environment outdoor use
Operation temperature -40 °C ... +50°C
Certificates CE
Warranty 5 years



A street light that makes moving in urban spaces safe even in the dark of night! It is perfect for driveways, streets, parking lots, and all other outdoor areas that need safe, affordable, and efficient lighting. Protection classes IP66 and IK08 ensure the fixture's durability and long life in outdoor conditions. Additionally, the light is ideal for collaboration with security cameras - see the product specifications for more details. Furthermore, the maintenance process of the light has been made exceptionally easy - allowing you to save on labor and time! This feature is ensured by the removable electric plate, which makes connecting wires during installation particularly convenient.

Street light Prolumen ADELA black 230V 50W 7500lm 60x140° IP66 740

Product code 22735

Brand Prolumen
Supply voltage 230V
Power factor 0.95
Output 50W
Maximum output 50W/1m
Luminous flux 7500lumens
Luminaire’s efficiency 150W
Correlated colour temperature pure white 4000K
Lens angle 60x140
Source of light LUMILEDS
Cri 70
Sdcm - macadam ellipses 6
Protection class IP66
Lifespan 100000h
Llmf tm21 L80B10 @25°C 100.000h
Height 201.2mm
Width 269.8mm
Length 479.7mm
Casing colour black
Casing material aluminium
Polishing matt
Power supply INVENTRONICS
Impact resistance IK08
Work environment outdoor use
Operation temperature -40 °C ... +50°C
Certificates CE
Warranty 5 years



A street light that makes moving in urban spaces safe even in the dark of night! It is perfect for driveways, streets, parking lots, and all other outdoor areas that need safe, affordable, and efficient lighting. Protection classes IP66 and IK08 ensure the fixture's durability and long life in outdoor conditions. Additionally, the light is ideal for collaboration with security cameras - see the product specifications for more details. Furthermore, the maintenance process of the light has been made exceptionally easy - allowing you to save on labor and time! This feature is ensured by the removable electric plate, which makes connecting wires during installation particularly convenient.

Street light Prolumen ADELA black 230V 70W 9100lm 60x140° IP66 DALI 730

Product code 18152 DALI dimmable

Brand Prolumen
Supply voltage 230V
Power factor 0.95
Dimmable DALI
Output 70W
Maximum output 70W/1m
Luminous flux 9100lumens
Luminaire’s efficiency 130W
Correlated colour temperature warm white 3000K
Lens angle 60x140
Source of light LUMILEDS
Cri 70
Sdcm - macadam ellipses 6
Protection class IP66
Lifespan 100000h
Llmf tm21 L80B10 @25°C 100.000h
Height 205.0mm
Width 272.0mm
Length 508.0mm
Casing colour black
Casing material aluminium
Polishing matt
Power supply SOSEN
Impact resistance IK08
Work environment outdoor use
Operation temperature -40 °C ... +50°C
Certificates CE
Warranty 5 years



A street light that makes moving in urban spaces safe even in the dark of night! It is perfect for driveways, streets, parking lots, and all other outdoor areas that need safe, affordable, and efficient lighting. Protection classes IP66 and IK08 ensure the fixture's durability and long life in outdoor conditions. Additionally, the light is ideal for collaboration with security cameras - see the product specifications for more details. Furthermore, the maintenance process of the light has been made exceptionally easy - allowing you to save on labor and time! This feature is ensured by the removable electric plate, which makes connecting wires during installation particularly convenient.

Street light Prolumen ADELA black 230V 90W 12500lm 60x140° IP66 730

Product code 22736

Brand Prolumen
Supply voltage 230V
Power factor 0.95
Output 90W
Maximum output 90W/1m
Luminous flux 12500lumens
Luminaire’s efficiency 139W
Correlated colour temperature warm white 3000K
Lens angle 60x140
Source of light LUMILEDS
Cri 70
Sdcm - macadam ellipses 6
Protection class IP66
Lifespan 100000h
Llmf tm21 L80B10 @25°C 100.000h
Height 201.2mm
Width 269.8mm
Length 479.7mm
Casing colour black
Casing material aluminium
Polishing matt
Power supply INVENTRONICS
Impact resistance IK08
Work environment outdoor use
Operation temperature -40 °C ... +50°C
Certificates CE
Warranty 5 years



A street light that makes moving in urban spaces safe even in the dark of night! It is perfect for driveways, streets, parking lots, and all other outdoor areas that need safe, affordable, and efficient lighting. Protection classes IP66 and IK08 ensure the fixture's durability and long life in outdoor conditions. Additionally, the light is ideal for collaboration with security cameras - see the product specifications for more details. Furthermore, the maintenance process of the light has been made exceptionally easy - allowing you to save on labor and time! This feature is ensured by the removable electric plate, which makes connecting wires during installation particularly convenient.

Street light Prolumen ADELA black 230V 90W 13500lm 60x140° IP66 740

Product code 22737

Brand Prolumen
Supply voltage 230V
Power factor 0.95
Output 90W
Maximum output 90W/1m
Luminous flux 13500lumens
Luminaire’s efficiency 150W
Correlated colour temperature pure white 4000K
Lens angle 60x140
Source of light LUMILEDS
Cri 70
Sdcm - macadam ellipses 6
Protection class IP66
Lifespan 100000h
Llmf tm21 L80B10 @25°C 100.000h
Height 201.2mm
Width 269.8mm
Length 479.7mm
Casing colour black
Casing material aluminium
Polishing matt
Power supply INVENTRONICS
Impact resistance IK08
Work environment outdoor use
Operation temperature -40 °C ... +50°C
Certificates CE
Warranty 5 years



A street light that makes moving in urban spaces safe even in the dark of night! It is perfect for driveways, streets, parking lots, and all other outdoor areas that need safe, affordable, and efficient lighting. Protection classes IP66 and IK08 ensure the fixture's durability and long life in outdoor conditions. Additionally, the light is ideal for collaboration with security cameras - see the product specifications for more details. Furthermore, the maintenance process of the light has been made exceptionally easy - allowing you to save on labor and time! This feature is ensured by the removable electric plate, which makes connecting wires during installation particularly convenient.

Street light Prolumen ADELA MW + Lux black 230V 100W 13400lm 60x140° IP66 1-10V 730

Product code 17094 **1-10V dimmable**

Brand Prolumen
Supply voltage 230V
Power factor 0.95
Dimmable 1-10V
Output 100W
Maximum output 100W/1m
Luminous flux 13400lumens
Luminaire’s efficiency 134W
Correlated colour temperature warm white 3000K
Lens angle 60x140
Source of light LUMILEDS
Cri 70
Sdcm - macadam ellipses 6
Protection class IP66
Lifespan 100000h
Llmf tm21 L80B10 @25°C 100.000h
Height 205.0mm
Width 272.0mm
Length 508.0mm
Casing colour black
Casing material aluminium
Polishing matt
Power supply INVENTRONICS
Impact resistance IK08
Work environment outdoor use
Operation temperature -40 °C ... +50°C
Certificates CE
Warranty 5 years



A street light that makes moving in urban spaces safe even in the dark of night! It is perfect for driveways, streets, parking lots, and all other outdoor areas that need safe, affordable, and efficient lighting. Protection classes IP66 and IK08 ensure the fixture's durability and long life in outdoor conditions. Additionally, the light is ideal for collaboration with security cameras - see the product specifications for more details. Furthermore, the maintenance process of the light has been made exceptionally easy - allowing you to save on labor and time! This feature is ensured by the removable electric plate, which makes connecting wires during installation particularly convenient.

Street light Prolumen ADELA MW + Lux black 230V 30W 4100lm 60x140° IP66 1-10V 730

Product code 17045 1-10V dimmable

Brand Prolumen
Supply voltage 230V
Power factor 0.95
Dimmable 1-10V
Output 30W
Maximum output 30W/1m
Luminous flux 4100lumens
Luminaire’s efficiency 137W
Correlated colour temperature warm white 3000K
Lens angle 60x140
Source of light LUMILEDS
Cri 70
Sdcm - macadam ellipses 2
Protection class IP66
Lifespan 100000h
Llmf tm21 L80B10 @25°C 100.000h
Height 201.2mm
Width 269.8mm
Length 479.7mm
Casing colour black
Casing material aluminium
Polishing matt
Power supply INVENTRONICS
Impact resistance IK08
Work environment outdoor use
Operation temperature -40 °C ... +50°C
Certificates CE
Warranty 5 years



Smart streetlight that makes moving in urban spaces safe even in the darkness of the night! Ideal for driveways, streets, parking lots, and all other outdoor areas requiring safe and efficient lighting. The luminaire is perfectly suited for integration with security cameras (see additional details in the product specifications). Additionally, the luminaire's maintenance process has been made particularly easy - saving on labor and time! This feature is provided by a removable electrical board, making wiring connections exceptionally convenient during installation.

Street light Prolumen ADELA MW + Lux black 230V 50W 6500lm 60x140° IP66 0-10V 730

Product code 17049 0-10V dimmable

Brand Prolumen
Supply voltage 230V
Power factor 0.95
Dimmable 0-10V
Output 50W
Maximum output 50W/1m
Luminous flux 6500lumens
Luminaire’s efficiency 130W
Correlated colour temperature warm white 3000K
Lens angle 60x140
Source of light LUMILEDS
Cri 70
Sdcm - macadam ellipses 6
Protection class IP66
Lifespan 100000h
Llmf tm21 L80B10 @25°C 100.000h
Height 201.2mm
Width 269.8mm
Length 479.7mm
Casing colour black
Casing material aluminium
Polishing matt
Power supply INVENTRONICS
Impact resistance IK08
Work environment outdoor use
Operation temperature -40 °C ... +50°C
Certificates CE
Warranty 5 years



Smart streetlight that makes moving in urban spaces safe even in the darkness of the night! Ideal for driveways, streets, parking lots, and all other outdoor areas requiring safe and efficient lighting. The luminaire is perfectly suited for integration with security cameras (see additional details in the product specifications). Additionally, the luminaire's maintenance process has been made particularly easy - saving on labor and time! This feature is provided by a removable electrical board, making wiring connections exceptionally convenient during installation.

Street light Prolumen Avarta 40W 5600lm 120° No dim 740

Product code 19056



Brand Prolumen
Output 40W
Maximum output 40W/1m
Luminous flux 5600lumens
Luminaire’s efficiency 140W
Correlated colour temperature pure white 4000K
Lens angle 120
Cri 70
Power supply SOSEN
Warranty 5 years

Street light Prolumen BEAST SF bracket black 230V 100W 16400lm 130x60° IP66 1-10V 730

Product code 22314 1-10V dimmable

Brand Prolumen
Supply voltage 230V
Power factor 0.95
Dimmable 1-10V
Output 100W
Maximum output 100W/1m
Luminous flux 16400lumens
Luminaire’s efficiency 164W
Correlated colour temperature warm white 3000K
Lens angle 130x60
Source of light LUMILEDS
Cri 70
Sdcm - macadam ellipses 6
Protection class IP66
Lifespan 100000h
Llmf tm21 L80B10 @25°C 100.000h
Height 105.0mm
Width 304.0mm
Length 428.0mm
Weight 3.82 kg
Casing colour black
Casing material aluminium + plastic
Polishing matt
Power supply INVENTRONICS
Impact resistance IK08
Work environment outdoor use
Operation temperature -40° - +50°C
Certificates CE, ENEC, CB
Warranty 5 years



A street light that makes moving in urban spaces safe even in the dark of night! It is perfect for driveways, streets, parking lots, and all other outdoor areas that need safe, affordable, and efficient lighting. Protection classes IP66 and IK08 ensure the fixture's durability and long life in outdoor conditions. Additionally, the light is ideal for collaboration with security cameras - see the product specifications for more details. Furthermore, the maintenance process of the light has been made exceptionally easy - allowing you to save on labor and time! This feature is ensured by the removable electric plate, which makes connecting wires during installation particularly convenient.

Street light Prolumen BEAST SF bracket black 230V 100W 16500lm 130x60° IP66 1-10V 740

Product code 18226 **1-10V dimmable**

Brand Prolumen
Supply voltage 230V
Power factor 0.95
Dimmable 1-10V
Output 100W
Maximum output 100W/1m
Luminous flux 16500lumens
Luminaire’s efficiency 165W
Correlated colour temperature pure white 4000K
Lens angle 130x60
Source of light LUMILEDS
Cri 70
Sdcm - macadam ellipses 6
Protection class IP66
Lifespan 100000h
Llmf tm21 L80B10 @25°C 100.000h
Height 105.0mm
Width 304.0mm
Length 428.0mm
Weight 3.82 kg
Casing colour black
Casing material aluminium + plastic
Polishing matt
Power supply INVENTRONICS
Impact resistance IK08
Work environment outdoor use
Operation temperature -40° - +50°C
Certificates CE, ENEC, CB
Warranty 5 years



A street light that makes moving in urban spaces safe even in the dark of night! It is perfect for driveways, streets, parking lots, and all other outdoor areas that need safe, affordable, and efficient lighting. Protection classes IP66 and IK08 ensure the fixture's durability and long life in outdoor conditions. Additionally, the light is ideal for collaboration with security cameras - see the product specifications for more details. Furthermore, the maintenance process of the light has been made exceptionally easy - allowing you to save on labor and time! This feature is ensured by the removable electric plate, which makes connecting wires during installation particularly convenient.

Street light Prolumen BEAST SF bracket black 230V 150W 21000lm 130x60° IP66 DALI 730

Product code 22732 DALI dimmable

Brand Prolumen
Supply voltage 230V
Power factor 0.95
Dimmable DALI
Output 150W
Maximum output 150W/1m
Luminous flux 21000lumens
Luminaire’s efficiency 140W
Correlated colour temperature warm white 3000K
Lens angle 130x60
Source of light LUMILEDS
Cri 70
Sdcm - macadam ellipses 6
Protection class IP66
Lifespan 100000h
Llmf tm21 L80B10 @25°C 100.000h
Height 105.0mm
Width 304.0mm
Length 428.0mm
Weight 3.82 kg
Casing colour black
Casing material aluminium + plastic
Polishing matt
Power supply SOSEN
Impact resistance IK08
Work environment outdoor use
Operation temperature -40° - +50°C
Certificates CE, ENEC, CB
Warranty 5 years



A street light that makes moving in urban spaces safe even in the dark of night! It is perfect for driveways, streets, parking lots, and all other outdoor areas that need safe, affordable, and efficient lighting. Protection classes IP66 and IK08 ensure the fixture's durability and long life in outdoor conditions. Additionally, the light is ideal for collaboration with security cameras - see the product specifications for more details. Furthermore, the maintenance process of the light has been made exceptionally easy - allowing you to save on labor and time! This feature is ensured by the removable electric plate, which makes connecting wires during installation particularly convenient.

Street light Prolumen BEAST SF bracket black 230V 200W 28800lm 130x60° IP66 DALI 730

Product code 22731 DALI dimmable

Brand Prolumen
Supply voltage 230V
Power factor 0.95
Dimmable DALI
Output 200W
Maximum output 200W/1m
Luminous flux 28800lumens
Luminaire’s efficiency 144W
Correlated colour temperature warm white 3000K
Lens angle 130x60
Source of light LUMILEDS
Cri 70
Sdcm - macadam ellipses 6
Protection class IP66
Lifespan 100000h
Llmf tm21 L80B10 @25°C 100.000h
Height 105.0mm
Width 304.0mm
Length 428.0mm
Weight 3.82 kg
Casing colour black
Casing material aluminium + plastic
Polishing matt
Power supply SOSEN
Impact resistance IK08
Work environment outdoor use
Operation temperature -40° - +50°C
Certificates CE, ENEC, CB
Warranty 5 years



A street light that makes moving in urban spaces safe even in the dark of night! It is perfect for driveways, streets, parking lots, and all other outdoor areas that need safe, affordable, and efficient lighting. Protection classes IP66 and IK08 ensure the fixture's durability and long life in outdoor conditions. Additionally, the light is ideal for collaboration with security cameras - see the product specifications for more details. Furthermore, the maintenance process of the light has been made exceptionally easy - allowing you to save on labor and time! This feature is ensured by the removable electric plate, which makes connecting wires during installation particularly convenient.

Street light Prolumen BEAST SF bracket black 230V 200W 30000lm 130x60° IP66 1-10V 740

Product code 17903 **1-10V dimmable**

Brand Prolumen
Supply voltage 230V
Power factor 0.95
Dimmable 1-10V
Output 200W
Maximum output 200W/1m
Luminous flux 30000lumens
Luminaire’s efficiency 150W
Correlated colour temperature pure white 4000K
Lens angle 130x60
Source of light LUMILEDS
Cri 70
Sdcm - macadam ellipses 6
Protection class IP66
Lifespan 100000h
Llmf tm21 L80B10 @25°C 100.000h
Height 105.0mm
Width 304.0mm
Length 428.0mm
Weight 3.82 kg
Casing colour black
Casing material aluminium + plastic
Polishing matt
Power supply INVENTRONICS
Impact resistance IK08
Work environment outdoor use
Operation temperature -40° - +50°C
Certificates CE, ENEC, CB
Warranty 5 years



A street light that makes moving in urban spaces safe even in the dark of night! It is perfect for driveways, streets, parking lots, and all other outdoor areas that need safe, affordable, and efficient lighting. Protection classes IP66 and IK08 ensure the fixture's durability and long life in outdoor conditions. Additionally, the light is ideal for collaboration with security cameras - see the product specifications for more details. Furthermore, the maintenance process of the light has been made exceptionally easy - allowing you to save on labor and time! This feature is ensured by the removable electric plate, which makes connecting wires during installation particularly convenient.

Street light Prolumen BEAST TR bracket black 230V 100W 16500lm 130x60° IP66 1-10V 740

Product code 17862 **1-10V dimmable**

Brand Prolumen
Supply voltage 230V
Power factor 0.95
Dimmable 1-10V
Output 100W
Maximum output 100W/1m
Luminous flux 16500lumens
Luminaire’s efficiency 165W
Correlated colour temperature pure white 4000K
Lens angle 130x60
Source of light LUMILEDS
Cri 70
Sdcm - macadam ellipses 6
Protection class IP66
Lifespan 100000h
Llmf tm21 L80B10 @25°C 100.000h
Height 88.0mm
Width 304.0mm
Length 428.0mm
Casing colour black
Casing material aluminium + plastic
Polishing matt
Power supply INVENTRONICS
Impact resistance IK08
Work environment outdoor use
Operation temperature -40° - +50°C
Certificates CE, ENEC, CB
Warranty 5 years



A street light that makes moving in urban spaces safe even in the dark of night! It is perfect for driveways, streets, parking lots, and all other outdoor areas that need safe, affordable, and efficient lighting. Protection classes IP66 and IK08 ensure the fixture's durability and long life in outdoor conditions. Additionally, the light is ideal for collaboration with security cameras - see the product specifications for more details. Furthermore, the maintenance process of the light has been made exceptionally easy - allowing you to save on labor and time! This feature is ensured by the removable electric plate, which makes connecting wires during installation particularly convenient.

Street light Prolumen BEAST TR bracket black 230V 240W 40947lm 100x140° IP66 0-10V 740

Product code 17802 0-10V dimmable

Brand Prolumen
Supply voltage 230V
Power factor 0.95
Dimmable 0-10V
Output 240W
Maximum output 240W/1m
Luminous flux 40947lumens
Luminaire’s efficiency 171W
Correlated colour temperature pure white 4000K
Lens angle 100x140
Source of light LUMILEDS
Cri 70
Sdcm - macadam ellipses 6
Protection class IP66
Lifespan 100000h
Height 184.2mm
Width 304.0mm
Length 595.4mm
Weight 7.03 kg
Casing colour black
Casing material aluminium
Polishing matt
Power supply INVENTRONICS
Impact resistance IK08
Work environment outdoor use
Operation temperature -40° - +50°C
Certificates CE, ENEC, CB
Warranty 5 years



A street light that makes moving in urban spaces safe even in the dark of night! It is perfect for driveways, streets, parking lots, and all other outdoor areas that need safe, affordable, and efficient lighting. Protection classes IP66 and IK08 ensure the fixture's durability and long life in outdoor conditions. Additionally, the light is ideal for collaboration with security cameras - see the product specifications for more details. Furthermore, the maintenance process of the light has been made exceptionally easy - allowing you to save on labor and time! This feature is ensured by the removable electric plate, which makes connecting wires during installation particularly convenient.

Street light Prolumen BEAST TR bracket black 230V 400W 66419lm 100x140° IP66 1-10V 750

Product code 17803 **1-10V dimmable**

Brand Prolumen
Supply voltage 230V
Power factor 0.95
Dimmable 1-10V
Output 400W
Maximum output 400W/1m
Luminous flux 66419lumens
Luminaire’s efficiency 166W
Correlated colour temperature pure white 5000K
Lens angle 100x140
Source of light LUMILEDS
Cri 70
Sdcm - macadam ellipses 6
Protection class IP66
Lifespan 100000h
Height 199.6mm
Width 339.6mm
Length 767.5mm
Weight 1.1 kg
Casing colour black
Casing material aluminium
Polishing matt
Power supply INVENTRONICS
Impact resistance IK08
Work environment outdoor use
Operation temperature -40° - +50°C
Certificates CE, ENEC, CB
Warranty 5 years



A street light that makes moving in urban spaces safe even in the dark of night! It is perfect for driveways, streets, parking lots, and all other outdoor areas that need safe, affordable, and efficient lighting. Protection classes IP66 and IK08 ensure the fixture's durability and long life in outdoor conditions. Additionally, the light is ideal for collaboration with security cameras - see the product specifications for more details. Furthermore, the maintenance process of the light has been made exceptionally easy - allowing you to save on labor and time! This feature is ensured by the removable electric plate, which makes connecting wires during installation particularly convenient.

Street light Prolumen BEAST U bracket black 230V 400W 66419lm 100x140° IP66 1-10V 750

Product code 17804 **1-10V dimmable**

Brand Prolumen
Supply voltage 230V
Power factor 0.95
Dimmable 1-10V
Output 400W
Maximum output 400W/1m
Luminous flux 66419lumens
Luminaire’s efficiency 166W
Correlated colour temperature pure white 5000K
Lens angle 100x140
Source of light LUMILEDS
Cri 70
Sdcm - macadam ellipses 6
Protection class IP66
Lifespan 100000h
Height 199.6mm
Width 339.6mm
Length 767.5mm
Weight 1.1 kg
Casing colour black
Casing material aluminium
Polishing matt
Power supply INVENTRONICS
Impact resistance IK08
Work environment outdoor use
Operation temperature -40° - +50°C
Certificates CE, ENEC, CB
Warranty 5 years



A street light that makes moving in urban spaces safe even in the dark of night! It is perfect for driveways, streets, parking lots, and all other outdoor areas that need safe, affordable, and efficient lighting. Protection classes IP66 and IK08 ensure the fixture's durability and long life in outdoor conditions. Additionally, the light is ideal for collaboration with security cameras - see the product specifications for more details. Furthermore, the maintenance process of the light has been made exceptionally easy - allowing you to save on labor and time! This feature is ensured by the removable electric plate, which makes connecting wires during installation particularly convenient.

Street light Prolumen BEAST YK bracket black 230V 200W 30000lm 130x60° IP66 1-10V 740

Product code 17861 **1-10V dimmable**

Brand Prolumen
Supply voltage 230V
Power factor 0.95
Dimmable 1-10V
Output 200W
Maximum output 200W/1m
Luminous flux 30000lumens
Luminaire’s efficiency 150W
Correlated colour temperature pure white 4000K
Lens angle 130x60
Source of light LUMILEDS
Cri 70
Sdcm - macadam ellipses 6
Protection class IP66
Lifespan 100000h
Llmf tm21 L80B10 @25°C 100.000h
Height 105.0mm
Width 304.0mm
Length 428.0mm
Weight 3.82 kg
Casing colour black
Casing material aluminium + plastic
Polishing matt
Power supply INVENTRONICS
Impact resistance IK08
Work environment outdoor use
Operation temperature -40° - +50°C
Certificates CE, ENEC, CB
Warranty 5 years



A street light that makes moving in urban spaces safe even in the dark of night! It is perfect for driveways, streets, parking lots, and all other outdoor areas that need safe, affordable, and efficient lighting. Protection classes IP66 and IK08 ensure the fixture's durability and long life in outdoor conditions. Additionally, the light is ideal for collaboration with security cameras - see the product specifications for more details. Furthermore, the maintenance process of the light has been made exceptionally easy - allowing you to save on labor and time! This feature is ensured by the removable electric plate, which makes connecting wires during installation particularly convenient.

Street light Prolumen BEAST YK bracket black 230V 300W 48900lm 130x60° IP66 1-10V 740

Product code 17863 **1-10V dimmable**

Brand Prolumen
Supply voltage 230V
Power factor 0.95
Dimmable 1-10V
Output 300W
Maximum output 300W/1m
Luminous flux 48900lumens
Luminaire’s efficiency 163W
Correlated colour temperature pure white 4000K
Lens angle 130x60
Source of light LUMILEDS
Cri 70
Sdcm - macadam ellipses 6
Protection class IP66
Lifespan 100000h
Llmf tm21 L70 @25°C 100.000h
Height 88.0mm
Width 304.0mm
Length 428.0mm
Casing colour black
Casing material aluminium + plastic
Polishing matt
Power supply INVENTRONICS
Impact resistance IK08
Work environment outdoor use
Operation temperature -40° - +50°C
Certificates CE, ENEC, CB
Warranty 5 years



A street light that makes moving in urban spaces safe even in the dark of night! It is perfect for driveways, streets, parking lots, and all other outdoor areas that need safe, affordable, and efficient lighting. Protection classes IP66 and IK08 ensure the fixture's durability and long life in outdoor conditions. Additionally, the light is ideal for collaboration with security cameras - see the product specifications for more details. Furthermore, the maintenance process of the light has been made exceptionally easy - allowing you to save on labor and time! This feature is ensured by the removable electric plate, which makes connecting wires during installation particularly convenient.

Street light Prolumen Hermoso 30/ 40/ 60W 9600lm CRI70 TP III° No dim 2200K, 3000K, 4000K 3CCT

Product code 19054

Brand Prolumen
Output 30/ 40/ 60W
Maximum output 30/ 40W/1m
Luminous flux 9600lumens
Correlated colour temperature 3CCT 2200K, 3000K, 4000K
Lens angle TP III
Cri 70
Power supply SOSEN
Warranty 5 years

Outdoor light with an elegant style. Available options: 30W, 40W, 60W, 90W. This light is suitable for poles with a diameter of 60-80mm. It is perfect for driveways, streets, parking lots, and all other outdoor areas that need safe, affordable, and efficient lighting.



Street light Prolumen Hermoso black 230V 30W 4000lm 90° IP66 730

Product code 17590

Brand Prolumen
Supply voltage 230V
Power factor 0.95
Output 30W
Maximum output 30W/1m
Luminous flux 4000lumens
Luminaire’s efficiency 133W
Correlated colour temperature warm white 3000K
Lens angle 90
Source of light PHILIPS LED
Cri 70
Sdcm - macadam ellipses 6
Protection class IP66
Lifespan 50000h
Llmf tm21 L90B10 @25°C 50.000h
Height 539.0mm
Diameter 422.0mm
Weight 27.5 kg
In package 1pc
Casing colour black
Casing material aluminium
Polishing matt
Power supply SOSEN
Impact resistance IK08
Work environment outdoor use
Operation temperature -40 °C ... +50°C
Certificates CE
Warranty 5 years



Outdoor light with an elegant style. Available options: 30W, 40W, 60W, 90W. This light is suitable for poles with a diameter of 60-80mm. It is perfect for driveways, streets, parking lots, and all other outdoor areas that need safe, affordable, and efficient lighting.

Street light Prolumen Hermoso black 230V 40W 6000lm 90° IP66 830

Product code 17044

Brand Prolumen
Supply voltage 230V
Power factor 0.95
Output 40W
Maximum output 40W/1m
Luminous flux 6000lumens
Luminaire’s efficiency 150W
Correlated colour temperature warm white 3000K
Lens angle 90
Source of light LUMILEDS
Cri 80
Sdcm - macadam ellipses 6
Protection class IP66
Lifespan 50000h
Llmf tm21 L90B10 @25°C 50.000h
Height 539.0mm
Diameter 422.0mm
Weight 5.7 kg
In package 1pc
Casing colour black
Casing material aluminium
Polishing matt
Power supply MEAN WELL
Impact resistance IK08
Work environment outdoor use
Operation temperature -40 °C ... +50°C
Certificates CE
Warranty 5 years



Outdoor light with an elegant style. Available options: 30W, 40W, 60W, 90W. This light is suitable for poles with a diameter of 60-80mm. It is perfect for driveways, streets, parking lots, and all other outdoor areas that need safe, affordable, and efficient lighting.

© LED House OÜ, (+372) 56 202 303
Kadaka street 3/3, Tallinn 10621, Estonia, info@ledhouse.ee

Street light Prolumen Hermoso black 230V 60/40/30W 9600lm CRI70 90° IP66 2200K, 3000K, 4000K 3CCT

Product code 22948

Brand Prolumen
Supply voltage 230V
Power factor 0.95
Output 60/40/30W
Maximum output 60W/1m
Luminous flux 9600lumens
Correlated colour temperature 3CCT 2200K, 3000K, 4000K
Lens angle 90
Source of light PHILIPS LED
Cri 70
Sdcm - macadam ellipses 6
Protection class IP66
Lifespan 50000h
Llmf tm21 L90B10 @25°C 50.000h
Height 539.0mm
Diameter 422.0mm
Weight 5.7 kg
In package 1pc
Casing colour black
Casing material aluminium
Polishing matt
Power supply SOSEN
Impact resistance IK08
Work environment outdoor use
Operation temperature -40 °C ... +50°C
Certificates CE
Warranty 5 years



Outdoor light with an elegant style. Available options: 30W, 40W, 60W, 90W. This light is suitable for poles with a diameter of 60-80mm. It is perfect for driveways, streets, parking lots, and all other outdoor areas that need safe, affordable, and efficient lighting.

Street light Prolumen Hermoso black 230V 60W 8400lm 90° IP66 730

Product code 19419

Brand Prolumen
Supply voltage 230V
Power factor 0.95
Output 60W
Maximum output 60W/1m
Luminous flux 8400lumens
Luminaire’s efficiency 140W
Correlated colour temperature warm white 3000K
Lens angle 90
Source of light PHILIPS LED
Cri 70
Sdcm - macadam ellipses 6
Protection class IP66
Lifespan 50000h
Llmf tm21 L90B10 @25°C 50.000h
Height 539.0mm
Diameter 422.0mm
In package 1pc
In box 2pcs
Casing colour black
Casing material aluminium
Polishing matt
Power supply SOSEN
Impact resistance IK08
Work environment outdoor use
Operation temperature -40 °C ... +50°C
Certificates CE
Warranty 5 years



Outdoor light with an elegant style. Available options: 30W, 40W, 60W, 90W. This light is suitable for poles with a diameter of 60-80mm. It is perfect for driveways, streets, parking lots, and all other outdoor areas that need safe, affordable, and efficient lighting.

Street light Prolumen Hermoso black 230V 60W 8400lm 90° IP66 830

Product code 17844

Brand Prolumen
Supply voltage 230V
Power factor 0.95
Output 60W
Maximum output 60W/1m
Luminous flux 8400lumens
Luminaire’s efficiency 140W
Correlated colour temperature warm white 3000K
Lens angle 90
Source of light PHILIPS LED
Cri 80
Sdcm - macadam ellipses 6
Protection class IP66
Lifespan 50000h
Llmf tm21 L90B10 @25°C 50.000h
Height 539.0mm
Diameter 422.0mm
Weight 5.7 kg
In package 1pc
Casing colour black
Casing material aluminium
Polishing matt
Power supply MEAN WELL
Impact resistance IK08
Work environment outdoor use
Operation temperature -40 °C ... +50°C
Certificates CE
Warranty 5 years



Outdoor light with an elegant style. Available options: 30W, 40W, 60W, 90W. This light is suitable for poles with a diameter of 60-80mm. It is perfect for driveways, streets, parking lots, and all other outdoor areas that need safe, affordable, and efficient lighting.

© LED House OÜ, (+372) 56 202 303
Kadaka street 3/3, Tallinn 10621, Estonia, info@ledhouse.ee

Street light Prolumen Hermoso black 230V 90W 13500lm 90° IP66 830

Product code 17845

Brand Prolumen
Supply voltage 230V
Power factor 0.95
Output 90W
Maximum output 90W/1m
Luminous flux 13500lumens
Luminaire’s efficiency 150W
Correlated colour temperature warm white 3000K
Lens angle 90
Source of light LUMILEDS
Cri 80
Sdcm - macadam ellipses 6
Protection class IP66
Lifespan 50000h
Llmf tm21 L90B10 @25°C 50.000h
Height 539.0mm
Diameter 422.0mm
Weight 5.7 kg
In package 1pc
Casing colour black
Casing material aluminium
Polishing matt
Power supply MEAN WELL
Impact resistance IK08
Work environment outdoor use
Operation temperature -40 °C ... +50°C
Certificates CE
Warranty 5 years



Outdoor light with an elegant style. Available options: 30W, 40W, 60W, 90W. This light is suitable for poles with a diameter of 60-80mm. It is perfect for driveways, streets, parking lots, and all other outdoor areas that need safe, affordable, and efficient lighting.

Street light Prolumen Meta 100W 13500lm TP II° No dim 727

Product code 19038

Brand Prolumen
Output 100W
Maximum output 100W/1m
Luminous flux 13500lumens
Luminaire’s efficiency 135W
Correlated colour temperature warm white 2700K
Lens angle TP II
Cri 70
Power supply MEAN WELL
Warranty 5 years
Cable 60mm



LED Street Light for illuminating streets and parking lots. Tube mounting for 60mm tube. This is a project sales product, please inquire about the delivery time and availability from our customer service.

Street light Prolumen Meta 20-50W 6750lm TP II° No dim 727

Product code 19039

Brand Prolumen
Output 20-50W
Maximum output 20-50W/1m
Luminous flux 6750lumens
Correlated colour temperature warm white 2700K
Lens angle TP II
Cri 70
Power supply SOSEN
Warranty 5 years
Cable 60mm



LED Street Light for illuminating streets and parking lots. Tube mounting for 60mm tube. This is a project sales product, please inquire about the delivery time and availability from our customer service.

Street light Prolumen Meta 20-50W 7500lm TP II° No dim 740

Product code 19041

Brand Prolumen
Output 20-50W
Maximum output 20-50W/1m
Luminous flux 7500lumens
Correlated colour temperature pure white 4000K
Lens angle TP II
Cri 70
Power supply SOSEN
Warranty 5 years
Cable 60mm



LED Street Light for illuminating streets and parking lots. Tube mounting for 60mm tube. This is a project sales product, please inquire about the delivery time and availability from our customer service.

Street light Prolumen Meta 40-100W 13500lm TP II° No dim 727

Product code 19040

Brand Prolumen
Output 40-100W
Maximum output 40-100W/1m
Luminous flux 13500lumens
Correlated colour temperature warm white 2700K
Lens angle TP II
Cri 70
Power supply SOSEN
Warranty 5 years
Cable 60mm



LED Street Light for illuminating streets and parking lots. Tube mounting for 60mm tube. This is a project sales product, please inquire about the delivery time and availability from our customer service.

Street light Prolumen Poseidon 230V 40W 7200lm 115x155° 740

Product code 19044

Brand Prolumen
Supply voltage 230V
Power factor 0.95
Output 40W
Maximum output 40W/1m
Luminous flux 7200lumens
Luminaire’s efficiency 180W
Correlated colour temperature pure white 4000K
Lens angle 115x155
Cri 70
Height 108.0mm
Width 174.0mm
Length 493.0mm
In box 8pcs
Power supply Without driver
Impact resistance IK08
Warranty 5 years



LED Street Light for illuminating streets and parking lots. Tube mounting for 60mm tube. This is a project sales product, please inquire about the delivery time and availability from our customer service.

Street light Prolumen Poseidon 230V 80W 14400lm 115x155° 740

Product code 19045

Brand Prolumen
Supply voltage 230V
Power factor 0.90
Output 80W
Maximum output 80W/1m
Luminous flux 14400lumens
Luminaire’s efficiency 180W
Correlated colour temperature pure white 4000K
Lens angle 115x155
Cri 70
Sdcm - macadam ellipses 6
Lifespan 50000h
Llmf tm21 L90B10 @25°C 50.000h
Height 108.0mm
Width 200.0mm
Length 562.0mm
In box 6pcs
Power supply Without driver
Warranty 5 years



LED Street Light for illuminating streets and parking lots. Tube mounting for 60mm tube. This is a project sales product, please inquire about the delivery time and availability from our customer service.

Street light Prolumen Poseidon 40W 6400lm TP III° 727

Product code 19042

Brand Prolumen
Output 40W
Maximum output 40W/1m
Luminous flux 6400lumens
Luminaire’s efficiency 160W
Correlated colour temperature warm white 2700K
Lens angle TP III
Cri 70
Power supply Without driver
Warranty 5 years



LED Street Light for illuminating streets and parking lots. Tube mounting for 60mm tube. This is a project sales product, please inquire about the delivery time and availability from our customer service.

Street light Prolumen Poseidon 75W 13500lm TP III° 740

Product code 19377

Brand Prolumen
Output 75W
Maximum output 75W/1m
Luminous flux 13500lumens
Luminaire’s efficiency 180W
Correlated colour temperature pure white 4000K
Lens angle TP III
Cri 70
Power supply Without driver
Warranty 5 years

LED Street Light for illuminating streets and parking lots. Tube mounting for 60mm tube. This is a project sales product, please inquire about the delivery time and availability from our customer service.



Street light Prolumen Poseidon 80W 12800lm TP III° 727

Product code 19043

Brand Prolumen
Output 80W
Maximum output 80W/1m
Luminous flux 12800lumens
Luminaire’s efficiency 160W
Correlated colour temperature warm white 2700K
Lens angle TP III
Cri 70
Power supply Without driver
Warranty 5 years

LED Street Light for illuminating streets and parking lots. Tube mounting for 60mm tube. This is a project sales product, please inquire about the delivery time and availability from our customer service.



Street light Prolumen Poseidon gray 230V 100W 13000lm 60x140° IP66 740

Product code 14977

Brand Prolumen
Supply voltage 230V
Output 100W
Maximum output 100W/1m
Luminous flux 13000lumens
Luminaire’s efficiency 130W
Correlated colour temperature pure white 4000K
Lens angle 60x140
Source of light CREE LED
Cri 70
Sdcm - macadam ellipses 6
Protection class IP66
Lifespan 50000h
Llmf tm21 L90B10 @25°C 50.000h
Height 100.0mm
Width 235.0mm
Length 610.0mm
Installation opening diameter 60mm
Casing colour gray
Casing material aluminium
Polishing matt
Power supply MEAN WELL
Impact resistance IK08
Work environment outdoor use
Operation temperature -40°C - +70°C
Certificates CE, ENEC



Street light Prolumen Poseidon gray 230V 100W 15000lm IP66 DALI 840

Product code 16972 DALI dimmable

Brand Prolumen
Supply voltage 230V
Dimmable DALI
Output 100W
Maximum output 100W/1m
Luminous flux 15000lumens
Luminaire’s efficiency 150W
Correlated colour temperature pure white 4000K
Source of light CREE LED
Cri 80
Sdcm - macadam ellipses 6
Protection class IP66
Lifespan 50000h
Llmf tm21 L90B10 @25°C 50.000h
Height 109.0mm
Width 240.0mm
Length 613.0mm
Installation opening diameter 60mm
Weight 4.57 kg
Package weight 5.27 kg
In package 1pc
Casing colour gray
Casing material aluminium
Polishing matt
Impact resistance IK08
Work environment outdoor use
Operation temperature -40°C - +70°C
Certificates CE, ENEC

LED Street Light for illuminating streets and parking lots. Tube mounting for 60mm tube. This is a project sales product, please inquire about the delivery time and availability from our customer service.



Street light Prolumen Poseidon gray 230V 24W 3600lm 150x150° IP66 830

Product code 16250

Brand Prolumen
Supply voltage 230V
Power factor 0.90
Output 24W
Maximum output 24W/1m
Luminous flux 3600lumens
Luminaire’s efficiency 150W
Correlated colour temperature warm white 3000K
Lens angle 150x150
Source of light CREE LED
Cri 80
Sdcm - macadam ellipses 6
Protection class IP66
Lifespan 50000h
Llmf tm21 L90B10 @25°C 50.000h
Height 100.0mm
Width 200.0mm
Length 570.0mm
Installation opening diameter 60mm
Casing colour gray
Casing material aluminium
Polishing matt
Power supply MEAN WELL
Impact resistance IK08
Work environment outdoor use
Operation temperature -40°C - +70°C
Certificates CE, ENEC



LED Street Light for illuminating streets and parking lots. Tube mounting for 60mm tube. This is a project sales product, please inquire about the delivery time and availability from our customer service.

Street light Prolumen Ryder black 230V 70W 7700lm IP66 DALI 830

Product code 18154 DALI dimmable

Brand Prolumen
Supply voltage 230V
Power factor 0.95
Dimmable DALI
Output 70W
Maximum output 70W/1m
Luminous flux 7700lumens
Luminaire’s efficiency 110W
Correlated colour temperature warm white 3000K
Source of light LUMILEDS
Cri 80
Sdcm - macadam ellipses 6
Protection class IP66
Lifespan 100000h
Llmf tm21 L80B10 @25°C 100.000h
Height 282.0mm
Diameter 610.0mm
Casing colour black
Casing material aluminium
Polishing matt
Power supply SOSEN
Impact resistance IK08
Work environment outdoor use
Operation temperature -40 °C ... +50°C
Certificates CE
Warranty 5 years



A street light that makes moving in urban spaces safe even in the dark of night! It is perfect for driveways, streets, parking lots, and all other outdoor areas that need safe, affordable, and efficient lighting. Protection classes IP66 and IK08 ensure the fixture's durability and long life in outdoor conditions. Additionally, the light is ideal for collaboration with security cameras - see the product specifications for more details. Furthermore, the maintenance process of the light has been made exceptionally easy - allowing you to save on labor and time! This feature is ensured by the removable electric plate, which makes connecting wires during installation particularly convenient.

Street light Street Master gray 230V 35W 5950lm 155x80° IP66 DALI 740

Product code 17782 **DALI dimmable**

Supply voltage 230V
Power factor 0.98
Dimmable DALI
Output 35W
Maximum output 35W/1m
Luminous flux 5950lumens
Luminaire’s efficiency 170W
Correlated colour temperature pure white 4000K
Lens angle 155x80
Cri 70
Protection class IP66
Lifespan 80000h
Height 102.0mm
Width 209.0mm
Length 507.0mm
Weight 3.3 kg
In package 1pc
Casing colour gray
Casing material aluminium
Polishing matt
No. of switches 30000pcs
Impact resistance IK09
Work environment outdoor use
Operation temperature -30° - +45°C
Certificates CE, ENEC
Warranty 5 years




